



Shenzhen Absen Optoelectronic Co., Ltd.

A2715 V3- Specifications

Version: V20230817

| Parameter | | Value |
|--------------------------|--|-------------------------------------|
| Physical Parameter | LED Type | Black SMD 3in1 1010 |
| | Pixel Pitch (mm) | 1.58 |
| | Panel Dimensions (WxHxD)/(mm) | 610x343x44.5 |
| | Pixel Per Panel | 384x216 |
| | Panel Weight (kg) | 5 |
| | Panel Material | Die Casting Aluminum |
| | Module Dimensions (WxH)/(mm) | 152.5x343 |
| Optoelectronic Parameter | Brightness (nit) | 800 |
| | Refresh Rate (Hz) | 3840 |
| | Gray scale (Bit) | 16 |
| | Contrast Ratio | 4500:1 |
| | Color Temperature (K) | 6500 |
| | Viewing Angle (H/V) (°) | 160/160 |
| | Driving Type | 1/48 |
| | AC Operating Voltage (V) | 100~240 |
| | Power Consumption (Max./Avg.)(W/m ²) | 540/180 |
| Application Parameter | Storage Temperature (°C) | -40~+60 |
| | Operating Temperature (°C) | -10~+40 |
| | Storage Humidity (RH) | 10%~85% |
| | Operating Humidity (RH) | 10%~80% |
| | IP Rating (Front/Rear) | IP40/IP21 |
| | Module Maintenance | Front |
| | PSU & Others Maintenance | Front |
| | Panel Installation Type | Front/Rear |
| | Max Rigging QTY. | 15 |
| | Certificate | CCC,CE,ETL,ROHS,FCC,TUV,EMC CLASS B |

Remark: Power consumption tolerance: $\pm 15\%$, according to the actual situation.

SHENZHEN ABSEN OPTOELECTRONIC CO., LTD 2001-2022 ALL RIGHTS RESERVED