

Absen Shenzhen Absen Optoelectronic Co., Ltd.
Absenicon C138-Specifications

Version: V20190328

| Parameter | | Value |
|---------------------------------|--|------------------------------|
| Physical Parameter | Product Model | C138 |
| | Display Diagonal Size(inch) | 137.5 |
| | LED Type | black SMD 1010 |
| | Pixel Pitch(mm) | 1.58 |
| | Display resolution | 1920×1080 |
| | Display Size(WxH)/(mm) | 3050 x 1715 |
| | Display Weight(kg) (Excluding frame and trim) | 150 |
| Optoelectronic Parameter | Standard Brightness (nit) | 350 |
| | Refresh Rate (Hz) | 1920 |
| | Contrast Ratio | 4000:1 |
| | Color Temperature (K) | 6500 |
| | Viewing Angle (H/V) (°) | 160/140 |
| | AC Operating Voltage (V) | 100~240 |
| | Power Consumption (Max./Avg.)(W per set) | 1800/600 |
| Application Parameter | Storage Temperature (°C) | - 40~ + 60 |
| | Operating Temperature (°C) | - 10~ + 40 |
| | Storage Humidity (RH) | 10 % 85 % |
| | Operating Humidity (RH) | 10 % ~80 % |
| | IP Rating (Front/Rear) | IP40/IP21 |
| | LED Lifetime (H) | 100000 |
| | Maintenance | Front |
| | Certificate | Every single panel FCC + ETL |

Remark :Power consumption tolerance: ±15%, according to the actual situation.