



Shenzhen Absen Optoelectronic Co., Ltd.

Absenicon3.0 C165 U- Specifications

Version : V20221011

Parameter		Value			
Physical Parameter	Product Model	Absenicon3.0 C165 U			
	Display Diagonal Size (Inch)	165			
	LED Type	1515			
	Display Size (W×H) / (mm)	3670*2173*28.5			
	Pixel Per Display (Pixels)	1920*1080			
	Display Weight (kg) (Including frame and rim)	wall mounting	Hanging	wall to floor	mobile stand
	218				
Optoelectronic Parameter	Standard Brightness (nit)	350			
	Refresh Rate (Hz)	3,840			
	Contrast Ratio	4000:1			
	Color Temperature (K)	6500			
	Viewing Angle(H/V) (°)	160/140			
	AC Operating Voltage (V)	200 ~ 240			
	Power Consumption (Max./Avg.) (W)	1800/600			
Application Parameter	Applying Space	100			
	Storage Temperature (°C)	-40 ~ +60			
	Operating Temperature (°C)	-10 ~ +40			
	Storage Humidity (RH)	10% ~ 85%			
	Operating Humidity (RH)	10% ~ 80%			
	IP Rating (Front/Rear)	IP40/IP21			
	Maintenance	Front			
	Certificate	ETL,FCC			

Remark:Power consumption tolerance: ±15%, according to the actual situation.

