

Absenicon C Slim

High Screen-to-body Ratio Screen









Easy installation/ maintenance

98% screen-to-body ratio

Ultra-slim frame

600nits brightness

Key Features



Highly Integrated Design

Far more than just a screen, the C Slim screen is highly integrated, including controller, modules, cabinets, installation mounts, cables and all necessary display elements needed for the installation.



Ultra-slim Frame

With a 5mm ultra-slim frame, the screen-to-body ratio reaches 98%, providing an immersive experience for all the viewers.

*The upper, left, right and bottom bezel are 5/5/5/23mm respectively *The thinnest part of the screen body is only 28.5mm



Refresh Your Vision

Experience stunning visual performance with Absenicon C Slim series. Every dark or bright detail looks vivid and clear with its 110% NTSC level colour gamut and 600nits brightness.



Easy and Reliable Content Sharing

Absenicon supports screen mirroring through computer, mobile phone and PAD screen. The screen share up to 4 devices at one time wirelessly, allowing creativity display simultaneously.



Smart Control

Absenicon brings the connectivity of smart TVs to a larger more dynamic LED display.And multiple functions can be realized through remote control.



Easy Installation and Maintenance

Support wall mounting, mobile stand installation, suitable for different indoor space environment. Simple installation process saves time and labor. In case of the LED module or internal component fails, it can be maintained from the front.

*C165S only supports wall mounted installation

Product Parameters

Parameter	C110S		C138S		C165S
Diagonal Size (inches)	1110"		138"		165"
Screen Dimensions (W x H)(mm)	2440*1372		3050*1715		3660*2058
Pixel Pitch(mm)	1.27		1.58		1.9
Screen Dimensions Including Bezel (W x HXD)(mm)	2450x1400x28.5		3060x1743x28.5		3670x2068x28.5
Screen Resolution (dots)	1920x1080		1920x1080		1920x1080
Installation	Wall mounting	Mobile stand	Wall mounting	Mobile stand	Wall mounting
Weight (kg)	117	139	175	197	247
Aspect Ratio	16:9		16:9		16:9
Brightness (nit)	600		600		600
Contrast Ratio	4000:1		5000:1		4000:1
Grayscale (bit)	14		14		14
Refresh Rate (Hz)	3840		3840		3840
Viewing Angle (Horizontal/Vertical)(°)	160/140		160/140		160/140
Ave./Max. Power Consumption (W)	584/1750		667/2000		800/2400
Android System	Android 8.0		Android 8.0		Android 8.0
Processor Core	Main frequency 1.7G 64-bit quad-core processor				
System capacity	4GB+16GB				
Control Interface	MiniUSB*1, RJ45*1				
Input/output Interface	HDMI2.0*3, USB2.0*1, USB3.0*1, Audio OUT*1, SPDIF OUT*1, RJ45*1				
Windows System	Optional				
Certification	FCC, CE				

*The thinnest part of the screen body is only 28.5mm



HQ Office

7120 Lake Ellenor Dr Orlando, FL 32809 407.203.8870 info@usabsen.com www.usabsen.com East Service Center&Warehouse 7307 Presidents Drive, Orlando, FL 32809 West Service Center & Showroom 20311 Valley Blvd Suite J, Walnut, CA 91789



in LinkedIn: @AbsenInc
IG: @absen_inc