

# A Complete Audio System Built Into a Stylish Adjustable Lectern

Covers Audiences up to 1,500. Adjusts from 39 to 45 inches!

**Quick Look:**  
**Wired, Wireless, Non-Sound**  
**Audience Size: 1,500**  
**Room Size: 15,000 sq. ft.**  
**SPL 106 dB**  
**Built-in Flush Mount Amp**  
**2 Jensen Speakers**  
**Dynamic Hot Gooseneck Mic**  
**Storage Space**  
**High Pressure Laminate**  
**Made in USA**  
**6 Year Warranty**



Color choices:

	Light oak,		Walnut,
	Medium oak,		Mahogany.

High pressure laminate with scratch-resistant finish.



Lectern easily adjusts from 39-in. to 45-in.



**UPGRADE YOUR LECTERN - INCREASE YOUR SOUND COVERAGE**  
 Increase audience coverage by adding our **Dual Module Companion Speaker (S1201)** - It can be placed inside the lectern or mounted remotely on an optional tripod (**S1090**) giving you a **total of 4 speakers**. All items sold separately.



## Features / Specifications

- ✓ Adjust the height with our smooth, effortless pneumatic dial. The reading table height can be set between 39-in. and 45-in. (measured from front of lectern)
- ✓ Exclusive built-in flush mount **Amplivox 50 watt multimedia stereo amplifier**. Battery powered or AC.
- ✓ Sculpted radius base with four hidden casters, 2 locking.
- ✓ Auxiliary input stereo jack with separate volume and tone controls for a CD player, tape player or LCD computer projector.
- ✓ Line out jack for a tape recorder. You can record your presentation as it is happening.
- ✓ 3 mic inputs (dynamic, condenser with phantom power, wireless) can be used at the same time.
- ✓ 2 speaker jacks for a total of 4 speakers possible (using a Y-connector).
- ✓ **Dual Wireless Capability** - SW wireless series **SW805A Amplifier** with built-in wireless receiver allows 2 people to be wireless simultaneously with second wireless mic kit.
- ✓ On-off switch with LED power indicator light. 1 jack for optional external AC Adapter/Recharger.
- ✓ Dimensions: 15-in. D x 21-in. W x 45-in. H Weight: 85 lbs.
- ✓ Runs on 10 D-cell alkaline batteries for up to 200 hours of talk time, S1460 International AC Adapter/Recharger (110/240V; 50/60Hz), S1465 NiCad Rechargeable Battery Pack (requires S1460). All Sold Separately.
- ✓ Front Panel Dimensions for Company Engravings/logos: 22-1/4"W x 7-3/4"H

	Model #	Shpg. Wt.	MSRP
<b>Executive Adjustable Sound Column Lectern</b> Includes 50 Watt Amp, 2 built-in speakers, dynamic gooseneck mic, reading table 20 3/4-in. W x 16 1/2-in. D	<b>S505A</b>	<b>85 lbs.</b>	<b>1,488.00</b>
<b>Executive Adjustable Wireless Sound Column Lectern</b> As above with built-in wireless receiver: Plus your choice of wireless lapel/headset mic or handheld mic and transmitter, reading table 20 3/4-in. W x 16 1/2-in. D	<b>SW505A</b>	<b>85 lbs.</b>	<b>1,796.00</b>
<b>Non-Sound Executive Adjustable Sound Column Lectern</b> reading table 20 3/4-in. W x 16 1/2-in. D	<b>W505A</b>	<b>75 lbs.</b>	<b>631.00</b>
<b>Dual Module Companion Speaker</b> - Two 6-in.x 8-in. speakers, 40 ft. cable, (14-in.x10-in.x 6 1/2-in.)	<b>S1201</b>	<b>15 lbs.</b>	<b>252.00</b>
<b>Reading Lamp</b> - Clip-on, AC, 25 watt bulb, 8-ft. cord	<b>S1100</b>	<b>1 lbs.</b>	<b>67.00</b>
<b>Clip on Gig Light</b> - Battery powered clip on Halogen light. Requires 4 AA batteries not included.	<b>S1135</b>	<b>2 lbs.</b>	<b>76.00</b>
<b>Compact Tripod 1-3/8-in</b> - Adjustable, 28-in. to 49-in., 27-in. folded	<b>S1090</b>	<b>4 lbs.</b>	<b>125.00</b>
<b>Lectern Protective Cover</b> - Brown vinyl. Water resistant. Fits 45-in.H x 27-1/2-in.W x 25-in.D.	<b>S1972</b>	<b>7 lbs.</b>	<b>130.00</b>

**AMPLIFIER POWER SOURCE NOT INCLUDED: Powered by 10 D-cell alkaline batteries for up to 200 hours talk time; S1460 International AC Adapter/ Recharger; S1465 Rechargeable NiCad Battery Pack for up to 20 hours before recharging (requires S1460). All sold separately.**

<b>International AC Adapter/Recharger</b> - 110/240 volt, 50/60Hz. 15-volt center positive, 2 amps, 7.5-ft cord. For S805A/SW805A amplifiers only.	<b>S1460</b>	<b>2 lbs.</b>	<b>131.00</b>
<b>NiCad Battery Pack</b> - Heavy duty rechargeable; for S805A/SW805A amps - requires S1460 AC Adapter/Recharger.	<b>S1465</b>	<b>4 lbs.</b>	<b>200.00</b>