

## WINDOW AIR CONDITIONERS

5,000 / 6,000 / 8,000 / 10,000 / 12,000 / 15,000 / 24,000 BTUs



### 2AWMC5000MSA

- Manual adjustable temperature control
- Slide-out washable filter
- 2-speed rotary dials
- 2-way air direction control
- Window mounting kit included
- ISTA 6A packaging



	1AW5000MSA	1AW6000DA
<b>UPC</b>	850012484530	850012484547
<b>POWER SUPPLY (V)</b>	115	115
<b>COOLING CAPACITY (BTU)</b>	5,000	6,000
<b>COVERAGE (SQ. FT.)</b>	150	250
<b>CEER</b>	11	11
<b>ENERGY STAR RATED</b>	No	No
<b>FAN SPEEDS (COOL/FAN)</b>	2/2	3/3
<b>AMPS</b>	3.9	4.8
<b>WATTS</b>	451	541
<b>REMOTE</b>	No	Yes
<b>WINDOW WIDTH (MIN./MAX.) (IN.)</b>	26/36	26/36
<b>WINDOW HEIGHT (MIN.) (IN.)</b>	14 <sup>1</sup> / <sub>2</sub>	14 <sup>1</sup> / <sub>2</sub>
<b>UNIT DIMENSIONS (WxHxD) (IN.)</b>	16 x 12 <sup>1</sup> / <sub>2</sub> x 15 <sup>1</sup> / <sub>4</sub>	16 x 12 <sup>1</sup> / <sub>2</sub> x 15 <sup>1</sup> / <sub>4</sub>
<b>PKG. DIMENSIONS (WxHxD) (IN.)</b>	18 <sup>1</sup> / <sub>4</sub> x 16 x 17	18 <sup>1</sup> / <sub>4</sub> x 16 x 17
<b>STUFFING QTY. (20'/40'/40' HQ)</b>	325/675/810	325/675/810
<b>WEIGHT (NET/GROSS) (LBS.)</b>	37.25/42	40/45
<b>REFRIGERANT</b>	R32	R410A

#### OUTLET CONFIGURATION



15 AMP 115V



15 AMP 115V



### 1AW6000DA

- Electronic controls
- Full range air direction control
- Temperature output range of 61°F-88°F (16°C-31°C)
- Auto, Sleep, Dry & ECO modes
- Remote control with built-in thermostat
- 24-hour timer
- Auto restart function
- Tilt-out, removable, and washable filter
- Window mounting kit included
- ISTA 6A packaging











**1AW8000DA / 2AW10000DA  
2AW12000DA / 1AW15000EA  
1AW18000EA / 1AW24000EA**

- Electronic controls
- Full range air direction control
- Temperature output range of 61°F-88°F (16°C-31°C)
- Auto, Sleep, Dry & ECO modes
- Remote control with built-in thermostat
- 24-hour timer
- Auto restart function
- Tilt-out, removable, and washable filter
- Window mounting kit included
- ISTA 6A packaging



	1AW8000DA	2AW10000DA	2AW12000DA	1AW15000EA	1AW18000EA	1AW24000EA
<b>UPC</b>	850012484554	853057008686	853057008808	850012484561	850012484578	850012484585
<b>POWER SUPPLY (V)</b>	115	115	115	115	230	230
<b>COOLING CAPACITY (BTU)</b>	8,000	10,000	12,000	15,000	18,000	24,000
<b>COVERAGE (SQ. FT.)</b>	350	450	550	700	1000	1500
<b>CEER</b>	10.9	10.9	10.9	11.8	11.8	10.3
<b>ENERGY STAR RATED</b>	<b>No</b>	<b>No</b>	<b>No</b>	<b>No</b>	<b>No</b>	<b>No</b>
<b>FAN SPEEDS (COOL/FAN)</b>	3/3	3/3	3/3	3/3	3/3	3/3
<b>AMPS</b>	6.2	8.3	9.6	11	7.1	11
<b>WATTS</b>	727	909	1091	1270	1525	2320
<b>REMOTE</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>WINDOW WIDTH (MIN./MAX.) (IN.)</b>	26/36	26/36	26/36	28/41	28/41	30/41
<b>WINDOW HEIGHT (MIN.) (IN.)</b>	14 <sup>1/2</sup>	16	16	19	19	19 <sup>1/2</sup>
<b>UNIT DIMENSIONS (WxHxD) (IN.)</b>	18 <sup>3/4</sup> x 13 <sup>1/2</sup> x 15 <sup>3/4</sup>	19 <sup>3/4</sup> x 15 <sup>1/4</sup> x 21 <sup>1/2</sup>	19 <sup>3/4</sup> x 15 <sup>1/4</sup> x 21 <sup>1/2</sup>	23 <sup>3/4</sup> x 20 x 25 <sup>1/2</sup>	23 <sup>3/4</sup> x 20 x 25 <sup>1/2</sup>	26 <sup>1/2</sup> x 18 <sup>3/4</sup> x 27
<b>PKG. DIMENSIONS (WxHxD) (IN.)</b>	21 <sup>1/2</sup> x 16 x 17 <sup>3/4</sup>	24 <sup>1/2</sup> x 18 <sup>1/2</sup> x 22 <sup>3/4</sup>	24 <sup>1/2</sup> x 18 <sup>1/2</sup> x 22 <sup>3/4</sup>	30 <sup>1/2</sup> x 21 <sup>1/4</sup> x 26 <sup>1/2</sup>	30 <sup>1/2</sup> x 21 <sup>1/4</sup> x 26 <sup>1/2</sup>	31 <sup>1/2</sup> x 21 <sup>3/4</sup> x 29 <sup>3/4</sup>
<b>STUFFING QTY. (20'/40'/40' HQ)</b>	265/550/656	144/304/380	144/304/380	96/216/268	96/216/268	84/188/233
<b>WEIGHT (NET/GROSS) (LBS.)</b>	48.5/55	61/68	68.5/76	106/117	117/128	130/142
<b>REFRIGERANT</b>	R410A	R410A	R410A	R410A	R410A	R410A
<b>OUTLET CONFIGURATION</b>	 15 AMP 115V	 15 AMP 115V	 15 AMP 115V	 15 AMP 115V	 20 AMP 230V	 20 AMP 230V

AW/SS\_WAC\_12162020