

WINDOW AIR CONDITIONERS

5,000 / 6,000 / 8,000 / 10,000 / 12,000 / 15,000 / 24,000 BTUs



2AWMC5000MSA

- Manual adjustable temperature control
- Slide-out washable filter
- 2-speed rotary dials
- 2-way air direction control
- Window mounting kit included
- ISTA 6A packaging



| | 1AW5000MSA | 1AW6000DA |
|---------------------------------------|--|--|
| UPC | 850012484530 | 850012484547 |
| POWER SUPPLY (V) | 115 | 115 |
| COOLING CAPACITY (BTU) | 5,000 | 6,000 |
| COVERAGE (SQ. FT.) | 150 | 250 |
| CEER | 11 | 11 |
| ENERGY STAR RATED | No | No |
| FAN SPEEDS (COOL/FAN) | 2/2 | 3/3 |
| AMPS | 3.9 | 4.8 |
| WATTS | 451 | 541 |
| REMOTE | No | Yes |
| WINDOW WIDTH (MIN./MAX.) (IN.) | 26/36 | 26/36 |
| WINDOW HEIGHT (MIN.) (IN.) | 14 ¹ / ₂ | 14 ¹ / ₂ |
| UNIT DIMENSIONS (WxHxD) (IN.) | 16 x 12 ¹ / ₂ x 15 ¹ / ₄ | 16 x 12 ¹ / ₂ x 15 ¹ / ₄ |
| PKG. DIMENSIONS (WxHxD) (IN.) | 18 ¹ / ₄ x 16 x 17 | 18 ¹ / ₄ x 16 x 17 |
| STUFFING QTY. (20'/40'/40' HQ) | 325/675/810 | 325/675/810 |
| WEIGHT (NET/GROSS) (LBS.) | 37.25/42 | 40/45 |
| REFRIGERANT | R32 | R410A |

OUTLET CONFIGURATION



15 AMP 115V



15 AMP 115V



1AW6000DA

- Electronic controls
- Full range air direction control
- Temperature output range of 61°F-88°F (16°C-31°C)
- Auto, Sleep, Dry & ECO modes
- Remote control with built-in thermostat
- 24-hour timer
- Auto restart function
- Tilt-out, removable, and washable filter
- Window mounting kit included
- ISTA 6A packaging











**1AW8000DA / 2AW10000DA
2AW12000DA / 1AW15000EA
1AW18000EA / 1AW24000EA**

- Electronic controls
- Full range air direction control
- Temperature output range of 61°F-88°F (16°C-31°C)
- Auto, Sleep, Dry & ECO modes
- Remote control with built-in thermostat
- 24-hour timer
- Auto restart function
- Tilt-out, removable, and washable filter
- Window mounting kit included
- ISTA 6A packaging



| | 1AW8000DA | 2AW10000DA | 2AW12000DA | 1AW15000EA | 1AW18000EA | 1AW24000EA |
|---------------------------------------|--|--|--|--|--|--|
| UPC | 850012484554 | 853057008686 | 853057008808 | 850012484561 | 850012484578 | 850012484585 |
| POWER SUPPLY (V) | 115 | 115 | 115 | 115 | 230 | 230 |
| COOLING CAPACITY (BTU) | 8,000 | 10,000 | 12,000 | 15,000 | 18,000 | 24,000 |
| COVERAGE (SQ. FT.) | 350 | 450 | 550 | 700 | 1000 | 1500 |
| CEER | 10.9 | 10.9 | 10.9 | 11.8 | 11.8 | 10.3 |
| ENERGY STAR RATED | No | No | No | No | No | No |
| FAN SPEEDS (COOL/FAN) | 3/3 | 3/3 | 3/3 | 3/3 | 3/3 | 3/3 |
| AMPS | 6.2 | 8.3 | 9.6 | 11 | 7.1 | 11 |
| WATTS | 727 | 909 | 1091 | 1270 | 1525 | 2320 |
| REMOTE | Yes | Yes | Yes | Yes | Yes | Yes |
| WINDOW WIDTH (MIN./MAX.) (IN.) | 26/36 | 26/36 | 26/36 | 28/41 | 28/41 | 30/41 |
| WINDOW HEIGHT (MIN.) (IN.) | 14 ^{1/2} | 16 | 16 | 19 | 19 | 19 ^{1/2} |
| UNIT DIMENSIONS (WxHxD) (IN.) | 18 ^{3/4} x 13 ^{1/2} x 15 ^{3/4} | 19 ^{3/4} x 15 ^{1/4} x 21 ^{1/2} | 19 ^{3/4} x 15 ^{1/4} x 21 ^{1/2} | 23 ^{3/4} x 20 x 25 ^{1/2} | 23 ^{3/4} x 20 x 25 ^{1/2} | 26 ^{1/2} x 18 ^{3/4} x 27 |
| PKG. DIMENSIONS (WxHxD) (IN.) | 21 ^{1/2} x 16 x 17 ^{3/4} | 24 ^{1/2} x 18 ^{1/2} x 22 ^{3/4} | 24 ^{1/2} x 18 ^{1/2} x 22 ^{3/4} | 30 ^{1/2} x 21 ^{1/4} x 26 ^{1/2} | 30 ^{1/2} x 21 ^{1/4} x 26 ^{1/2} | 31 ^{1/2} x 21 ^{3/4} x 29 ^{3/4} |
| STUFFING QTY. (20'/40'/40' HQ) | 265/550/656 | 144/304/380 | 144/304/380 | 96/216/268 | 96/216/268 | 84/188/233 |
| WEIGHT (NET/GROSS) (LBS.) | 48.5/55 | 61/68 | 68.5/76 | 106/117 | 117/128 | 130/142 |
| REFRIGERANT | R410A | R410A | R410A | R410A | R410A | R410A |
| OUTLET CONFIGURATION |  15 AMP 115V |  15 AMP 115V |  15 AMP 115V |  15 AMP 115V |  20 AMP 230V |  20 AMP 230V |