

WINDOW AIR CONDITIONERS



BTUS 5,000 / 6,000 / 8,000 / 10,000 / 12,000 / 15,000 / 24,000



2AW500MSA

- Manual adjustable temperature control
- Slide-out washable filter
- 2-speed rotary dials
- 2-way air direction control
- Window mounting kit included
- ISTA 6A packaging



	2AW500MSA	2AW600DA
UPC	850012484202	850012484141
POWER SUPPLY (V)	115	115
COOLING CAPACITY (BTU)	5,000	6,000
COVERAGE (SQ. FT.)	150	250
CEER	11	11
ENERGY STAR RATED	No	No
FAN SPEEDS (COOL/FAN)	2/2	3/3
AMPS	4.5	5
WATTS	460	490
REMOTE	No	Yes
WINDOW WIDTH (MIN./MAX.) (IN.)	23/34	26/36
WINDOW HEIGHT (MIN.) (IN.)	14½	14½
UNIT DIMENSIONS (W×H×D) (IN.)	16 × 12 × 13½	16 × 12½ × 15¼
PKG. DIMENSIONS (W×H×D) (IN.)	18¼ × 15¼ × 14¾	18¼ × 16 × 17
STUFFING QTY. (20'/40'/40' HQ)	-/-/918	325/675/810
WEIGHT (NET/GROSS) (LBS.)	36/42	40/45
REFRIGERANT	R32	R32
OUTLET CONFIGURATION		



2AW600DA

- Electronic controls
- Full range air direction control
- Temperature output range of 61°F-88°F (16°C-31°C)
- Auto, Sleep, Dry & ECO modes
- Remote control with built-in thermostat
- 24-hour timer
- Auto restart function
- Tilt-out, removable, and washable filter
- Window mounting kit included
- ISTA 6A packaging





2AW8000DA / 3AW10000DA / 3AW12000DA / 2AW15000EA / 2AW18000EA / 2AW24000EA

- Electronic controls
- Full range air direction control
- Temperature output range of 61°F-88°F (16°C-31°C)
- Auto, Sleep, Dry & ECO modes
- Remote control with built-in thermostat
- 24-hour timer
- Auto restart function
- Tilt-out, removable, and washable filter
- Window mounting kit included
- ISTA 6A packaging



	2AW8000DA	3AW10000DA	3AW12000DA	2AW15000EA	2AW18000EA	2AW24000EA
UPC	850012484158	850012484172	850012484189	850012484103	850012484110	850012484127
POWER SUPPLY (V)	115	115	115	115	230	230
COOLING CAPACITY (BTU)	8,000	10,000	12,000	15,000	18,000	24,000
COVERAGE (SQ. FT.)	350	450	550	700	1000	1500
CEER	10.9	10.9	10.9	11.8	11.8	10.3
ENERGY STAR RATED	No	No	No	No	No	No
FAN SPEEDS (COOL/FAN)	3/3	3/3	3/3	3/3	3/3	3/3
AMPS	7.0	8.0	9.5	12.8	9.0	13.0
WATTS	740	850	990	1270	1500	2360
REMOTE	Yes	Yes	Yes	Yes	Yes	Yes
WINDOW WIDTH (MIN./MAX.) (IN.)	26/36	26/36	26/36	28/41	28/41	30/41
WINDOW HEIGHT (MIN.) (IN.)	14½	16	16	19	19	19½
UNIT DIMENSIONS (W×H×D) (IN.)	18¾ × 13½ × 15¾	19¾ × 15¼ × 21½	19¾ × 15¼ × 21½	23¾ × 20 × 25½	23¾ × 20 × 25½	26½ × 18¾ × 27
PKG. DIMENSIONS (W×H×D) (IN.)	21½ × 16 × 17¾	24½ × 18½ × 22¾	24½ × 18½ × 22¾	30½ × 21¼ × 26½	30½ × 21¼ × 26½	31½ × 21¼ × 29¾
STUFFING QTY. (20'/40'/40' HQ)	265/550/656	144/304/380	144/304/380	96/216/268	96/216/268	84/188/233
WEIGHT (NET/GROSS) (LBS.)	48.5/55	61/68	68.5/76	106/117	117/128	130/142
REFRIGERANT	R32	R32	R32	R32	R32	R32
OUTLET CONFIGURATION	