THROUGH-THE-WALL AIR CONDITIONER

WITH HEAT | 10,000 BTU | ELECTRONIC



CHOOSING THE RIGHT AIR CONDITIONER MEASURE AREA OF THE ROOM MATCH ROOM SIZE WITH CORRECT BTUs SQ. FT. ROOM SIZE **BTUs** 5,000 150 10' × 15' 250 10' × 25' 6,000 350 17' × 20' 8,000 450 10,000 15' × 30' 550 20' × 27' 12,000 700 15,000 20' × 35' 1.000 25' × 40' 18,000 CALCULATE ROOM SIZE 25,000 1,500 30' × 50' MAKE ANY ADJUSTMENTS **INCREASE BTU 10%** FOR SUNNY ROOMS. DECREASE BTU 10% FOR SHADED ROOMS. ADD 600 BTUs FOR EACH ADDITIONAL PERSON OVER TWO. ADD 4,000 BTUs IF UNIT IS USED IN A KITCHEN.

	3AWTWH10002A
UPC CODE	850026535143
COOLING CAPACITY (BTU)	10000
HEATING CAPACITY (BTU)	10600
ENERGY STAR	No
COVERAGE AREA (sq. ft.)	450
CEER	9.6
VOLTAGE	208/230V
AMPS	4.6/5.0
WATTS	1042/1022
FAN SPEEDS (cool/fan/heat)	3/3/1
UNIT DIMENSIONS (W×H×D) (in.)	24.25×14.25×20.25
PKG. DIMENSIONS (W×H×D) (in.)	28×17×27
WEIGHT (Net/Gross) (lbs.)	69/86
CONTAINER QTY. (40HQ)	306
REFRIGERANT	R32
OUTLET CONFIGURATION	20A - 230V

FEATURES

- Fits most standard through-the-wall AC sleeves
- 3 cooling and fan speeds & 1 heat speed
- 4-way adjustable air vents
- · Cool, Heat, Fan, Eco, and Sleep modes
- Quick & easy installation
- · Mounting kit included
- Electronic controls
- Follow-me remote control acts as portable thermostat
- 24-hour timer
- Auto-restart
- Adjustable thermostat (62-86°F)
- · Easy clean slide out filter



