

WINDOW AIR CONDITIONERS

5,000 / 6,000 / 8,000 / 10,000 / 12,000 / 15,000 / 24,000 BTUs



2AWMC5000MSA

- Manual adjustable temperature control
- Slide-out washable filter
- 2-speed rotary dials
- 2-way air direction control
- Window mounting kit included
- ISTA 6A packaging



	1AW5000MSA	1AW6000DA
UPC	850012484530	850012484547
POWER SUPPLY (V)	115	115
COOLING CAPACITY (BTU)	5,000	6,000
COVERAGE (SQ. FT.)	150	250
CEER	11	11
ENERGY STAR RATED	No	No
FAN SPEEDS (COOL/FAN)	2/2	3/3
AMPS	3.9	4.8
WATTS	451	541
REMOTE	No	Yes
WINDOW WIDTH (MIN./MAX.) (IN.)	26/36	26/36
WINDOW HEIGHT (MIN.) (IN.)	14 ^{1/2}	14 ^{1/2}
UNIT DIMENSIONS (WxHxD) (IN.)	16 x 12 ^{1/2} x 15 ^{1/4}	16 x 12 ^{1/2} x 15 ^{1/4}
PKG. DIMENSIONS (WxHxD) (IN.)	18 ^{1/4} x 16 x 17	18 ^{1/4} x 16 x 17
STUFFING QTY. (20'/40'/40' HQ)	325/675/810	325/675/810
WEIGHT (NET/GROSS) (LBS.)	37.25/42	40/45
REFRIGERANT	R32	R410A

OUTLET CONFIGURATION



15 AMP 115V



15 AMP 115V



1AW6000DA

- Electronic controls
- Full range air direction control
- Temperature output range of 61°F-88°F (16°C-31°C)
- Auto, Sleep, Dry & ECO modes
- Remote control with built-in thermostat
- 24-hour timer
- Auto restart function
- Tilt-out, removable, and washable filter
- Window mounting kit included
- ISTA 6A packaging











**1AW8000DA / 2AW10000DA
2AW12000DA / 1AW15000EA
1AW18000EA / 1AW24000EA**

- Electronic controls
- Full range air direction control
- Temperature output range of 61°F-88°F (16°C-31°C)
- Auto, Sleep, Dry & ECO modes
- Remote control with built-in thermostat
- 24-hour timer
- Auto restart function
- Tilt-out, removable, and washable filter
- Window mounting kit included
- ISTA 6A packaging



	1AW8000DA	2AW10000DA	2AW12000DA	1AW15000EA	1AW18000EA	1AW24000EA
UPC	850012484554	853057008686	853057008808	850012484561	850012484578	850012484585
POWER SUPPLY (V)	115	115	115	115	230	230
COOLING CAPACITY (BTU)	8,000	10,000	12,000	15,000	18,000	24,000
COVERAGE (SQ. FT.)	350	450	550	700	1000	1500
CEER	10.9	10.9	10.9	11.8	11.8	10.3
ENERGY STAR RATED	No	No	No	No	No	No
FAN SPEEDS (COOL/FAN)	3/3	3/3	3/3	3/3	3/3	3/3
AMPS	6.2	8.3	9.6	11	7.1	11
WATTS	727	909	1091	1270	1525	2320
REMOTE	Yes	Yes	Yes	Yes	Yes	Yes
WINDOW WIDTH (MIN./MAX.) (IN.)	26/36	26/36	26/36	28/41	28/41	30/41
WINDOW HEIGHT (MIN.) (IN.)	14 ^{1/2}	16	16	19	19	19 ^{1/2}
UNIT DIMENSIONS (WxHxD) (IN.)	18 ^{3/4} x 13 ^{1/2} x 15 ^{3/4}	19 ^{3/4} x 15 ^{1/4} x 21 ^{1/2}	19 ^{3/4} x 15 ^{1/4} x 21 ^{1/2}	23 ^{3/4} x 20 x 25 ^{1/2}	23 ^{3/4} x 20 x 25 ^{1/2}	26 ^{1/2} x 18 ^{3/4} x 27
PKG. DIMENSIONS (WxHxD) (IN.)	21 ^{1/2} x 16 x 17 ^{3/4}	24 ^{1/2} x 18 ^{1/2} x 22 ^{3/4}	24 ^{1/2} x 18 ^{1/2} x 22 ^{3/4}	30 ^{1/2} x 21 ^{1/4} x 26 ^{1/2}	30 ^{1/2} x 21 ^{1/4} x 26 ^{1/2}	31 ^{1/2} x 21 ^{3/4} x 29 ^{3/4}
STUFFING QTY. (20'/40'/40' HQ)	265/550/656	144/304/380	144/304/380	96/216/268	96/216/268	84/188/233
WEIGHT (NET/GROSS) (LBS.)	48.5/55	61/68	68.5/76	106/117	117/128	130/142
REFRIGERANT	R410A	R410A	R410A	R410A	R410A	R410A
OUTLET CONFIGURATION	 15 AMP 115V	 15 AMP 115V	 15 AMP 115V	 15 AMP 115V	 20 AMP 230V	 20 AMP 230V