

THRU-THE-WALL AIR CONDITIONERS WITH HEAT





8,000 / 10,000 / 12,000 / 14,000 BTUs



2ATWH8000A / 2ATWH10002A 2ATWH12002A / 2ATWH14002

- Temperature output range of 61°F-88°F (16°C-31°C)
- 3-speed fan and fan-only mode
- Auto, sleep, dry, and eco modes
- Tilt out, removable & washable filter
- Electronic controls with LED display
- 4-way air direction
- 24-hour timer
- Remote Control (batteries included)
- Fits Standard Wall Sleeve: 26 x 15^{3/4} x 16^{3/4} (Sold Separate)
- Electric Heat Option
- ISTA 6A packaging



	2ATWH8000A	2ATWH10002A	2ATWH12002A	2ATWH14002A
UPC	853057008938	853057008907	853057008914	853057008921
POWER SUPPLY (V)	115	230	230	230
COOLING CAPACITY (BTU)	8,000	10,000	12,000	14,000
HEATING CAPACITY (BTU)	4,200	10,600	10,600	10,600
COVERAGE (SQ. FT.)	350	450	550	650
CEER	9.6	9.6	9.6	9.6
ENERGY STAR RATED	No	No	No	No
FAN SPEEDS (COOL/HEAT/FAN)	3/3/3	3/3/3	3/3/3	3/3/3
RATED CURRENT (A) (COOL)	7.2	4.6	5.5	6.7
RATED CURRENT (A) (HEAT)	12.5	15	15	15
RATED INPUT (W) (COOL)	810	1030	1230	1490
RATED INPUT (W) (HEAT)	1320	3500	3500	3500
REMOTE	Yes	Yes	Yes	Yes
UNIT DIMENSIONS (WxHxD) (IN.)	24 ^{1/4} x 14 ^{1/2} x 20 ^{1/4}	24 ^{1/4} x 14 ^{1/2} x 20 ^{1/4}	24 ^{1/4} x 14 ^{1/2} x 20 ^{1/4}	24 ^{1/4} x 14 ^{1/2} x 20 ^{1/4}
PKG. DIMENSIONS (WxHxD) (IN.)	27 ^{3/4} x 18 ^{1/2} x 27	27 ^{3/4} x 18 ^{1/2} x 27	27 ^{3/4} x 18 ^{1/2} x 27	27 ^{3/4} x 18 ^{1/2} x 27
STUFFING QTY. (20'/40'/40' HQ)	120/204/255	120/204/255	120/204/255	120/204/255
WEIGHT (NET/GROSS) (LBS.)	66.25/ 80.5	75/ 88	76/ 90.5	77.25/ 91.5
REFRIGERANT	R410A	R410A	R410A	R410A
OUTLET CONFIGURATION	 15 AMP 115V	 20 AMP 230V	 20 AMP 230V	 20 AMP 230V

AW/SS_TTWHeat_12162020