





WINDOW AIR CONDITIONERS WITH HEAT – 8,000 / 12,000 / 18,000 / 24,000 BTUs



2AWH8000A / 2AWH12000A 2AWH18000A / 2AWH24000A

- Electronic controls
- Full range air direction control
- Temperature output range of 61°F-88°F (16°C-31°C)
- Auto, Sleep, Dry & ECO modes
- Remote control with built-in thermostat
- 24-hour timer
- Auto restart function
- Tilt-out, removable, and washable filter
- Window mounting kit included
- ISTA 6A packaging



	2AWH8000A	2AWH12000A	2AWH18000A	2AWH24000A
UPC	853057008747	853057008716	853057008723	853057008730
POWER SUPPLY (V)	115	230	230	230
COOLING CAPACITY (BTU)	7,800	12,000	18,000	23,200
HEATING CAPACITY (BTU)	4,000	11,000	10,600	10,600
COVERAGE (SQ. FT.)	350	550	1,000	1,500
CEER	11.2	11.1	11	10.1
ENERGY STAR RATED	No	No	No	No
FAN SPEEDS (COOL/HEAT/FAN)	3/3/3	3/3/3	3/3/3	3/3/3
RATED CURRENT (A) (COOL)	16	21	11	16.5
RATED CURRENT (A) (HEAT)	12	16	16	16
RATED INPUT (W) (COOL)	940	1560	1900	2850
RATED INPUT (W) (HEAT)	1320	3500	3500	3500
REMOTE	Yes	Yes	Yes	Yes
WINDOW WIDTH (MIN./MAX.) (IN.)	26/36	26/36	28/41	30/41
WINDOW HEIGHT (MIN.) (IN.)	16	16	19	19 ^{1/2}
UNIT DIMENSIONS (WxHxD) (IN.)	20 x 15 ^{1/4} x 24	20 x 15 ^{1/4} x 24	23 ^{3/4} x 18 x 25 ^{1/2}	26 ^{1/2} x 19 x 27
PKG. DIMENSIONS (WxHxD) (IN.)	21 ^{3/4} x 17 x 26	21 ^{3/4} x 17 x 26	26 x 20 x 30	29 ^{1/4} x 20 ^{1/4} x 30 ^{3/4}
STUFFING QTY. (20'/40'/40' HQ)	425/360/170	425/360/170	96/216/268	84/188/233
WEIGHT (NET/GROSS) (LBS.)	69.5/77.25	79.5/89.5	121/132	134/145.25
REFRIGERANT	R410A	R410A	R410A	R410A
OUTLET CONFIGURATION	 15 AMP 115V	 20 AMP 230V	 20 AMP 230V	 20 AMP 230V

AW/SS_WAC_HEAT_12152020