



ATLONA OPTICAL/DIGITAL COAXIAL 2-WAY CONVERTER



Weight	0.40 lbs
SKU#	AT-AD2

Features:

- Supports two-way conversion: Digital Coaxial to Toslink or Toslink to Coaxial.
- Supports audio input from 2 channels up to 5.1 channels
- Supports amplification of S/PDIF audio and extends the transferring distance, through coaxial and/or Toslink cables.
- Select one input from Coaxial or Toslink input ports, and send S/PDIF audio signal to both Coaxial and Toslink output ports simultaneously.
- Compact size and easy to install.

Technical Specifications:

- Power Supply: DC 7.5V / 500mA
- Dimensions: 1.6(W)x1.5(D)x0.8(H) - (inch)
- Weight: 0.4LB

Connection Diagram

1. S/Pdif to TOSLink conversion



2. TOSLink to S/Pdif conversion



3. Boost on a TOSLink line



4. Boost on S/Pdif line



Rear View



Inputs/Outputs:

- Inputs: 1 x Digital Coaxial, 1 x Optical/Toslink
- Outputs: 1 x Digital Coaxial, 1 x Optical/Toslink

Warranty:

3 year manufacture warranty (parts and labor)

RoHS **dts**

Atlona
2151 O'toole Ave Unit D
San Jose, CA 95131
Tel: 408-954-8782
Fax: 408-954-8792
toll free: 1-877-536-3976

WWW.ATLONA.COM

COMPATIBLE WITH: **AMX** Control **RTI** **UNIVERSAL** Remote control **d-tools**

