

Specifications

Microphones

Element Fixed-charge back plate, permanently polarized condenser

Frequency Response 30-20,000 Hz

Open Circuit Sensitivity -40 dB (10.0 mV) re 1V at 1 Pa

Maximum Input Sound Level 140 dB SPL

Dynamic Range 112 dB

Signal-to-Noise Ratio 66 dB

Phantom Power Requirements 22-52V DC

Switches LED Color: mic on, mic off

Current Consumption 7.6 mA

Weight ES925C6/FM5: 109 g (3.8 oz)

ES925C12/FM5: 133 g (4.7 oz)

ES925C15/FM5: 138 g (4.9 oz)

ES925C18/FM5: 143 g (5.0 oz)

ES925C21/FM5: 148 g (5.2 oz)

ES925C24/FM5: 153 g (5.4 oz)

Dimensions ES925C6/FM5: 38.0 mm (1.50") W x 48.0 mm (1.89") D x 207.6 mm (8.17")

ES925C12/FM5: 38.0 mm (1.50") W x 48.0 mm (1.89") D x 315.0 mm (12.40")

ES925C15/FM5: 38.0 mm (1.50") W x 48.0 mm (1.89") D x 391.2 mm (15.40")

ES925C18/FM5: 38.0 mm (1.50") W x 48.0 mm (1.89") D x 391.2 mm (15.40")

Output Connector Integral 5-pin XLRM-type

Optional Interchangeable Elements ESE-Ca cardioid (120°), ESE-Ha hypercardioid (100°), ESE-MLa MicroLine

Accessories Included One pair of isolators; nut; AT8109a foam windscreen; set screw (M2 x 2); hex

Audio-Technica Case Style M44