

Specifications:

- **Frequency Range:** 554 MHz - 586 MHz
- **Compatible Systems:** 16 Compatible system operation
- **Switchable Frequencies:** 106 Preset frequencies
- **Manual Mode:** n/a
- **Frequency Response:** 45 Hz - 18 kHz
- **Comander System:** 2:1
- **Pilot Tone:** 32 kHz
- **Receiving System:** Single tuner, diversity
- **Signal-to-Noise Ratio:** 105 dB at 30 kHz deviation (A-weighted)
- **Total Harmonic Distortion:** $\leq 7\%$ (33 kHz deviation at 1 kHz)
- **Sensitivity:** 5 dBuV (S/N 60 dB at 25 kHz deviation, A-weighted)
- **Audio Output (AF=0):** Balanced: -12 dBv @ 25 kHz deviation, 600 ohm load
- **Output Connectors:** 1/4", XLR 1/4", XLR
- **Audio Level Adjust:** Balanced: -12 to +9 dBu, Line: -24 to +4 dBu (adjustable in 3 dB-steps)
- **Range:** 300 Foot, (91 M) 450', (137 M)
- **Power Supply:** 100 - 240V / 50 - 60 Hz, 12V DC, 1A
- **Net Weight:** 1.92 lbs