

Product Specifications:

Receiver

Frequency Band: 554 to 586 MHz

Bandwidth: 32 MHz

#Of Simultaneous Systems: Up to 16

Switchable Frequencies: 106 pre-coordinated frequencies

Wireless Range: Up to 300' / 91 m

Antenna Connector: 2 x BNC (8 VDC, 150 mA)

Outputs:

1 x XLR 3-pin balanced

1 x 1/4" TS unbalanced

Audio Output Level:

XLR: -12 dBV at 25 kHz deviation, 600-Ohm load, +6 gain

1/4": -18 dBV at 25 kHz deviation, 10-Ohm load, +6 gain

Audio Level Control: -12 to +9 dB in 3 dB steps

Frequency Response: 45 Hz to 18 kHz

Transmitter

RF Power Output: 10/30 mW

Bandwidth: 64 MHz

Gain Adjustment: 0 dB, -6 dB, -12 dB, -24 dB

Inputs: 1 x mini-XLR 3-pin

Input Impedance:

Mic: 10 kOhms

Line: 1 MOhm

Maximum SPL: Approximately 128 to 140 dB (depending on microphone)

Battery Life: Approximately 14 hours

Current Consumption: 110 mA typical

HT7 Microphone

Product Type: Microphone

Height: 1.6 in

Weight: 0.25 oz

Color: Beige

Body Material: Alloy steel