

AVOCOR G SERIES DATASHEET

65" & 75" PRELIMINARY



START YOUR MEETINGS QUICKLY AND SIMPLY

Reduce time spent setting up your meeting with **single Type-C connectivity** that connects the display to any Win10 laptop in seconds. This single cable delivers 4k video, audio and USB touch while getting Ethernet, and power instantly, and the 4K HDMI output can drive a 2nd display with ease.



Built-in Doppler proximity sensors detect movement and starts-up the display without any physical contact. The **wake-on-presence sensors** detect people in the room, triggering the display to automatically wake when the room is occupied and to go into power-saving mode if no movement is detected.

INTUITIVE USER EXPERIENCE

Uig

The easy-to-use proprietary interface, **Avocor UiQ** guides you through your meetings. A customizable dynamic start screen, and touch menu that allows for remote-control-free use and over-the-air updates that enable firmware updates to be securely and efficiently deployed.



The bezel-free interactive display utilizes the latest generation of **Avocor Intelligent Touch which supports palm rest and up to 4 passive pens**. Offering object recognition as well as easily switching between pen, finger, and palm, the G series delivers a realistic writing experience, creating a fluid collaborative environment for all teammates.

ENHANCED PERFORMANCE AND FEATURES

60% brighter than other interactive displays, the optically bonded 500nit glass with zero parallax means every annotation and note looks exactly how you expect them to and the anti-glare glass ensure the display will shine bright and clear even in bright rooms.

-11

Three top-edge USB ports provide easy-to-access guest connections and makes the addition of a camera simple for a seamless video conferencing solution. Integrated high-quality speakers provide a 40w crystal-clear audio experience, while the active microphone ensures low distortion and superior echo-cancelation.





AVOCOR G SERIES DATASHEET

	21	PI	ΔΥ	
-	10		- ~ '	

DISPLAY				
Model	AVG-6560	AVG-7560		
Diagonal size (inch)	65	75		
Backlight	Direct-lit L	ED		
Aspect ratio	16:9			
Resolution	3840 x 2160 @ 60Hz			
Response time	9.5ms			
Brightness	500 (cd/m2)			
Contrast ratio	5000:1			
Viewing angle	178°/178			
Supported colors	30 bit deep color			
Display orientation	Landscape			
TOUCH SYSTEM				
Interface	3 x USB-B 3	3.0		
Touch	Up to 20 point Avocor InGlass™ M5 Intelligent Touch - supports 4 x fine tip stylus - palm rest			
Glass	Zero parallax, bonded, anti-glare, anti-fingerprint			
Supported operating system	Windows 8 / 10, Mac OSX*, Linux*			
CONNECTIVITY				
		ich 1 x DisplayPort 1 2 1 x USB B 3 0 touch		
Side inputs	1 x Type-C (60W PD), 2 x HDMI 2.0, 2 x USB-B 3.0 touch, 1 x DisplayPort 1.2, 1 x USB-B 3.0 touch, 5 x USB-A 3.0 hub, 1 x USB-A service port			
Audio	1 x 3.5mm audio out, 1 x optical (SPDIF)			
Control	1 x IR input, 1 x RS-232, 1 x LAN Ethernet (RJ-45) in, 1 x LAN Ethernet (RJ-45) out			
OPS Slot	Yes, 3840 x 2160 @60Hz			
AUDIO & MICROPHONE				
Built-in speakers	2 x 20W - rear downward facing			
Microphone array	4 x far-field, beam-forming - max 5m range			
Presence sensor	Yes, max 3.5 range			
DISPLAY & REMOTE FUNCTIONS				
Auto-source- detection	Yes			
Source preview	Yes			
Image settings	5 x user / vivid / cinema	/ game / sports		
PHYSICAL SPECIFICATIONS				
Product dimensions	1480.4 x 883.4 x 115.7 mm 58.28 x 34.78 x 4.56 in	1700 x 1100 x 120 mm 66.93 x 43.31 x 4.72 in		
Shipping dimensions	1683 x 1155 x 255 mm 66.26 x 45.47 x 10.04 in	2000 x 1180 x 284 mm 78.74 x 46.46 x 11.18 in		
Weight	Net: 56 kgs 123.46 lbs	Net: 71 kgs 156.53 lbs		
Wall mount (VESA)	Gross: 75.55 kgs 166.56 lbs	Gross: 100 kgs 220.46 lbs		
IPC mount	400 x 400 mm 15.75 x 15.75 in 800 x 400 mm 31.50 x 15.75 in			
Handles	100 x 100 mm 3.94 x 3.94 in 4 x removable			
OWER	4 x 16110 Vu			
-	AC100.2401/ (worldw)			
Power supply	AC100-240V (worldwide), 50/60Hz			
AC power out	C14 to region-specific			
Max power consumption Standby	<335W <0.5W	<395W		
	≤0.5W			
ENVIRONMENTAL				
Operating temperature	0°C ~ 40°C			
Storage temperature	-20°C ~ 60°C			
Humidity	20% ~ 85	%		
WHAT COMES IN THE BOX				
	1 x Remote control & batteries, 2 x 3mm fine-tip passive touch pen, AC power cords (1 x UK, 1 x EU 1 x US, 1 x AUS), 1 x USB-B 3.0 cable (3m 118.1 in), 1 x Type-C cable (1.8m 70.9i in), 1 x HDMI cable			
	(3m 118.1 in), 1 x qui	ck start guide		
WARRANTY				

Details are subject to change without notice. All other logos and trademarks acknowledged. E&OE. * Please note up to 20-point touch in PC mode with Windows 8/10. Mac OSX and Linux only supports single touch.

