

The sculpted lines of Alta™ bring an exciting, new choice to typical range hood shapes. Infrared controls and perimeter aspiration allow you to imagine new design possibilities while you experience the ultimate in capture efficiency.

SIZE	STAINLESS	GREASE FILTERS (replacement)	NON-DUCTED FILTERS		
30 in.	ALT430SS	HPFA52 (Type "H2")	HPF52 (Type "Xh2")		
36 in.	ALT436SS	HPFA52 (Type "H2")	HPF52 (Type "Xh2")		

HVI PERFORMANCE									
			Sones			CFM			
Duct Orientation	Size	Damper	Normal	Medium*	High	Normal	Medium*	High 0.25 in. w.g.	High 0.1 in. w.g.
Vertical - Rectangular	3¼ in. x 10 in.	Included	<0.3*	3.0	8.0*	115*	270	340*	390*
Horizontal - Rectangular	3¼ in. x 10 in.	Included	<0.3*	3.0	7.5*	110*	280	380*	430*
Vertical - Rectangular	3¼ in. x 14 in.	Included	<0.3	3.0	7.5	130	280	370	410
Horizontal - Rectangular	3¼ in. x 14 in.	Included	<0.3	3.0	7.5	110	290	420	460
Round - Vertical	7 in.	Sold Separately	<0.3	3.0	7.5	130	270	340	390

FEATURES					
Max. Blower Airflow	650 CFM				
Control type	3-Speed Infrared				
Delay off	yes				
Filter Clean Reminder	yes				
Heat Sentry™	yes				
ADA Capable	yes				
Lighting	3-level LED (included)				
Grease Filter(s)	Peripheral				
Installation Hardware	EZ1 Bracket				
ENERGY STAR®	no				
Recirculation	Non-ducted filters sold separately				
AC INDUIT					

AC INPUT

120 V, 60 Hz - 1.9 AMPS

OPTIONAL ACCESSORIES					
7-in. Round Damper	BP87Q				
ADA Wiring Kit	HAWRK3				
Make-up Air Damper	MD6TU, MD8TU, or MD10TU				
Remote Control	HCR3				
TROTTORE CONTROL	11010				

MOUNTING HEIGHT


24 in. to 30 in. from cooktop to bottom of hood

LIMITED WARRANTY


1-year

3-year (LED modules only)

(See installation manual for full warranty text.)









SPECIFICATION SHEET



HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 and 0.25 in. static pressure at high speed based on tests conducted in an HVI-approved state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.
* Where noted performance rating is not HVI certified but was established in accordance with HVI Standardized test procedure.

99046188B