



Use this XLR to 1/4in cable to connect microphones and balanced sources to unbalanced inputs. This pro-audio cable is made from 22 AWG twisted pair audio cable under an aluminum foil shield and 60% copper braid for maximum shielding from noise. The highly flexible 7mm PVC jacket reduces the risk of the cable kinking and damaging the conductors.

Bright nickel plating on solid brass connectors resists wear from reconfiguring and moving equipment from one venue to another. Spring strain relief on the 1/4in plug and a chuck strain relief inside the XLR reduce the effects of age on the solder joints and contacts.

Specifications

General Info

| | | | |
|-------------------|-------|--------------------|-------------------------|
| Product Line | C2G | UPC Number | 757120400431 |
| Country Of Origin | China | Application Sector | Residential, Commercial |
| Type | Cable | | |

Dimensions

| | |
|--------------|-------|
| Cable Length | 25 ft |
|--------------|-------|

Additional Information

| | | | |
|--------------------------|-----|--------------------------|------------------------------|
| Prop 65 Warning Required | Yes | Prop 65 Warning Language | Cancer and Reproductive Harm |
|--------------------------|-----|--------------------------|------------------------------|

Technical Information

| | | | |
|-----------------|--------------------------|--------------|----------------|
| Jacket Material | PVC (Polyvinyl Chloride) | Cable Type | Audio, Adapter |
| Jacket Rating | Standard Non-Rated | Adapter Rear | 1/4in TS Male |
| Adapter Front | XLR 3-pin Female | | |