

C2G 75ft (22.9m) C2G Performance Series Ultra Flexible Active High Speed HDMI™ Cable - 4K 30Hz In-Wall, CMG (FT4) Rated Part No. AVD_CG_C2G10385

C2G Performance Series Ultra Flexible Active High Speed HDMI™ Cables extend HDMI™ signals over a high performance active HDMI™ cable and support HDMI™ audio and video features including 4K Ultra HD.



These cables are perfect for connecting a wide variety of devices from computers to projectors and monitors, AV presentation furniture, or in-wall applications requiring high speed HDMI™ features and video resolutions up to 4K (4096 x 2160) at 60Hz perfect for conference rooms, classrooms, houses of worship, and other commercial installations.

This Ultra Flexible Active High Speed HDMI™ Cable was designed for installations in tight spaces and offers commercial grade connectors that feature compact overmolding for high density environments, integrated finger grips on the top, bottom, and sides, for easy insertion and removal, and the gripping connector shell has 2x greater port retention to keep your devices connected. The gold plated connectors on the cable allow for better shielding, increased electrical conductivity, and durability.

C2G Performance Series Ultra Flexible Active High Speed HDMI™ Cable amplifies the signal from the source and sends it longer $distances \ without \ degrading \ that \ signal. \ Active \ HDMI^{\text{TM}} \ cables \ can \ only \ run \ in \ one \ direction \ - \ connect \ the \ source \ end \ to \ the$ source and the display end to your display. The connectors are conveniently labeled for source and display, so there is no confusion with this directional cable. The source connector end even has a tag on the cable as an extra reminder. Lastly, this fully-functional, high bandwidth cable has been tested to perform at industry standards and is backed by a lifetime warranty.

Features & Benefits

Supports output resolutions up to 4K (3840 x 2160) at 60Hz, providing high-quality video for viewing your screen content

In-wall (CMG/FT4) rated jacket, so you can safely run the cable inside of a wall and have a clutter free, clean look

Integrated finger grips on the connectors for easy insertion and removal

Gripping connector shell for 2x greater port retention

Gold plated connectors for increased electrical conductivity and enhanced durability

 $\label{lem:connector} \mbox{Directional cable with source connector labeled and tagged to easily differentiate}$ from the labeled display connector

Supports CEC extensions for control of consumer electronics devices through a single Backed by five-year warranty

control point		Bucked by five year warranky		
Specifications				
General Info				
Product Line	C2G	Color	Black	
UPC Number	757120103851	Country Of Origin	China	
Features	Gripping Connectors	Application Sector	Commercial	
Warranty Type	5-Year	Туре	HDMI Cable	
Dimensions				
Product Weight US	2.65 kg	Product Length US	75.0 FT	
Cable Length	75 ft			
Listing Agencies / 3rd Party Agencies				
CE Certified	Yes	REACH Compliant	Yes	
Additional Information				
RoHS Compliant	Yes			
Technical Information				
Jacket Material	PVC (Polyvinyl Chloride)	Operating Temperature Min	-40 °C	
Wire Gauge	24 AWG	Video Resolution	4K 30Hz	
Storage Humidity	85% RH (Non-Condensing)	Plating Specification	Gold	

Jacket Application	In-Wall Rated	Bend Radius	76 mm
Signal Transmission	Unidirectional	Operating Temperature Max	79 °C
Cable Type	High Speed HDMI, Ultra-Flexible	Jacket Rating	CL2 Rated, CMG Rated, FT4 Rated
Cable Diameter	9.5 mm	Data Transfer Rate	10.2 Gbps
Connector 2	HDMI Male	Connector 1	HDMI Male
Video Output Support	HDMI	Operating Temperature	-40°-75°C
Operating Humidity	85% RH (Non-Condensing)	Video Input Support	HDMI
Conductor Material	Copper	Storage Temperature	-10° - 55° C