

Features

- Extend 4K at 60Hz (4 - 2 - 0) up to 130ft and 1080p at 60Hz up to 230ft with Cat 6a cable
- Extend 4K at 60Hz (4 - 2 - 0) up to 115ft and 1080p at 60Hz up to 200ft with Cat 5e/6 cable
- HDCP 2.2 compliant, to create a secure connection between the source and display
- Supports CEC pass-through, allowing central control to all HDMI compatible devices
- Supports RS232 pass-through via HDBT port
- HDBaseT Chipset VS010, for simpler HDBaseT installations

Physical Spec Information

- Receiver; Operating Temperature - 0°C to 45°C (32°F to 113°F); Storage Temperature 20°C to 70°C (-4°F to 158°F); Humidity - 10% to 90%, Non-Condensing; ESD Protection - Human-body Model - ±8kV (Air-gap discharge) / ±4kV (Contact discharge)

Electrical Spec Information

- Receiver; Power Supply - Bi-directional PoC, one power adapter at either transmitter or receiver side can power both units; Power Supply - DC 18V 1A; Power Consumption (Max) - 8.88W (Pair, PoC)

Specifications

- Connector 1: (1) HDMI Female, (1) RJ-45 Female
- Connector 2: (1) HDMI Female, (1) RJ-45 Female, (1) DC Power Plug
- Video Resolution: 4K 60Hz, 4K 30Hz, 4K, 1080p 60Hz, 1080p
- Number of Gangs: 1
- Data Transfer Rate: 10.2 Gbps
- Operating Temperature: 0 C, 45 C
- Storage Temperature: -20 C, 70 C
- Weight: 2.45 lbs