

C2G 12ft (3.7m) TAA-Compliant F-Series Cat6 Snagless Shielded (STP) Network Cable - Red Part No. AVD_CG_C2G43758

This Cat6 cable meets stringent TAA compliant requirements and is approved for use in United States government projects and facilities. Protect a high speed network from noise and electromagnetic interference when connecting with our

counter EMI, RFI, and alien crosstalk. Available in a wide variety of colors to easily

Snagless Shielded Cat6 patch cable. This Snagless Shielded Cat6 network cable is designed for network adapters, hubs, switches, routers, servers and more. Meets or exceeds all ANSI/TIA-568.2-D Category 6 industry standards for supporting a wide variety of applications, including 1000BASE-T [1 Gigabit Ethernet]. Constructed with premium, made in the USA copper cabling with aluminum foil shield designed to

color-code a network installation.



Features & Benefits

TAA-compliant

Snagless RJ45 connector design protects clips from being easily snapped off – great for applications with high insertion cycles

50-micron gold-plated contacts improve signal integrity

Lifetime warranty

Constructed with high quality, made in the USA raw cable for consistent, reliable performance

Standard RJ45 connectors and unshielded twisted pair wires

Available in a variety of colors and lengths up to 25ft

Specifications

Gen	era	П	ln	fο

Product Line	C2G	Color	Red
UPC Number	757120437581	Country Of Origin	Mexico
Features	PoE (Power Over Ethernet)	Application Sector	Commercial, Industrial, Residential
Standard	ANSI/TIA-568.2-D;ISO/IEC 11801- 1	Warranty Type	Lifetime
Туре	Cable		

Dimensions

Product Length US 12.0 FT Cable Length 12 ft

Listing Agencies / 3rd Party Agencies

CE Certified	Yes	REACH Compliant	Yes
Trade Programs			
TAA Compliant	Yes		
Technical Information			
Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	26 AWG
Jacket Application	Riser Rated	Shielded/Unshielded	Shielded
Shield Type	STP	Cable Type	Booted, Ethernet Patch Cable, Snagless
Jacket Rating	CMR Rated	Cable Diameter	6 mm
Connector 2	RJ-45 Male	Connector 1	RJ-45 Male
Operating Temperature	-20°-75°C, -4°-167°F		