



For switching between two USB-C sources and two USB-C or USB-A devices, this device supports automatic switching by detecting a new source or manual switching via the front panel button or RS-232 API commands. It supports USB 3.2 Gen 1 with data transfer rates up to 5 Gbps and is compatible with a wide range of USB peripherals, including webcams, PTZ cameras, keyboards, mice, printers, displays, and more. This plug-and-play device is versatile and easy to use

Features & Benefits

Two USB-C ports for host PC connection	Two USB-C ports and two USB-A ports for connecting devices
Supports USB 3.2 Gen 1 with data transfer speeds up to 5Gbps	Supports auto-switching when new devices are detected or manual switching via the front panel button or RS-232 API commands
Compatible with a broad range of USB sources and devices	Compatible with a variety of devices including webcams, PTZ cameras, keyboards, mice, printers, and displays.
This USB switch is a plug-and-play device, ensuring easy and hassle-free setup without the need for additional drivers or software.	

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120542636	Country Of Origin	China
Features	RS232	Application Sector	Commercial, Residential
Warranty Type	3-Year	Type	Switch

Dimensions

Product Width US	4.92 in	Product Weight US	1.1 lb
Product Depth US	3.15 in	Product Height US	1.18 in

Listing Agencies / 3rd Party Agencies

CE Certified	Yes	FCC Compliant	Yes
REACH Compliant	Yes		

Additional Information

RoHS Compliant	Yes
----------------	-----

Technical Information

Data Transfer Rate	5 Gbps	Connector 2	USB-A Female, USB-A Female, USB-C Female, USB-C Female
Connector 1	USB-C Female, USB-C Female	Operating Temperature	32°-104°F (0°-40°C)