



Protect a high speed network from noise and electromagnetic interference when connecting with our Snagless Shielded Cat6 patch cable. For voice/data/video distribution, this cable will handle bandwidth-intensive applications and drastically reduces both impedance and structural return loss (SRL). Each patch cable is fully tested to meet ANSI/TIA 568 C.2 Cat6 component requirements.

Each of the individual pairs is bonded together to help maintain the twist-spacing throughout the line right up to the termination point. Constructed from high quality cable and plugs, this design minimizes Near-End Crosstalk (NEXT) levels. Available in a variety of colors to easily color-code a network installation. Individual length label on each cable for ease of use.

Features & Benefits

| Designed for network adapters, hubs, switches, routers, HDBaseT applications and more | Supports 10 Gigabit networks up to 180ft for fast data transmission and maximum performance and supports 1 Gigabit up to 328ft |
|---|--|
| Meets the ANSI/TIA-568-C.2 Cat6 requirements for supporting a wide variety of applications | Constructed with shielded twisted pair (STP) wires, designed to protect a high speed network from noise and electromagnetic interference |
| Snagless connector design for high density environments and protecting the RJ-45 connector's lock | Available in a variety of colors to color-code a network |

Specifications

General Info

| Product Line | C2G | Color | Blue |
|-------------------|---------------------------|--------------------|--|
| UPC Number | 757120009801 | Country Of Origin | Vietnam |
| Features | PoE (Power Over Ethernet) | Application Sector | Commercial, Industrial, Residential |
| Warranty Type | Lifetime | Туре | Cable |
| Dimensions | | | |
| Product Length US | 0.5 FT | Cable Length | 0.5 ft |
| Outside Diameter | 6.09 mm | | |

| CE Certified | Yes | REACH Compliant | Yes |
|--------------------|--------------------------|-----------------------------|----------------------|
| Additional Informa | ation | | |
| RoHS Compliant | Yes | | |
| Technical Informa | tion | | |
| Jacket Material | PVC (Polyvinyl Chloride) | Category Performance Rating | Cat 6 |
| Wire Gauge | 26 AWG | Shielded/Unshielded | Shielded |
| Conductor | 4-Pair Twisted | Shield Type | STP |
| Cable Type | Ethernet Patch Cable | Jacket Rating | Standard / Non-Rated |
| Cable Diameter | 6.2 mm | Connector Type | Booted, Snagless |
| Indoor/Outdoor | Indoor | Connector 2 | RJ-45 Male |
| Connector 1 | RJ-45 Male | | |
| | | | |