The USB-C to A SuperSpeed USB 5Gbps Male to Male Cable is the perfect solution for connecting any standard USB-C enabled device to a USB-A device or accessory for charging and data transfer.

Ensure that a USB-C equipped laptop, smartphone, or tablet is fully charged and ready to go from the 3A charging output, while simultaneously transferring photos, music, or data at speeds up to 5Gbps.

The USB-C connector has a symmetrical design which is identical on both sides, so it does not matter if you plug it in upside-down or right-side-up. It will plug in the first time, every time while preventing damage to the connector port.cessory for charging and data transfer.

Ensure that a USB-C equipped laptop, smartphone, or tablet is fully charged and ready to go from the 3A charging output, while simultaneously transferring photos, music, or data at speeds up to 5Gbps.

The USB-C connector has a symmetrical design which is identical on both sides, so it does not matter if you plug it in upside-down or right-side-up. It will plug in the first time, every time while preventing damage to the connector port.

## Features & Benefits

| | |
|---|---|
| Data transfer speeds up to 5Gbps | 3A charging output |
| Reversible, symmetrical USB-C connector | USB IF Certified |

## Specifications

### General Info

| | | | |
|---|---|---|---|
| Product Line | C2G | Color | White |
| UPC Number | 757120288350 | Country Of Origin | China |
| Application Sector | Commercial, Residential | Warranty Type | Lifetime |
| Type | Cable | | |

### Dimensions

| | | | |
|---|---|---|---|
| Product Length US | 3.0 FT | Cable Length | 3 ft |

## Technical Information

| | | | |
|---|---|---|---|
| Jacket Material | PVC (Polyvinyl Chloride) | Wire Gauge | 30 AWG |
| Storage Humidity | 15-85% RH (Non-Condensing) | Bend Radius | 48 mm |
| Conductor Stranding | Stranded | Cable Type | USB |
| Jacket Rating | VW-1 | Amperage | 3 A |
| Cable Diameter | 4.8 mm | Data Transfer Rate | 5 Gbps |
| Connector 2 | USB-A Male | Connector 1 | USB-C Male |
| Operating Temperature | 0°-50°C | Operating Humidity | 15-85% RH (Non-Condensing) |
| Storage Temperature | -25° - 70° C | | |