

C2G 10ft (3m) Serial RS232 DB9 Cable with Low Profile Connectors M/F - In-Wall CMG-Rated Part No. CG-52158



Audio/Video installations in educational and commercial settings often require in-wall rated cable. Our CMG-rated line was specifically engineered to meet this requirement while overcoming common challenges faced by installers in these environments. Low-Profile connectors (1.25 in total depth) save valuable space in the gang box, while the rounded shape accommodates smaller monitor mounts so that the cable can be easily hidden from view.

Specifically designed to support RS-232/Serial communications, this cable is fully shielded to prevent unwanted EMI/RFI interference. The fully molded cable design delivers excellent strain relief, while connector thumbscrews provide a quick and easy connection every time.

The transmit and receive signals are crossed to ensure proper data transmission.

CMG-rated cables meet with many NEC requirements for Communications Cables - General Purpose In Wall Use . Our cables meet the following ratings: CMG, FT4 (Canada)

## Features & Benefits

- Designed to support RS-232/Serial communications
- CMG-rated for in-wall use
- Shielded to prevent unwanted EMI/RFI interference
- Connector thumbscrews for a quick and easy connection

## Specifications

General Info			
Product Line	C2G	UPC Number	757120521587
Country Of Origin	Vietnam	Application Sector	Residential, Commercial, Industrial
Гуре	Cable		
Dimensions			
Cable Length	10 ft		
Additional Information			
Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
Cechnical Information			
Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	28 AWG
Cable Type	Serial	Jacket Rating	CMG (FT4) Rated
Adapter Rear	DB9 Female	Adapter Front	DB9 Male