# CEILING MOUNTS **RPMA<sup>™</sup> □** ELITE<sup>®</sup> PROJECTOR MOUNT



## **FEATURES**

### MICROZONE<sup>™</sup> ADJUSTMENTS PATENT-PENDING

This feature makes projector registration fast and precise (including flush-mount installations).

#### **CENTRIS® TECHNOLOGY** 2 PATENT-PENDING

Enables effortless fingertip positioning. Selfadjusts to support different projector weights.

#### CABLE MANAGEMENT 3

**SPECIFICATIONS** 

\* Dimensions don't include interface bracket

±3°

±20°

360°

Black

6.5″

(165 mm)

o 5.5' (140 mm)

2.75" x 6.5" x 5.5"

(69 x 165 x 140 mm)

Black, Silver, White

Pitch Adjustment

Point ±20°

1-1/2" DIA NPT

50 lbs (22.7 kg)

Roll

Pitch

Yaw

Dimensions\*

Color, Custom

Color, Universal

Weight Capacity

(HxWxD)

**TECHNICAL DRAWINGS** 

5.5"

(140 mm) (114 mm

4.5

۷

Route cables through top of mount without additional accessories.

## Q-LOCK<sup>™</sup> QUICK RELEASE LEVER

Provides quick connect/disconnect of the projector for service and enhanced security with an integrated key and lock system.


# WHAT YOU NEED TO KNOW

## ABOUT RPMA ELITE

- New universal interface with faster installation, and lamp and filter access •
- Keyed locking options (A/B/C/D) •
- Compatible with a wide array of accessories •
- Ships fully-assembled with everything you need for installation in one box
- Available in custom (black) or universal (black, silver, white)



## **RECOMMENDED ACCESSORIES**



LSB101 Lateral Shift Accessory

For a complete list of projector mount accessories see page 18.



1.0" -> 5.24" (133 mm) (25 mm) 2.72" (69 mm)

Roll Adjustment Point ±3°

6



