



## High Definition 3G-SDI BNC to BNC Cable



These broadcast quality cables supports SDI, HD-SDI and 3G-SDI and meet all requirements for 3 Gbps signal/ data serial interface transmission. Constructed with a specially formulated digital ready heavy duty 18 Awg RG6 cable that is 100% Shielded and terminated with True 75 Ohm nickel over brass BNC Connectors for proper impedance and minimal signal reflection. Comes in multiple lengths and covered under our famous Lifetime Warranty.

### Features

- Supports SDI, HD-SDI and 3G-SDI
- Meets requirements for 3 Gbps signal / data serial interface
- True 75 Ohm BNC Connectors
- Specially formulated 18 Awg RG6 cable
- 100% Shielded
- Lifetime Warranty



### Specifications

Performance Grade: Best	Temperature Rating: 75 deg C
Connector Type 1: BNC Male 75 Ohm	Voltage Rating: 30V
Connector Type 2: BNC Male 75 Ohm	Jacket Type: X-traflex mist black PVC
Connector Finish: Nickel	Weight Lbs: 0.2
Gauge: 18 AWG	RoHS Compliant: Yes
Center Conductor: Solid Oxygen Free Tinned copper	Warranty: Lifetime
Dielectric: Foam Polyethylene	
Shielding: <95% tinned copper braid and 100% Aluminum	
Mylar Wrap	
UL Rated: Yes	

<b>BB-C-3GSDI-3</b>	3ft.
<b>BB-C-3GSDI-6</b>	6ft.
<b>BB-C-3GSDI-10</b>	10ft.
<b>BB-C-3GSDI-15</b>	15ft.
<b>BB-C-3GSDI-25</b>	25ft.
<b>BB-C-3GSDI-50</b>	50ft.
<b>BB-C-3GSDI-100</b>	100ft.