

INSTRUCTIONS: WHFLP & DLHF Base Installation



**ALWAYS DISCONNECT ELECTRICAL POWER AND GAS
BEFORE MOVING EQUIPMENT**

Parts:

- 096792 WHLFP KIT,BASE WHFLP WASHER-6"
- 096794 WHLFP KIT,BASE WHFLP WASHER-10"
- 096511 DLHF KIT,BASE DLH DRYER 6"
- 096006 DLHF KIT,BASE DLH DRYER 10"

Tools:

- Spirit level
- Wrench

Note: Two people required.

WHFLP washer base installation

1. Screw the four supplied feet into the threaded holes on the underside of the base.
2. After reviewing the machine's installation manual location-requirements section, place the base in the installation location with the top C-channels running from front-to-back as shown below.



3. Level the base: front-to-back and side-to-side.
4. Unpack the washer.
5. Slightly extend the washer's adjustable feet so they will rest on the bottom of the base's C-channel.
6. Lift the washer and position on the base so that all four feet are in the C-channels. The front of the washer should overhang the front of the base so that the toe panel can be lowered and removed to allow servicing.
7. Adjust the *washer's* feet to level the washer front-to-back and side-to-side. Lock the washer's feet in place using the provided locking-nut wrench in the drum kit. The machine must not rock when pushed.
8. Complete the installation per the machine's installation manual.

Laundrylux®

DLHF dryer base installation

1. Screw the four supplied feet into the threaded holes on the underside of the base.
2. Unpack the dryer.
3. Place a blanket on the floor, to protect the dryer, and carefully lay the dryer on its left or right side.
4. Remove the four mounting feet from the underside of the dryer.
5. Raise the base so the base's top side is adjacent to the underside of the dryer.
6. Feed in the four sets of kit-supplied screw, washer and lock washers through the top side of the base and into the threaded holes of the underside of the dryer. The front of the washer should overhang the front of the base so that the toe panel can be lowered and removed to allow servicing. Once orientation is confirmed tighten all four screws.
7. After reviewing the machine's installation manual location-requirements section, carefully raise the dryer/base unit and locate the machine in the final installation position.
8. Using the pedestal's feet, level the dryer front-to-back and side-to-side. The machine must not rock when pushed.
9. Complete the installation per the installation manual.