Polacoat[®] In-Wall

Rigid Rear Projection Screens

DA-PLEX

SUGGESTED SPECIFICATIONS:

Da-Lite's Polacoat® Da-Plex In-Wall Rear Projection Screens

Rear projection screen(s) shall be Da-Lite's Polacoat® In-Wall Da-Plex, Type DA-100, DA-150, DA-180, DA-230, DA-50WA, DA-75WA, DA-100WA or Video Vision in thicknesses of ¼", ¾" or ½" as manufactured by Da-Lite Screen Company, Inc., Polacoat® Division, Blue Ash, Ohio. The screen substrate shall be clear acrylic plastic. The substrate shall have an optical coating on one surface not exceeding .004" in thickness. The overall size of the acrylic panels shall be as detailed with tolerances of +/- .125" for ¼" or +/- .250" for ¾" or +/- .375" for ½".

NOTES:

Da-Plex rear projection screens shall be mounted with the coated surface toward the audience.

Job site installation and framing shall conform to manufacturer's recommendations.

Da-Plex screens cannot be cut in the field.

DA-GLAS

SUGGESTED SPECIFICATIONS:

Da-Lite's Polacoat® Da-Glas In-Wall Rear Projection Screens

Rear projection screen(s) shall be Da-Lite's Polacoat® In-Wall Da-Glas, Type DA-100, DA-150, DA-180, DA-230, DA-50WA, DA-75WA, DA-100WA or Video Vision in thicknesses of ¼", %" or ½" as manufactured by Da-Lite Screen Company, Inc., Polacoat® Division, Blue Ash, Ohio. The screen substrate shall be clear float glass. The substrate shall have an optical coating on one surface not exceeding .004" in thickness. The overall size of the glass panels shall be as detailed with tolerances of +/- .125" for ¼" or +/- .250" for ¾" or +/- .375" for ½".

NOTES:

Da-Glas rear projection screens shall be mounted with the coated surface toward the audience.

Job site installation and framing shall conform to manufacturer's recommendations.

Da-Glas screens cannot be cut in the field.

Da-Plex... Available Sizes for Various Thicknesses*

Thickness	Approx. Net Wt. Per Sq. Ft.	Approx. Ship Wt. Per Sq. Ft.
1⁄4" – up to 9' x 18'	1½ lbs.	9 lbs.
¾" – up to 9' x 18'	2¼ lbs.	12 lbs.
½" – up to 9' x 18'	3 lbs.	15 lbs.

*Larger sizes available upon request and special order

DA-150

DA-180

DA-230

□ Video Vision

Da-Glas... Available Sizes for Various Thicknesses*

Description	Approx. Net Wt. Per Sq. Ft.	Approx. Ship Wt. Per Sq. Ft.
¼" – up to 8' x 12'	31/2 lbs.	12 lbs.
¾" – up to 10' x 20'	5¼ lbs.	16 lbs.
1⁄2" - up to 10' x 20'	7 lbs.	20 lbs.

*Larger sizes available upon request and special order

Indicate Overall Dimensions of Screen Panel(s)

Viewing Area H=	W=	Overall Size H=	W=

WHEN ORDERING, MARK APPROPRIATE SELECTIONS:

1.	Select	optical	coating:

- DA-50WA
- DA-75WA
- DA-100WA
- DA-100
- DA-130
- 2. Select substrate:
- Da-Plex (acrylic)
- Da-Glas (glass)
- 3. Select options:
- \Box High contrast tint (not available on Video Vision)
- □ Anti-glare coating
- Butt Edges (when a multiple screen installation is chosen
- Edge to Edge coating (when used without a frame.)

- 4. Select optional light baffle:
- Zero Gap available on Da-Plex ¾" thick panels up to 60" high and ½" panels up to 84" high.
- □ T-Mullion available on ¼" thick panels up to 60" high and ¾" and ½" panels up to 84" high.


5. Select optional factory installed frame:

- Deluxe frame (up to 10' x 20')
- □ Standard frame (¼" and ¾" only)
- Base frame (¼" only; Da-Plex to 6' x 8'; Da-Glas to 4' x 5')
- \Box Self trimming (up to 9' x 16')




PRODUCT VIEWS


Self Trimming Frame




Deluxe Frame




Standard Frame






Tolerance on Frame Size is 1/4" (6.4 MM)





Approximate Net Weight Per Linear Foot: 5 Oz. (1.42 KG/M)







A Milestone AV Technologies Brand

3100 North Detroit Street Warsaw, Indiana 46582 P: 574.267.8101 or 800.622.3737 F: 574.267.7804 or 877.325.4832 E: info@da-lite.com www.da-lite.com

DL-0233 12.13 © 2013 Milestone AV Technologies LLC. Printed in U.S.A.

