Model B® With CSR

Spring Roller-Type Screen with Controlled Screen Return



SUGGESTED SPECIFICAT	TIONS:projection screen(s),
(H) x	_(W), wall or ceiling mounting type. Screen to have
a powder coated white 22-	gauge octagonal steel case with flat back design
and fitted with end caps co	oncealing roller ends with integral bearing surface
to support roller and integr	ral brackets for wall mounting by means of slotted
screw holes and ceiling mo	ounting by means of powder coated hanger rings.
To be equipped with Contr	folled Screen Return (CSR) to control the return

speed of the screen into the case. Bottom of fabric shall be mounted securely into a powder coated tubular steel slat. Ends of slat shall be protected by plastic caps. A steel pull bail shall be attached to slat. A 36" (91 cm) pull cord with plastic knob is included. To have masking borders standard on flame retardant and mildew resistant fiberglass fabric. Fabric shall be mounted into a metal strip in a metal Camlok® roller system without tape, glue, staples or cords so that fabric may be easily replaced yet cannot be pulled from roller.

Video (NTSC 4:3) Format Dimensions

View	ng Area	Non	ninal	A - Overa	ll Length	B - Bet	ween			D - Case	Diameter	Approx	. Ship.
(H	x w)	Diag	gonal	of C	ase	Hange	r Eyes	C - Bra	ackets	(Wi	dth)	W	t.
ln.	Cm	ln.	Cm	In.	Cm	In.	Cm	In.	Cm	In.	Cm	Lbs.	Kg
43" x 57"	109 x 145	72"	183	63%"	161	62%"	159	3%"	9.2	2¾"	7	16	7.3
50" x 67"	127 x 170	84"	213	73%"	186	72%"	184	3%"	9.2	2¾"	7	17	7.7
57" x 77"	145 x 196	96"	244	84%"	214	83%"	212	3%"	9.2	23/4"	7	25	11.3
60" x 80"	152 x 203	100"	254	87%"	222	86%"	220	3%"	9.2	2¾"	7	26	11.8
69" x 92"	175 x 234	120"	305	99%"	252	98%"	251	3%"	9.2	2¾"	7	29	13.2

HDTV (16:9) Format Dimensions

Viewin (H x	_		ninal Jonal	A - Overa	•	B - Bet Hange		C - Bra	ickets	D - Case I (Wie	Diameter dth)	Approx Wi	
In.	Cm	In.	Cm	ln.	Cm	In.	Cm	In.	Cm	In.	Cm	Lbs.	Kg
37½" x 67"	95 x 170	77"	196	73%"	186	72%"	184	3%"	9.2	2¾"	7	16	7.3
45" x 80"	114 x 203	92"	234	87%"	222	86%"	220	3%"	9.2	2¾"	7	25	11.3
52" x 92"	132 x 234	106"	269	99%"	252	98%"	251	3%"	9.2	2¾"	7	28	12.7

(16:10) Wide Format Dimensions

Viewin (H)	g Area (w)		ninal Jonal	A - Overa of C		B - Bet Hange		C - Bra	ackets	D - Case I (Wi	Diameter dth)	Approx Wi	-
In.	Cm	In.	Cm	ln.	Cm	ln.	Cm	In.	Cm	In.	Cm	Lbs.	Kg
50" x 80"	127 x 203	94"	239	87%"	222	86%"	220	3%"	9.2	23/4"	7	24	10.9
57½" x 92"	146 x 234	109"	277	99%"	252	98%"	251	3%"	9.2	23/4"	7	26	12.3

Square Format Dimensions

Sizes ((H x w)	A - Overa	•	B - Bet Hange		C - Bra	ackets		Diameter dth)	Approx Wt	•
In.	Cm	In.	Cm	In.	Cm	In.	Cm	In.	Cm	Lbs.	Kg
60" x 60"	152 x 152	63%"	161	62%"	159	3%"	9.2	23/4"	7	16	7.3
70" x 70"	178 x 178	73%"	186	72%"	184	3%"	9.2	2¾"	7	19	8.6
72" x 72"	183 x 183	75%"	191	74%"	190	3%"	9.2	23/4"	7	21	9.5
84" x 84"	213 x 213	87%"	222	86%"	220	3%"	9.2	2¾"	7	28	12.7
96" x 96"	244 x 244	99%"	252	98%"	251	3%"	9.2	23/4"	7	32	14.5

PRODUCT NOTES

- Matte White, Video Spectra 1.5, High Contrast Matte White and High Power®: Surfaces will be seamless.
- Overall case length dimensions +/- 1/4" (6 mm).
- · Specifications subject to change without notice.
- Hanger rings add ¾" (19 mm) to the overall dimension C.
- · Custom formats and sizes available upon request.
- Optional Accessories: to provide clearance: Furnish 6" (15 cm) heavy extension wall brackets to mount screen. To provide for keystone elimination: Furnish #11 or #23 adjustable extension wall brackets. Furnish magnetic tilt lock for keystone elimination.
- NOTE: Brackets also are used for mounting screen across a corner.


WHEN ORDERING, MARK APPROPRIATE SELECTIONS:

- 1. Select size from charts on the other side.
- 2. Select viewing surface (All Da-Lite surfaces are GREENGUARD GOLD Certified.):
- ☐ Matte White
- ☐ High Contrast Matte White
- ☐ High Power®


☐ Video Spectra 1.5

- 3. Optional accessories:
- No. 6 Wall Bracket 6" (15 cm) nonadjustable extension brackets (75#, 34 kg, per pair maximum) (black or white).
- No. 11 Wall Bracket 10" or 14" (25 or 36 cm) non-adjustable extension brackets (75#, 34 kg, per pair maximum) (black or white).
- No. 23 Adjustable Wall Bracket 10", 14", 15¾", 18¼", 20" or 24" (25, 36, 40, 46, 51 or 61 cm) adjustable extension brackets (75#, 34 kg, per pair maximum) (black or white).
- Tilt-Lock for Keystone Elimination (used with extension brackets).
- ☐ T-Bar Clip for drop ceilings (50#, 23.7 kg, per pair maximum) (black or white).
- ☐ Pull Rod 38" (97 cm).
- No borders (Black masking borders standard).
- ☐ Black case (white standard).

PRODUCT VIEWS



ACCESSORIES



No. 23 Adjustable Wall Bracket Screen can be extended 10", 14", 15¾", 18¼", 20" or 24" from wall by wing nut and bolt adjustment.




No. 11 Wall Bracket Screen can be extended 10" or 14" from wall by changing position of bracket.




No. 6 Wall Bracket Screen can be extended 6" from wall.

Extension Wall Brackets (75# Per Pair Maximum) -



T-Bar Clip for drop ceiling, 50 lb. capacity.



Tilt Lock for Keystone elimination. Used with extension brackets.

Pull Rod - 38"
Zinc plated rod with black plastic handle grip allows easy

access to screen
when mounted out of
reach. Also can be
used as a pointer.

DA-LITE

A Milestone AV Technologies Brand

3100 North Detroit Street Warsaw, Indiana 46582 P. 574.267.8101 or 800.622.3737 F. 574.267.7804 or 877.325.4832 E: info@da-lite.com www.da-lite.com

DL-0225 11.13

© 2013 Milestone AV Technologies LLC. Printed in U.S.A.

Project Name:	
Architect:	
Contractor:	Phone:
Reseller:	Phone: