Specifications



Eaton 9PX3K3UNP2G2

Eaton 9PXG2 3000VA 3000W 120/208V Online Double-Conversion UPS - Hardwired Input / Output, Cybersecure Network Card, Maintenance Bypass, 6U Rack/Tower

General specifications	
PRODUCT NAME	Eaton 9PX UPS
CATALOG NUMBER	9PX3K3UNP2G2
UPC	037332294258
PRODUCT LENGTH/DEPTH	27 in
PRODUCT HEIGHT	10.2 in
PRODUCT WIDTH	17.3 in
PRODUCT WEIGHT	203 lb
WARRANTY	3 year limited
COMPLIANCES	CISPR22 Class A / FCC part 15 Class A
CERTIFICATIONS	cULus Listed NOM ENERGY STAR certified





Battery	
BATTERY MANAGEMENT	ABM+ technology uses battery replacement analytics to predict when you should replace UPS batteries based on real-life usage and conditions.
BATTERY REPLACEMENT	Hot-swappable internal batteries and extended battery modules (EBMs). Replacement battery part # EBP-1805 (qty 1 per UPS)
BATTERY TYPE	Sealed, lead-acid
EXTENDED BATTERY CAPABILITY	Add up to 12 EBMs, part # 9PXEBM180RTG2

Electrical output

RECEPTACLE	Hardwired
TOPOLOGY	Online/Double-conversion
WATTAGE	3000 W
VA RATING	3000 VA
OUTPUT WAVEFORM	True sine wave
VOLTAGE	120/208V
OUTPUT POWER FACTOR	1.0
OUTPUT VOLTAGE RANGE	±1% steady-state
OUTPUT FREQUENCY	50/60 Hz

Electrical input	
INPUT CONNECTION	Hardwired
INPUT NOMINAL VOLTAGE	208V default (200/208/220/230/240V)
INPUT FREQUENCY RANGE	60 Hz: 50–70 Hz, 50 Hz: 40–60 Hz
INPUT POWER FACTOR	>0.99 typical

Communications	
EXPANSION SLOTS	(1) Mini-Slot (MS) expansion port with Gigabit Network Card (NETWORK-M3) included
ETHERNET INTERFACE	Yes
INCLUDES NETWORK CARD	Yes
SOFTWARE COMPATIBILITY	Brightlayer Data Centers suite
USER INTERFACE	Graphical display, 5-button programmable menu, LED indicator

Environmental	
ALTITUDE	3000 m
BTU RATING	Online: 415 BTU/hr, Battery: 471 BTU/hr, High Efficiency: 177 BTU/hr
NOISE LEVEL	<43 dB at 1 meter
RELATIVE HUMIDITY	0-95% non-condensing
TEMPERATURE RANGE	0° to 40°C (32° to 104°F)

Additional specifications

PACKAGE CONTENTS

L	
SPECIAL FEATURES	Gigabit Network Card (NETWORK-M3) included
FORM FACTOR	Rack/tower
RACK SIZE	6U
RACK MOUNTING KIT	Yes
EFFICIENCY	96%

- 3000VA 3000W 9PX G2 Online Double-Conversion UPS
- 9PXPPDM2G2 PowerPass distribution module
- NETWORK-M3
 Gigabit network card
- USB cable
- RS-232 cable
- Cable gland for hardwire connection
- Rack-mounting hardware
- Tower support stands
- Quick Start Guide

SURGE PROTECTION	Yes
INTERNAL BYPASS	Yes

Warranty and support	
STANDARD FACTORY WARRANTY	 3-YEAR FACTORY WARRANTY - 3 years - Parts, electronics and batteries coverage - Standard ground shipping - Technical support
EXTENDED SERVICE PLANS	 ADVANCED DEPOT EXCHANGE - 5-year depot repair: 9SW5Y-3000UC - Expedited parts coverage for 5 years - Parts, electronics and UPS batteries coverage - Next business day shipping - Technical support 5-YEAR ON-SITE PLAN: WFLN75XX- 6009UC - On-site parts and labor coverage for years 5 - Parts, electronics and UPS batteries coverage - 24x7 on-site labor coverage, next-day response - Next-day shipping - Technical support

Resources

BROCHURES	9PX G2 3-11kVA VRLA full brochure 9PX3K3UNP2G2 feature focus
DRAWINGS	Eaton 9PX G2 UPS 9PX3K3UG2 9PX5KG2 9PX6KG2 2D drawing Eaton 9PX G2 9PXPPDM2G2 2D drawing
SPECIFICATIONS AND DATASHEETS	<u>9PX3K3UNP2G2 runtime</u> graph
TECHNICAL DATA SHEETS	Eaton 9PX G2 UPS 3kVA 3U technical specifications
WARRANTY GUIDES	<u>9PX three year limited</u> warranty

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland

Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

