

Tripp Lite's B055-001-UDP is currently not compatible with Intel HD630 graphic cards.

## NetDirector DisplayPort USB Server Interface Unit with Virtual Media and CAC Support (B064-IPG Series)

MODEL NUMBER: **B055-001-UDP**



Connects a DisplayPort USB server to a compatible Tripp Lite B064-Series NetDirector KVM switch up to 164 ft. (50 m) away using Cat5e/6 cabling. Requires B064-IPG Series KVM switch with v1.0.071 or later firmware installed.

### Description

The B055-001-UDP NetDirector® DisplayPort USB Server Interface Unit connects a server, computer or CAC reader with DisplayPort™ and/or USB ports to a Tripp Lite B064-IPG Series KVM switch with v1.0.071 or later firmware installed. Using Cat5e/6 cabling, you can locate the KVM switch up to 164 feet (50 meters) from the server.

Allowing the DisplayPort server to access the KVM switch's Virtual Media functionality via low-cost Cat5e/6 cable eliminates the need for bulky KVM cables. This frees up precious space in your server cabinet, and allows for better ventilation and longer cable runs. Running cable through conduit and other tight spaces takes advantage of the increased flexibility when setting up your network application.

No software or external power supply is needed. The unit's compact, lightweight design is plug-and-play for immediate installation and deployment. It complies with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Note: SIU's that were purchased prior to that of your KVM switch may require a firmware upgrade in order for them to work properly (see Maintenance under OSD Operation section of your B064-Series KVM Owner's Manual for details)

### Features

#### Convenient, Cost-Effective KVM Connection

- Connects DisplayPort USB server to Tripp Lite B064-IPG Series KVM switch with v1.0.071 or later firmware via Cat5e/6 cable
- Allows server to access Virtual Media functionality
- Supports Common Access Card (CAC)
- Maximum distance between server and KVM switch of 164 ft. (50 m)

### Highlights

- Provides connected DisplayPort server with Virtual Media access
- Supports Common Access Card (CAC)
- Eliminates thick, heavy KVM cable kits
- Ideal for running cable through conduit and other tight spaces
- Plug-and-play—no software or power supply required

### System Requirements

- Server, CPU or CAC reader with DisplayPort and USB ports
- B064-IPG Series HWv1 KVM switch with v1.0.071 or later firmware installed, or any B064-IPG Series HWv2 KVM switch
- Cat5e/6 cable

### Package Includes

- B055-001-UDP NetDirector DisplayPort USB Server Interface Unit



#### Eliminates Bulky KVM Cables

- Frees precious space in server cabinet
- Provides better ventilation and longer cable runs
- More flexibility for running cable through conduit and other tight spaces

#### Plug-and-Play Convenience

- No software or external power supply required
- Ready for immediate installation and deployment

#### TAA-Compliant

- Complies with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

## Specifications

OVERVIEW	
UPC Code	037332198099
Technology	Cat5/5e; DisplayPort; USB
PHYSICAL	
Shipping Dimensions (hwd / cm)	4.32 x 12.19 x 12.45
Shipping Dimensions (hwd / in.)	1.70 x 4.80 x 4.90
Shipping Weight (kg)	0.18
Shipping Weight (lbs.)	0.40
WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>