# Eaton EMI104-10

## Catalog Number: EMI104-10

Eaton Metered Input rack PDU, 0U, L6-30P input, 5.76 kW max, 200-240V, 24A, 10 ft cord, Single-phase, Outlets: (36) C13 Outlet grip, (6) C19 Outlet grip

### General specifications

Product Name Catalog Number
Eaton metered input rack PDU EMI104-10

UPC Product Length/Depth

743172050458 2.05 in

Product Height Product Width

66.5 in 2.1 in

Product Weight Warranty
15.54 lb 3 year

Compliances Certifications

TAA Compliant UL Listed



#### **Product specifications**

Form factor

0U (Vertical)

Outlet control

No

Phase

Single-phase

Wattage

5.76 kW max

**Amperage Rating** 

24A

Input voltage

200-240V

Input connection

L6-30P

Outlets

(36) C13 Outlet grip, (6) C19 Outlet grip

Cord length

10 ft

Frequency rating

50-60 Hz

Ethernet interface

Yes

Serial interface

RS-232

**Operating Temperature** 

0° to 60°C (32° to 140°F)

#### Resources

**Brochures** 

Eaton ePDU G3 brochure

Certification reports

Eaton RoHS Declaration of Conformity: ePDU G3

**Drawings** 

Eaton ePDU G3 Metered Input EMI104-10 technical drawing

Eaton Metered Input PDU Visio stencils

Manuals and user guides

Eaton ePDU G3 EMP installation and connection quick start guide

Eaton ePDU G3 instruction set - system objects

Eaton ePDU G3 installation and connectivity quick start guide

Eaton ePDU G3 operations manual

Service and troubleshooting

ePDU G3 firmware and MIBs

EMI104-10 eNMC replacement configuration file

Specifications and datasheets

Eaton Specification Sheet - EMI104-10

Warranty guides

Eaton limited warranty for rackmount PDUs



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.

