

Cat6a Pass-Through Cassette - (x12) RJ45

MODEL NUMBER: N484-12RJ







Description

Tripp Lite's N484-12RJ is a High Density Cat6a Pass-through Cassette with (x12) RJ45 connections. Designed specifically for use with Tripp Lite's N484-00U and N484-01U chassis'; up to 4 cassettes per N484-01U, or 1 per N484-00U. Each RJ45 connection is rated for 10 Gbps Ethernet data transfer speeds. Installation is simple, with the cassette being easily installed or removed using screw tabs to lock or unlock it from the panel; no tools required. Furthermore, each cassette features factory terminated connectors that reduce the time and labor required of field connector terminations. Cassette housing is manufactured with heavy duty, 1.0mm Cold Rolled Steel.

Features

- High Density Copper Cassette for use with the N484-00U and N484-01U chassis'
- Cat6a Pass-through Cassette, with (x12) RJ45 connections
- Rated for 10 Gbps Ethernet data transfer speeds
- Installation is simple, with the cassette being easily installed or removed using screw tabs to lock or unlock it from the panel; no tools required
- Each cassette features factory terminated connectors that reduce the time and labor required of field connector terminations.
- Housing made of heavy duty, 1.0mm Cold Rolled Steel

Specifications

OVERVIEW		
UPC Code	037332187222	
Technology	Cat6a	
PHYSICAL		
Shipping Dimensions (hwd / in.)	2.36 x 7.90 x 1.46	
Shipping Dimensions (hwd / cm)	5.99 x 20.07 x 3.71	

Highlights

- High Density Copper Cassette for use with the N484-00U and N484-01U chassis'
- Cat6a Pass-through Cassette, with (x12) RJ45 connections
- Rated for 10 Gbps Ethernet data transfer speeds

Package Includes

- N484-12RJ Cat6a Pass-Through Cassette - (x12) RJ45
- Quick Start Guide

TRIPP-LITE

1000 Eaton Boulevard Cleveland, OH 44122 United States

Shipping Weight (lbs.)	0.51	
Shipping Weight (kg)	0.23	
Unit Dimensions (hwd / in.)	1.200 x 5.120 x 4.700	
Unit Dimensions (hwd / cm)	3.65 x 11.35 x 3.43	
Unit Dimensions (hwd / mm)	36.5 x 113.5 x 34.3	
ENVIRONMENTAL		
Operating Temperature Range	-4 to 122 F (-20 to 50 C)	
CONNECTIONS		
Number of Ports	12	
Side A - Connector 1	RJ45 (FEMALE)	
Side B - Connector 1	RJ45 (FEMALE)	
STANDARDS & COMPLIANCE		
Product Compliance	RoHS; REACH	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.