

## Power Cord C14 to C15 - Heavy-Duty, 15A, 250V, 14 AWG, 6 ft. (1.83 m), Red

MODEL NUMBER: P018-006-ARD



Connects a PDU or UPS system with a C14 input port to network hardware, such as computers, servers and storage drives, with C15 power connectors.

### Features

#### Safe, Reliable Power Solution

- Connects PDU or UPS system with C14 input to network hardware with C15 power connectors
- Ideal for replacing an old or lost cord
- Recommended for Cisco, HP and other C15-compatible hardware

#### Color-Coded Cable and Connectors

- Colored red for easy identification in crowded rack or workstation

#### Optimum Construction

- 14 AWG wire
- Flexible SJT jacket
- 250V/15A rating
- UL-listed

## Specifications

| OVERVIEW             |                          |
|----------------------|--------------------------|
| UPC Code             | 037332199188             |
| Device Compatibility | Network Switch; UPS; PDU |
| Country/Region       | North America            |

### Highlights

- Easy-to-identify red SJT jacket and fully molded red ends
- Flexible 14 AWG wire for easy routing
- 250V/15A rating
- UL-listed
- Recommended for Cisco®, HP and other C15-compatible hardware

### Package Includes

- P018-006-ARD Heavy-Duty Computer Power Cord, Red, 6 ft.



Tripp Lite  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

| <b>INPUT</b>                        |                              |
|-------------------------------------|------------------------------|
| Maximum Input Amps                  | 15                           |
| Voltage Compatibility (VAC)         | 250                          |
| <b>PHYSICAL</b>                     |                              |
| Color                               | Red                          |
| Number of Conductors                | 3                            |
| Wire Gauge (AWG)                    | 14                           |
| Wire Gauge (OD - mm <sup>2</sup> )  | 2.08                         |
| Cable Length (ft.)                  | 6                            |
| Cable Length (m)                    | 1.8                          |
| Cable Length (in.)                  | 72                           |
| Cable Length (cm)                   | 182.88                       |
| Power Cord Jacket Type              | SJT                          |
| Shipping Dimensions (hwd / cm)      | 25.15 x 17.78 x 1.27         |
| Shipping Dimensions (hwd / in.)     | 9.90 x 7.00 x 0.50           |
| Shipping Weight (kg)                | 0.32                         |
| Shipping Weight (lbs.)              | 0.71                         |
| <b>ENVIRONMENTAL</b>                |                              |
| Operating Temperature Range         | -4 F to 221 F (-20 TO 105 C) |
| Storage Temperature Range           | -4 F to 221 F (-20 TO 105 C) |
| Operating Humidity Range            | 10-85% RH                    |
| Storage Humidity Range              | 10-85% RH                    |
| <b>CONNECTIONS</b>                  |                              |
| Side A - Connector 1                | IEC-320-C14                  |
| Side B - Connector 1                | IEC-320-C15                  |
| <b>SPECIAL FEATURES</b>             |                              |
| High Voltage                        | Yes                          |
| Locking Plug                        | No                           |
| <b>WARRANTY</b>                     |                              |
| Product Warranty Period (Worldwide) | Lifetime limited warranty    |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>