

Null Modem Serial DB9 Serial Cable (DB9 F/F), 10 ft. (3.05 m)

MODEL NUMBER: P450-010



Features

- DB9 female to DB9 female
- Full Handshake Null wiring configuration: 1+6 4, 2-3, 3-2, 4 1+6, 5-5, 7-8, 8-7.
- Superior molded cables with foil-shielding for maximum EMI/RFI protection
- Gold-plated connectors provide superior conductivity

Specifications

OVERVIEW		
UPC Code	037332154682	
PHYSICAL		
FITIGLAL		
Color	Black	
Cable Jacket Color	Black	
Cable Length (ft.)	10	
Cable Length (m)	3.05	
Shipping Dimensions (hwd / in.)	0.50 x 4.45 x 6.40	
Shipping Dimensions (hwd / cm)	1.27 x 11.30 x 16.26	
Shipping Weight (lbs.)	0.30	
Shipping Weight (kg)	0.14	
CONNECTIONS		

Highlights

- Superior molded cables with integral strain relief and foilshielding for maximum EMI/RFI protection
- Gold-plated connectors provide superior conductivity
- Null modem cables connect two serial devices that require a null

modem configuration

System Requirements

 Two serial devices with DB9M connectors requiring a null modem (cross-wired) configuration

Package Includes

 10-ft. (3.05 m) Null Modem Gold Cable DB9F to DB9F



Side A - Connector 1	DB9 (FEMALE)
Side B - Connector 1	DB9 (FEMALE)
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies