

## DisplayPort 1.2 to DVI Active Adapter Cable, DP with Latches to DVI (M/M), 3 ft. (0.91 m)

MODEL NUMBER: P581-003-V2



Converts a DisplayPort v1.2 video signal for display on a DVI monitor, projector or television.

### Features

#### Send High-Quality DisplayPort v1.2 Video Signals to a DVI Display

- Connects DisplayPort computer to DVI-enabled monitor, projector or TV
- Ideal for displaying video on large monitor or digital sign
- DVI-D and latching DisplayPort male connectors
- No separate adapter required

#### Vibrant, Superior Video Quality

- Supports computer video resolutions up to 1920 x 1200
- Supports HD video resolutions up to 1920 x 1080 (1080p)
- Converts Single-Mode and Dual-Mode (DP++) DisplayPort output
- Perfect for use with graphics cards, such as AMD Eyefinity, that do not output DP++ signals

#### Superior Materials for Superior Performance

- Double shielding with foil and braid for maximum EMI/RFI protection
- Gold-plated connectors and contacts for excellent conductivity
- Latching DisplayPort plug for secure connection
- Integral strain relief for long life

## Specifications

### Highlights

- Active adapter for use with any DisplayPort port
- Supports computer video resolutions up to 1920 x 1200
- Supports HD video resolutions up to 1920 x 1080 (1080p)
- No separate adapter required
- Gold-plated connectors and contacts

### Package Includes

- P581-003-V2 DisplayPort 1.2 to DVI Active Adapter Cable, 3 ft.



UPC Code	037332191960
Technology	DVI; DisplayPort
<b>VIDEO</b>	
Max Supported Video Resolution	1920 x 1200 @60Hz
Max Supported Color Depth	24-bit True Color
<b>PHYSICAL</b>	
Color	Black
Cable Length (ft.)	3
Cable Length (m)	0.9
Shipping Dimensions (hwd / cm)	22.86 x 17.78 x 1.27
Shipping Dimensions (hwd / in.)	9.00 x 7.00 x 0.50
Shipping Weight (kg)	0.13
Shipping Weight (lbs.)	0.28
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	32~113°F (0~45°C)
Storage Temperature Range	14~158°F (-10~70°C)
Operating Humidity Range	10%~85% RH, Non-Condensing
Storage Humidity Range	5%~90% RH, Non-Condensing
<b>CONNECTIONS</b>	
Side A - Connector 1	DISPLAYPORT (MALE)
Side B - Connector 1	DVI-D DUAL-LINK (MALE) (WIRED TO DVI-D SINGLE-LINK)
<b>FEATURES &amp; SPECIFICATIONS</b>	
Displayport Specification	1.2
<b>SPECIAL FEATURES</b>	
Latching Connector	Yes
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	3-year limited warranty