



Protect It! 6-Outlet Surge Protector - 5-15R Outlets, USB-C and USB-A Ports, 5-15P Direct Plug-In, 1080 Joules, Gray

MODEL NUMBER: SK60C











Protects your computer and other home/office electronics against dangerous power surges, spikes and line noise.

Features

6-Outlet Surge Protector with USB Charging Safeguards Your Sensitive Electronics

Ideal for your home, office, retail or industrial workstation, this Protect It!® surge protector features a surge protection rating of 1080 joules to defend your valuable electronic components against power surges and spikes. The unit plugs directly into a wall outlet, avoiding annoying cord clutter.

NEMA 5-15R Outlets Accept a Wide Range of Electronic Devices

Plug your computer, printer, wireless router, desk lamp and other home/office electronics into six NEMA 5-15R outlets to protect them against dangerous surges, spikes and line noise.

Premium Protection from EMI/RFI Line Noise Helps Your Equipment Perform Better

This surge protector filters out disruptive EMI (electromagnetic interference) and RFI (radio frequency interference) line noise that can disturb your electronics and inflict hardware damage or data loss. This EMI/RFI filtering also helps your connected components perform better and last longer.

USB Charger Keeps Mobile Devices Ready for Use

One USB-C port and two USB-A ports are available for charging your smartphone, tablet or other USB mobile devices. The USB-C port has 3A and the USB-A ports 2.4A each for charging multiple devices at the same time. A green LED confirms at a glance that your equipment is protected.

Specifications

OVERVIEW		
UPC Code	037332288783	
Product Type	Surge Protector	
Charging Form Factor	Direct Plug-In	
Device Compatibility	Phone; Tablet; Amazon Kindle	

Highlights

- 6 NEMA 5-15R outlets distribute AC power to connected home/office/work equipment
- 1080 joules protect your valuable electronics against dangerous surges and spikes
- Plugs directly into the wall (no cord required) for easy installation and no cable clutter
- USB-A and USB-C ports power and charge smartphones and other mobile devices
- Easy-to-see green LED lets you know at a glance that your equipment is protected

Package Includes

- SK60C 6-Outlet Surge Protector, Gray
- · Owner's manual





Nominal Input Voltage(s) Supported	120V AC	
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V	
Input Cord Length Details	Direct Plug-In	
Voltage Compatibility (VAC)	120	
Input Plug Type	NEMA 5-15P	
Input Cord Length (ft.)	0	
Right-Angle Plug	No	
Input Cord Length (m)	0.00	
Integrated Cord Clip	No	
OUTPUT		
Output Capacity (Watts)	1875	
Frequency Compatibility	60 Hz	
Output Receptacles	(6) 5-15R	
Circuit Breaker (amps)	15	
Transformer Accommodation	No	
Output Amp Capacity	15	
Right-Angle Outlets	No	
CONNECTIONS		
Number of Ports	3	
USER INTERFACE, ALERTS & CONTROLS		
Diagnostic LED(s)	Yes	
Diagnostic LED Details	Green - Protected	
CHARGING		
Number of Charging Ports	3	
Total Charging Amps	2.4A each for 2 USB-A and 3A for USB-C	
Total Charging Watts	1875	
Charging Method	USB	
Charging Port Type	USB A (FEMALE); USB C (FEMALE)	
Charging Ports / Amps	(2) 2.4A; (1) 3A	
Overcharge Protection	No	
Charging Amps per Port	2.A each for USB-A and 3A for USB-C	





SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	1080	
AC Suppression Response Time	< 1 ns	
Protection Modes	L-N, L-G, N-G	
UL1449 Let Through Rating	500, 500, 600	
EMI / RFI Filtering	150KHz-100MHz	
Isolated Filter Banks	no	
Immunity	Conforms to IEE 587/ANSI C62.41	
Automatic Shut-Off	Yes	
DATALINE SURGE SUPPRESSION		
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
Telephone/DSL Protection	No	
PHYSICAL		
Color	Gray	
Material of Construction	Plastic	
Housing Color	Gray	
Mounting Holes or Slots	No	
Receptacle Color	Gray	
Shipping Dimensions (hwd / in.)	5.76 x 4.16 x 2.60	
Shipping Dimensions (hwd / cm)	14.63 x 10.57 x 6.60	
Shipping Weight (lbs.)	0.66	
Shipping Weight (kg)	0.30	
Unit Dimensions (hwd / in.)	5.520 x 3.920 x 2.270	
Unit Dimensions (hwd / cm)	14.2 x 9.1 x 7.1	
Unit Weight (lbs.)	0.57	
Unit Weight (kg)	0.26	
FEATURES & SPECIFICATIONS		
Rotatable Outlets	No	
Antimicrobial	No	
GaN Technology	No	
STANDARDS & COMPLIANCE		
Product Certifications	CAN/CSA-C22.2 No. 286 (Canada); CAN/CSA-C22.2 No. 42 (Canada); UL 1449	





Product Compliance	RoHS	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$7,500 Ultimate Lifetime Insurance	

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.