



Protect It! 6-Outlet Surge Protector - 5-15R Outlets, USB-C and USB-A Ports, 5-15P Direct Plug-In, 1080 Joules, Black

MODEL NUMBER: SK60CB











Protects your computer and other home/office electronics against dangerous power surges, spikes and line noise.

Features

6-Outlet Surge Protector with USB Charging Safeguards Your Sensitive Electronics

Ideal for your home, office, retail or industrial workstation, this Protect It!® surge protector features a surge protection rating of 1080 joules to defend your valuable electronic components against power surges and spikes. The unit plugs directly into a wall outlet, avoiding annoying cord clutter.

NEMA 5-15R Outlets Accept a Wide Range of Electronic Devices

Plug your computer, printer, wireless router, desk lamp and other home/office electronics into six NEMA 5-15R outlets to protect them against dangerous surges, spikes and line noise.

Premium Protection from EMI/RFI Line Noise Helps Your Equipment Perform Better

This surge protector filters out disruptive EMI (electromagnetic interference) and RFI (radio frequency interference) line noise that can disturb your electronics and inflict hardware damage or data loss. This EMI/RFI filtering also helps your connected components perform better and last longer.

USB Charger Keeps Mobile Devices Ready for Use

One USB-C port and two USB-A ports are available for charging your smartphone, tablet or other USB mobile devices. The USB-C port has 3A and the USB-A ports 2.4A each for charging multiple devices at the same time. A green LED confirms at a glance that your equipment is protected.

Specifications

OVERVIEW		
UPC Code	037332288790	
Product Type	Surge Protector	
Charging Form Factor	Direct Plug-In	
Device Compatibility	Phone; Tablet; Amazon Kindle	

Highlights

- 6 NEMA 5-15R outlets distribute AC power to connected home/office/work equipment
- 1080 joules protect your valuable electronics against dangerous surges and spikes
- Plugs directly into the wall (no cord required) for easy installation and no cable clutter
- USB-A and USB-C ports power and charge smartphones and other mobile devices
- Easy-to-see green LED lets you know at a glance that your equipment is protected

Package Includes

- SK60CB 6-Outlet Surge Protector, Black
- · Owner's manual





Nevita Nominal Input Voltage(e) Supported 120V AC Recommended Electrical Services 120V Input Cord Length Details Direct Plug-in Voltage Compatibility (VAC) 120 Input Plug Type NEMA 5-15P Input Cord Length (R) 0 Input Cord Length (R) 0.00 Integrated Cord Clip No Note Type Output Carpacity (Watts) 1800 Frequency Compatibility 60 Hz Output Receptacles (8) 5-15R Circuit Researe (amps) 16 Circuit Researe (amps) 16 Right-Angle Outlets No CONNECTIONS Number of Ports 3 Segmentation of Ports Diagnostic LED petails 7 es Diagnostic LED petails 9 es Diagnostic LED petails 6 eren - Protected Charging Amps 2.44 each for 2 USB-A and 3A for USB-C Otanging Ports USB A (FEMALE); USB C (FEMALE) Charging Port Jymp USB A (FEMALE); USB C (FEM			
Recommended Electrical Service 120V Input Cord Length Details Direct Plug-In Voltage Compatibility (VAC) 120 Input Plug Type NEMA 6-15P Input Cord Length (It) 0 Input Cord Length (Im) 0.00 Integrated Cord Clip No OUTPUT OUTPUT OUTPUT Output Capacity (Watts) 1800 Frequency Compatibility 60 Hz Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Transformer Accommodation No Output Amp Capacity 16 Right-Angle Outlets No CONNECTIONS Sumber of Ports 3 USER INTERFACE, ALERTS & CUEVES USER INTERFACE, ALERTS & CUEVES Diagnostic LED(s) Yes Diagnostic LED petalls Green - Protected CHARGING Number of Charging Ports 3 Total Charging Matts 1,675 Total Chargin	INPUT		
Input Cord Length Details Direct Plug-in Voltage Compatibility (VAC) 120 Input Drype NEMA 5-15P Input Cord Length (It) 0 Right-Angle Plug No Integrated Cord Clip No OUTPUT PORTPUT PORTPUT PORTPUT PORTPUT PORTPUT PORTPUT PORTPUT PORTPUT	Nominal Input Voltage(s) Supported	120V AC	
Votage Compatibility (VAC) 120 Input Plug Type NEMA 5-15P Input Cord Length (It) 0 Right-Angle Plug No Input Cord Length (m) 0.00 Integrated Cord Clip No OUTPUT OUTPUT Output Capacity (Watts) 1800 Frequency Compatibility 60 Hz Output Receptacles (6) 5-15R Croul Breaker (amps) 15 Transformer Accommodation No Output Amp Capacity 15 Right-Angle Outlets No CONNECTIONS Number of Ports 3 See: Number of Ports Diagnostic LED(s) Yes Diagnostic LED Details Green - Protected CHARGING Number of Charging Ports 3 Total Charging Appare 2.44 each for 2 USB-A and 3A for USB-C Total Charging Watts 1875 Charging Method USB A (FEMALE); USB C (FEMALE) Charging Port X / Amps USB A (24A; (1) 3A	Recommended Electrical Service	120V	
Input Ping Type NEMA 5-15P Input Cord Length (ft.) 0 Right-Angle Ping No Input Cord Length (m) 0.00 Integrated Cord Clip No OUTPUT Output Capacity (Wats) 1800 Frequency Compatibility 60 Hz Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Transformer Accommodation No Output Amp Capacity 15 Right-Angle Outets No CONNECTIONS Number of Ports 3 Output Remarks & Cutter S & Cut	Input Cord Length Details	Direct Plug-In	
Input Card Length (ft.) 0 Right-Angle Plug No Input Card Length (m) 0.00 Integrated Cord Clip No OUTPUT OUTPUT Output Capacity (Wats) 1800 Frequency Compatibility 60 Hz Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Transformer Accommodation No Output Amp Capacity 15 Right-Angle Outlets No CONNECTIONS Number of Ports 3 CUSER INTERFACE, ALERTS & CVELL Diagnostic LED(s) Yes Diagnostic LED Details Green - Protected CHARGING Number of Charging Ports 3 Total Charging Amps 2.4A each for 2 USB-A and 3A for USB-C Total Charging Watts 1876 Charging Method USB A (FEMALE); USB C (FEMALE) Charging Ports / Amps (2) 2.44; (1) 3A	Voltage Compatibility (VAC)	120	
Right-Angle Plug No Input Cord Length (m) 0.00 Integrated Cord Clip No OUTPUT Output Capacity (Watts) 1800 Frequency Compatibility 60 Hz Cutput Receptacles (6) 5-15R Circuit Breaker (amps) 15 Transformer Accommodation No Couput Amp Capacity 15 Right-Angle Outlets No CONNECTIONS Number of Ports 3 USER INTERFACE, ALERTS & CONTROLS Diagnostic LED Details Green - Protected CHARGING Number of Charging Ports 3 CHARGING Number of Charging Ports 3 Total Charging Ports 3 CHARGING Number of Charging Ports 3 Total Charging Amps 2.4A each for 2 USB-A and 3A for USB-C Total Charging Watts 1875 C	Input Plug Type	NEMA 5-15P	
Input Cord Length (m) 0.00 Integrated Cord Clip No OUTPUT OUTPUT OUTPUT OUTPUT 60 Hz OUTPUT Capacity (Watts) 1800 COUTPUT Capacity (%) 5-15R Circuit Breaker (amps) 15 Circuit Breaker (amps) 15 Circuit Amp Capacity 15 Counted Capacity 15 COUNTECTIONS Number of Ports 3 CONNECTIONS Diagnostic LED (s) Yes Diagnostic LED (s) Yes Diagnostic LED (betails 7 (see - Protected CHARGING Number of Charging Ports 3 CHARGING Number of Charging Ports 3 CHARGING Number of Charging Ports 3 CHARGING Value (ample) 2 (ample) 2 (am	Input Cord Length (ft.)	0	
OUTPUT OUTPUT OUTPUT (Spacity (Watts) 1800 Frequency Compatibility 60 Hz Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Transformer Accommodation No Output Amp Capacity 15 Right-Angle Outlets No CONNECTIONS Number of Ports 3 USER INTERFACE, ALERTS & CONTOLS Diagnostic LED (s) Yes Diagnostic LED Details Green - Protected CHARGING Number of Charging Ports 3 Total Charging Amps 2.4A each for 2 USB-A and 3A for USB-C Total Charging Watts 1875 Charging Method USB A (FEMALE); USB C (FEMALE) Charging Port Type USB A (FEMALE); USB C (FEMALE)	Right-Angle Plug	No	
OUTPUT Output Capacity (Watts) 1800 Frequency Compatibility 60 Hz Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Transformer Accommodation No Output Amp Capacity 15 Right-Angle Outlets No CONNECTIONS Number of Ports 3 Diagnostic LED(s) Yes Diagnostic LED betails Green - Protected CHARGING CHARGING Total Charging Ports 3 Total Charging Watts 1875 Charging Method USB (FEMALE); USB C (FEMALE) Charging Ports / Amps (2) 2.4A; (1) 3A	Input Cord Length (m)	0.00	
Output Capacity (Watts) 1800 Frequency Compatibility 60 Hz Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Transformer Accommodation No Output Amp Capacity 15 Right-Angle Outlets No CONNECTIONS Number of Ports 3 USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Diagnostic LED Details Green - Protected CHARGING Number of Charging Ports 3 Total Charging Amps 2.4A each for 2 USB-A and 3A for USB-C Total Charging Watts 1875 Charging Method USB Charging Port Type USB A (FEMALE); USB C (FEMALE) Charging Ports / Amps (2) 2.4A; (1) 3A	Integrated Cord Clip	No	
Frequency Compatibility 60 Hz Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Transformer Accommodation No Output Amp Capacity 15 Right-Angle Outlets No CONNECTIONS Number of Ports 3 USER INTERFACE, ALERTS & CONTOLS Diagnostic LED(s) Yes Diagnostic LED Details Green - Protected CHARGING Number of Charging Ports 3 Total Charging Amps 2.4A each for 2 USB-A and 3A for USB-C Total Charging Watts 1875 Charging Method USB Charging Port Type USB A (FEMALE); USB C (FEMALE) Charging Ports / Amps (2) 2.4A; (1) 3A	ОИТРИТ		
Circuit Breaker (amps) 15 Transformer Accommodation No Output Amp Capacity 15 Right-Angle Outlets No CONNECTIONS Number of Ports 3 Diagnostic LED (s) Yes Diagnostic LED Details Green - Protected CHARGING Number of Charging Ports 3 Total Charging Watts 1875 Charging Method USB (FEMALE); USB C (FEMALE) Charging Ports / Amps (2) 2.4A; (1) 3A	Output Capacity (Watts)	1800	
Circuit Breaker (amps) 15 Transformer Accommodation No Output Amp Capacity 15 Right-Angle Outlets No CONNECTIONS Number of Ports 3 Diagnostic LED(s) Yes Diagnostic LED Details Green - Protected CHARGING Number of Charging Ports 3 Total Charging Method USB Charging Port Type USB A (FEMALE); USB C (FEMALE) Charging Ports / Amps (2, 2.4A; (1) 3A	Frequency Compatibility	60 Hz	
Transformer Accommodation No Output Amp Capacity 15 Right-Angle Outlets No CONNECTIONS Number of Ports 3 USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Diagnostic LED Details Green - Protected CHARGING Number of Charging Ports 3 Total Charging Amps 2.4A each for 2 USB-A and 3A for USB-C Total Charging Watts 1875 Charging Method USB Charging Port Type USB A (FEMALE); USB C (FEMALE) Charging Ports / Amps (2) 2.4A; (1) 3A	Output Receptacles	(6) 5-15R	
Output Amp Capacity 15 Right-Angle Outlets No CONNECTIONS Number of Ports 3 USER INTERFACE, ALERTS & CONTOLS Diagnostic LED(s) Yes Diagnostic LED Details Green - Protected CHARGING Number of Charging Ports 3 Total Charging Amps 2.4A each for 2 USB-A and 3A for USB-C Total Charging Watts 1875 Charging Method USB Charging Port Type USB A (FEMALE); USB C (FEMALE) Charging Ports / Amps (2) 2.4A; (1) 3A	Circuit Breaker (amps)	15	
Right-Angle Outlets CONNECTIONS Number of Ports 3 USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Diagnostic LED Details Green - Protected CHARGING Number of Charging Ports 3 Total Charging Amps 2.4A each for 2 USB-A and 3A for USB-C Total Charging Watts 1875 Charging Method USB Charging Port Type USB A (FEMALE); USB C (FEMALE) Charging Ports / Amps (2) 2.4A; (1) 3A	Transformer Accommodation	No	
Number of Ports 3 USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Diagnostic LED Details Green - Protected CHARGING Number of Charging Ports 3 Total Charging Amps 2.4A each for 2 USB-A and 3A for USB-C Total Charging Watts 1875 Charging Method USB Charging Port Type USB A (FEMALE); USB C (FEMALE) Charging Ports / Amps (2) 2.4A; (1) 3A	Output Amp Capacity	15	
Number of Ports 3 USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Diagnostic LED Details Green - Protected CHARGING Number of Charging Ports 3 Total Charging Amps 2.4A each for 2 USB-A and 3A for USB-C Total Charging Watts 1875 Charging Method USB Charging Port Type USB A (FEMALE); USB C (FEMALE) Charging Ports / Amps (2) 2.4A; (1) 3A	Right-Angle Outlets	No	
Diagnostic LED(s) Poignostic LED Details Green - Protected CHARGING Number of Charging Ports 1 Total Charging Amps 2.4A each for 2 USB-A and 3A for USB-C Total Charging Watts 1875 Charging Method USB Charging Port Type USB A (FEMALE); USB C (FEMALE) Charging Ports / Amps (2) 2.4A; (1) 3A	CONNECTIONS		
Diagnostic LED(s) Pes Green - Protected CHARGING Number of Charging Ports Total Charging Amps 2.4A each for 2 USB-A and 3A for USB-C Total Charging Watts 1875 Charging Method USB Charging Port Type USB A (FEMALE); USB C (FEMALE) Charging Ports / Amps (2) 2.4A; (1) 3A	Number of Ports	3	
CHARGING Number of Charging Ports Total Charging Watts Charging Method Charging Port Type USB A (FEMALE); USB C (FEMALE) Charging Ports / Amps Green - Protected 3 Charging Ports 1875 Charging Method USB Charging Port Type USB A (FEMALE); USB C (FEMALE) Charging Ports / Amps (2) 2.4A; (1) 3A	USER INTERFACE, ALERTS & CONTROLS		
CHARGING Number of Charging Ports 3 Total Charging Amps 2.4A each for 2 USB-A and 3A for USB-C Total Charging Watts 1875 Charging Method USB Charging Port Type USB A (FEMALE); USB C (FEMALE) Charging Ports / Amps (2) 2.4A; (1) 3A	Diagnostic LED(s)	Yes	
Number of Charging Ports 3 Total Charging Amps 2.4A each for 2 USB-A and 3A for USB-C Total Charging Watts 1875 Charging Method USB Charging Port Type USB A (FEMALE); USB C (FEMALE) Charging Ports / Amps (2) 2.4A; (1) 3A	Diagnostic LED Details	Green - Protected	
Total Charging Amps 2.4A each for 2 USB-A and 3A for USB-C Total Charging Watts 1875 Charging Method USB Charging Port Type USB A (FEMALE); USB C (FEMALE) Charging Ports / Amps (2) 2.4A; (1) 3A	CHARGING		
Total Charging Watts 1875 Charging Method USB Charging Port Type USB A (FEMALE); USB C (FEMALE) Charging Ports / Amps (2) 2.4A; (1) 3A	Number of Charging Ports	3	
Charging Method USB Charging Port Type USB A (FEMALE); USB C (FEMALE) Charging Ports / Amps (2) 2.4A; (1) 3A	Total Charging Amps	2.4A each for 2 USB-A and 3A for USB-C	
Charging Port Type USB A (FEMALE); USB C (FEMALE) Charging Ports / Amps (2) 2.4A; (1) 3A	Total Charging Watts	1875	
Charging Ports / Amps (2) 2.4A; (1) 3A	Charging Method	USB	
	Charging Port Type	USB A (FEMALE); USB C (FEMALE)	
Overcharge Protection No	Charging Ports / Amps	(2) 2.4A; (1) 3A	
	Overcharge Protection	No	
Charging Amps per Port 2.A each for USB-A and 3A for USB-C	Charging Amps per Port	2.A each for USB-A and 3A for USB-C	





SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	1080	
AC Suppression Response Time	<1 ns	
Protection Modes	L-N, L-G, N-G	
UL1449 Let Through Rating	500, 500, 600	
EMI / RFI Filtering	150KHz-100MHz	
Isolated Filter Banks	no	
Immunity	Conforms to IEE 587/ANSI C62.41	
Automatic Shut-Off	Yes	
DATALINE SURGE SUPPRESSION		
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
Telephone/DSL Protection	No	
PHYSICAL		
Color	Black	
Material of Construction	Plastic	
Housing Color	Black	
Mounting Holes or Slots	No	
Receptacle Color	Black	
Shipping Dimensions (hwd / in.)	5.76 x 4.16 x 2.60	
Shipping Dimensions (hwd / cm)	14.63 x 10.57 x 6.60	
Shipping Weight (lbs.)	0.66	
Shipping Weight (kg)	0.30	
Unit Dimensions (hwd / in.)	5.520 x 3.920 x 2.270	
Unit Dimensions (hwd / cm)	14.2 x 9.1 x 7.1	
Unit Weight (lbs.)	0.57	
Unit Weight (kg)	0.26	
FEATURES & SPECIFICATIONS		
Rotatable Outlets	No	
Antimicrobial	No	
GaN Technology	No	
STANDARDS & COMPLIANCE		
Product Certifications	CAN/CSA-C22.2 No. 286 (Canada); CAN/CSA-C22.2 No. 42 (Canada); UL 1449	





Product Compliance	RoHS
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	Lifetime limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$7,500 Ultimate Lifetime Insurance

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.