

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Conference Power Surge Protector - 4 NEMA 5-15R Outlets, 4 USB-A Ports, 6-ft. (1.83 m) Cord, Black

MODEL NUMBER: TLP406USBUFO











Safely charges and powers up to 8 mobile devices, including laptops, during important workplace meetings and conferences.

Features

Keep Your Team's Devices Powered and Charged During Important Meetings

Workplace meetings involve a variety of devices – laptops, smartphones, tablets – to keep everyone coordinated and up to date with the information necessary to make important decisions. Guaranteeing those devices remain charged and powered is Tripp Lite's Conference Power Surge Protector. Rounded to ensure equal access to everyone at the table, this UL-certified surge protector delivers ample power and reliable protection to as many as eight mobile devices at the same time.

NEMA 5-15R Outlets Accept a Wide Range of Electronic Devices

Plug your laptops, projector, printer or other conference-table electronics into four NEMA 5-15R outlets to protect them against dangerous surges, spikes and line noise. Each outlet is located far enough apart from the others to accept bulky transformers without blocking adjacent outlets.

4 USB-A Ports Share 4.2 Amps of Charging Power

The USB ports are available for charging your smartphones, tablets and other USB mobile devices. They share 4.2A of charging power, which is plenty for delivering ample power to demanding devices.

1800 Joules Safeguard Your Sensitive Electronics

This Protect Itl® surge protector features a surge suppression rating of 1800 joules to defend your sensitive electronic components against even the strongest power surges and spikes. Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the TLP406USBUFO protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G).

Premium Protection from EMI/RFI Line Noise Helps Your Equipment Perform Better

Various electromagnetic and radio sources found in virtually every home and business can cause disruptive interference on the AC line. Known as EMI (electromagnetic interference) and RFI (radio frequency interference), this line noise is a common cause of performance problems. This surge protector filters out disruptive line noise that can disturb your electronics and inflict hardware damage or data loss. This EMI/RFI filtering also helps your connected components perform better and last longer.

Premium Safety Features Protect Your Valuable Equipment

The on/off switch provides one-touch control over all connected equipment. Red and green LEDs confirm your connected equipment is grounded and protected.

Right-Angle Plug Makes Connecting in Tight Spaces Easier

The space-saving right-angle NEMA 5-15P connector with 6-ft. (1.83 m) braided power cord is easy to install in confined spaces, such as behind a computer desk or workstation. The right-angle construction also relieves strain on the cable and connector and prevents the cable from bending awkwardly.

Highlights

- Ideal for conference tables, meeting rooms and other areas with multiple mobile devices
- 4 NEMA 5-15R outlets spaced widely apart to accommodate bulky transformers
- 1800 joules protect your valuable electronics against dangerous surges and spikes
- 4 USB ports share 4.2A for fast charging of phones, tablets and other mobile devices
- Right-angle NEMA 5-15P plug with 6-ft. (1.83 m) cord allows easy connection in confined spaces

Applications

- Keep vital mobile devices fully powered and charged during important conferences and meetings
- Protect laptops, tablets, smartphones and other valuable electronics against AC power surges and spikes
- Filter potentially damaging line noise to improve connected equipment's performance and lifespan
- Safeguard valuable data against damage stemming from unexpected surges

Package Includes

- TLP406USBUFO Conference
 Power Surge Protector
- · Owner's manual



Specifications

OVERVIEW UPC Code 037332260734 Product Type Surge Protector Charging Form Factor Strip Device Compatibility Amazon Kindle; Laptop; Phone; Tablet INPUT Noninal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V Voltage Compatibility (VAC) 120 Maximum Surge Amps 1800 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 6 Right-Angle Plug No Input Cord Length (m) 1.83 Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output (Wats) 1800 Output Receptacles (4) 5-15R Circuit Breaker (amps) 15 Right-Angle Outletis No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Response Time < 1ns Protection Modes Includes full normal mode (H-N) and common mode (N-G / H-G	_		
Product Type Surge Protector Charging Form Factor Strip Device Compatibility Amazon Kindle: Laptop: Phone: Tablet NPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V Voltage Compatibility (VAC) 120 Maximum Surge Amps 1800 Input Plug Type NEMA 5-1SP Input Cord Length (ft.) 6 Right-Angle Plug No Input Cord Length (m) 1.83 Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output Receptacles (4) 5-15R Circuit Breaker (amps) 15 Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1800 AC Suppression Response Time 1 Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression	OVERVIEW		
Charging Form Factor Strip Device Compatibility Amazon Kindle; Laptop; Phone; Tablet INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V Voltage Compatibility (VAC) 120 Maximum Surge Amps 1800 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 6 Right-Angle Plug No Input Cord Length (m) 1.83 Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output (Watts) 1800 Output Receptacles (4) 5-15R Circuit Breaker (amps) 15 Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1800 AC Suppression Response Time < 1ns Protection Modes Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression	UPC Code	037332260734	
Device Compatibility Amazon Kindle; Laptop; Phone; Tablet INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V Voltage Compatibility (VAC) 120 Maximum Surge Amps 1800 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 6 Right-Angle Plug No Input Cord Length (m) 1.83 Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output (Watts) 1800 Output (Watts) 1800 Culput Receptacles (4) 5-15R Circuit Breaker (amps) 15 Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1800 AC Suppression Response Time 7 Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression	Product Type	Surge Protector	
INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V Voltage Compatibility (VAC) 120 Maximum Surge Amps 1800 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 6 Right-Angle Plug No Input Cord Length (m) 1.83 Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output (Watts) 1800 Output Receptacles (4) 5-15R Circuit Breaker (amps) 15 Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1800 AC Suppression Response Time Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression	Charging Form Factor	Strip	
Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V Voltage Compatibility (VAC) 120 Maximum Surge Amps 1800 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 6 Right-Angle Plug No Input Cord Length (m) 1.83 Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output (Watts) 1800 Output Receptacles (4) 5-15R Circuit Breaker (amps) 15 Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1800 AC Suppression Response Time < 1ns	Device Compatibility	Amazon Kindle; Laptop; Phone; Tablet	
Recommended Electrical Service 120V Voltage Compatibility (VAC) 120 Maximum Surge Amps 1800 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 6 Right-Angle Plug No Input Cord Length (m) 1.83 Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output (Watts) 1800 Output Receptacles (4) 5-15R Circuit Breaker (amps) 15 Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1800 AC Suppression Joule Response Time 1 Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression	INPUT		
Voltage Compatibility (VAC) 120 Maximum Surge Amps 1800 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 6 Right-Angle Plug No Input Cord Length (m) 1.83 Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output (Watts) 1800 Output Receptacles (4) 5-15R Circuit Breaker (amps) 15 Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1800 AC Suppression Response Time < 1ns	Nominal Input Voltage(s) Supported	120V AC	
Maximum Surge Amps 1800 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 6 Right-Angle Plug No Input Cord Length (m) 1.83 Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output (Watts) 1800 Output Receptacles (4) 5-15R Circuit Breaker (amps) 15 Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1800 AC Suppression Response Time < 1ns	Recommended Electrical Service	120V	
Input Plug Type	Voltage Compatibility (VAC)	120	
Input Cord Length (ft.) 6 Right-Angle Plug No Input Cord Length (m) 1.83 Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output (Watts) 1800 Output Receptacles (4) 5-15R Circuit Breaker (amps) 15 Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1800 AC Suppression Response Time < 1ns Protection Modes Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression	Maximum Surge Amps	1800	
Right-Angle Plug Input Cord Length (m) Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output (Watts) 1800 Output Receptacles (4) 5-15R Circuit Breaker (amps) 15 Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1800 AC Suppression Response Time Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression	Input Plug Type	NEMA 5-15P	
Input Cord Length (m) Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output (Watts) 1800 Output Receptacles (4) 5-15R Circuit Breaker (amps) 15 Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1800 AC Suppression Response Time Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression	Input Cord Length (ft.)	6	
Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output (Watts) 1800 Output Receptacles (4) 5-15R Circuit Breaker (amps) 15 Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1800 AC Suppression Response Time < 1ns Protection Modes Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression	Right-Angle Plug	No	
OUTPUT Frequency Compatibility 60 Hz Output (Watts) 1800 Output Receptacles (4) 5-15R Circuit Breaker (amps) 15 Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1800 AC Suppression Response Time < 1ns Protection Modes Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression	Input Cord Length (m)	1.83	
Frequency Compatibility 60 Hz Output (Watts) 1800 Output Receptacles (4) 5-15R Circuit Breaker (amps) 15 Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1800 AC Suppression Response Time < 1ns Protection Modes Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression	Integrated Cord Clip	No	
Output (Watts) 1800 Output Receptacles (4) 5-15R Circuit Breaker (amps) 15 Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1800 AC Suppression Response Time < 1ns Protection Modes Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression	OUTPUT		
Output Receptacles (4) 5-15R Circuit Breaker (amps) 15 Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1800 AC Suppression Response Time < 1ns Protection Modes Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression	Frequency Compatibility	60 Hz	
Circuit Breaker (amps) 15 Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1800 AC Suppression Response Time < 1ns Protection Modes Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression	Output (Watts)	1800	
Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1800 AC Suppression Response Time < 1ns Protection Modes Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression	Output Receptacles	(4) 5-15R	
USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1800 AC Suppression Response Time < 1ns Protection Modes Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression	Circuit Breaker (amps)	15	
Diagnostic LED(s) SURGE / NOISE SUPPRESSION AC Suppression Joule Rating AC Suppression Response Time - 1ns Protection Modes Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression	Right-Angle Outlets	No	
SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1800 AC Suppression Response Time < 1ns Protection Modes Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression	USER INTERFACE, ALERTS & CONTROLS		
AC Suppression Joule Rating 1800 AC Suppression Response Time < 1ns Protection Modes Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression	Diagnostic LED(s)	Yes	
AC Suppression Response Time < 1ns Protection Modes Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression	SURGE / NOISE SUPPRESSION		
Protection Modes Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression	AC Suppression Joule Rating	1800	
	AC Suppression Response Time	< 1ns	
UL1449 Let Through Rating 800,800,800	Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression	
	UL1449 Let Through Rating	800,800,800	
EMI / RFI Filtering Yes	EMI / RFI Filtering	Yes	





Immunity	Conforms to IEE 587/ANSI C62.41	
Automatic Shut-Off	No	
CHARGING		
Charging Ports / Amps	(4) 4.2A	
Number of Charging Ports	4	
Charging Method	USB	
Charging Port Type	USB A (FEMALE)	
DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	No	
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
PHYSICAL		
Antimicrobial Coating	No	
Color	Black	
Color (AC Line Cord)	Black/Gray	
Housing Color	Black	
Integrated Keyhole Mounting Slots	Yes	
Material of Construction	Plastic	
Receptacle Color	Black	
Shipping Dimensions (hwd / cm)	7.87 x 18.54 x 18.54	
Shipping Dimensions (hwd / in.)	3.10 x 7.30 x 7.30	
Shipping Weight (kg)	0.77	
Shipping Weight (lbs.)	1.70	
Unit Dimensions (hwd / cm)	5.08 x 18 x 18	
Unit Dimensions (hwd / in.)	2 x 7.08 x 7.08	
SPECIAL FEATURES		
Rotatable Outlets	No	
STANDARDS & COMPLIANCE		
Canada	CAN/CSA-C22.2 No. 269.3:2017 (2nd Ed); CAN/CSA-C22.2 No.308-14	
Approvals	EXCEEDS IEEE 587 CATAGORY A&B SPECIFICATIONS	
UL1449 3rd Edition (AC Suppression)	UL1449 4th edition	
NOM (Mexico)	Y	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

UL1363 (Power Tap)	UL1363
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$2,500 Ultimate Lifetime Insurance

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies