

8-Outlet Surge Protector with 2 USB Ports (2.1A Shared) - 8 ft. (2.43 m) Cord, 1200 Joules, Tel/Modem, Black

MODEL NUMBER: TLP88TUSBB











8-outlet surge protector safeguards your home/office electronics against dangerous surges, spikes and line noise.

Features

8-Outlet Surge Protector with USB Safeguards Your Sensitive Electronics Ideal for your home or office workstation, this Protect It!® 8-outlet surge protector features a surge protection rating of 1200 joules to defend your sensitive electronic components against strong power surges and spikes. Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the TLP88TUSBB protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G).

NEMA 5-15R Outlets Accept a Wide Range of Electronic DevicesPlug your PC, printer, wireless router, game console, television, sound system or other home/office electronics into eight NEMA 5-15R outlets to protect them against dangerous surges, spikes and line noise. Three outlets are widely spaced to accommodate bulky power transformers without blocking adjacent outlets. Built-in safety covers prevent dust and debris from falling into unused outlets.

RJ11 Cable Surge Protection Covers All Your BasesBuilt-in RJ11 jacks allow connection of telephone, fax and modem equipment. The TLP88TUSBB prevents dangerous "back door" power surges from damaging your data line components.

2 USB Ports Share 2.1 Amps of Charging PowerThis surge protector with 2 USB ports is ideal for keeping your devices at full capacity. Two USB-A ports are available for charging your smartphone, tablet and other USB mobile devices.

Premium Protection from EMI/RFI Line Noise Helps Your Equipment Perform Better Various electromagnetic and radio sources found in virtually every home and business can cause disruptive interference on the AC line. Known as EMI (electromagnetic interference) and RFI (radio frequency interference), this line noise is a common cause of performance problems. This surge protector filters out disruptive line noise that can disturb your electronics and inflict hardware damage or data loss. This EMI/RFI filtering also helps your connected components perform better and last longer.

Includes the Latest Safety FeaturesThe lighted on/off switch provides one-touch control over connected equipment. A green LED confirms your connected equipment is protected.

Highlights

- 8 NEMA 5-15R outlets distribute AC power to connected home/office equipment
- 1200 joules protect your valuable electronics against dangerous surges and spikes
- 2 USB ports share 2.1A for fast charging of phones, tablets and other mobile devices
- 8-ft. (2.43 m) cord with NEMA 5-15P plug allows flexibility in placing devices away from AC outlet
- RJ11 cable connectors offer surge protection to phone/fax/modem equipment

Applications

- Protect computers, peripherals, home theater equipment and other valuable electronics against AC power surges and spikes
- Filter potentially damaging line noise to improve connected equipment's performance and lifespan
- Safeguard valuable data against corruption stemming from unexpected surges
- Charge smartphones, tablets or other USB devices via USB ports

Package Includes

- TLP88TUSBB Protect It! 8-Outlet Surge Protector, Black
- Owner's manual



Versatile Surge Protector Provides Multiple Installation Options This surge protector with 8-ft. (2.43 m) cord and space-saving right-angle NEMA 5-15P plug helps you connect to a wall outlet located behind furniture placed flush against the wall. Keyhole slots incorporated into the bottom panel provide convenient wall or desk mounting options for the black plastic housing.

Specifications

OVERVIEW		
UPC Code	037332223579	
Product Type	Surge Protector	
Charging Form Factor	Strip	
Device Compatibility	Phone; Tablet; Amazon Kindle	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input Plug Features	Right Angle	
Input Cord Gauge Type	14 gauge; SJT	
Input Cord Gauge (AWG)	14	
Voltage Compatibility (VAC)	120	
Maximum Surge Amps	35500	
Input Plug Type	NEMA 5-15P	
Input Cord Details	SJT	
Input Cord Length (ft.)	8	
Right-Angle Plug	Yes	
Input Cord Length (m)	2.44	
Integrated Cord Clip	No	
оитрит		
Frequency Compatibility	50 / 60 Hz	
Output Receptacles	(8) 5-15R	
Circuit Breaker (amps)	15	
Overload Protection	15A resettable illuminated combo switch / circuit breaker	
Transformer Accommodation	(6) Yes	
Outlet Orientation	Double row of 8 outlets total	
Right-Angle Outlets	Yes	



Switches Combination AC circuit breaker and 2 position red illuminated on/oif power switch CHARGING CHARGING Value of Charging Potts 2 Colspan="2">Colspa	Diagnostic LED(s)	Yes		
CHARGING Number of Charging Ports 2 Total Charging Watts 10.5 Charging Method USB Charging Port Type USB A (FEMALE) Charging Port Fype USB A (FEMALE) Charging Ports / Amps (2) 2.1A Overcharge Protection No SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1200 AC Suppression Response Time <1 ns	Switches	Combination AC circuit breaker and 2 position red illuminated on/off power switch		
Number of Charging Ports 2 Total Charging Watts 10.5 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 2.1A Overcharge Protection No SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1200 AC Suppression Response Time < 1 ns	Diagnostic LED Details	Built-in LED confirms suppressor "protection present" (green) status		
Total Charging Watts 10.5 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 2.1A Overcharge Protection No SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1200 AC Suppression Response Time < 1 ns	CHARGING	CHARGING		
Charging Method USB A (FEMALE) Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 2.1A Overcharge Protection No SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1200 AC Suppression Response Time < 1 ns Protection Modes Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression UL1-449 Let Through Rating 500,500,500 EMI / RFI Filtering Yes Automatic Shut-Off No DATALINE SURGE SUPPRESSION Telephone/DSL Protection Details 1 line in/2 line out Cable (Coax) Protection No Network (Ethernet) Protection No Network (Ethernet) Protection Yes PHYSICAL Material of Construction Plastic Power Cord Color Black Housing Color Black Mounting Holes or Slots Yes Receptacle Color Black Shipping Weight (kg) 0.85 Unit Dimensions	Number of Charging Ports	2		
Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 2.1A Overcharge Protection No SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1200 AC Suppression Response Time < 1 ns Protection Modes Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression UL1449 Let Through Rating 500,500,500 EMI / RFI Filtering Yes Automatic Shut-Off No DATALINE SURGE SUPPRESSION Telephone/DSL Protection Details 1 line in/2 line out Cable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL PHYSICAL PHYSICAL Physical (Construction Plastic Plastic Power Cord Color Black Housing Color Black Mounting Holes or Slots Yes Receptacle Color Black Shipping Dimensions (hwd / in.) 11.02 x 7.09 x 1.50 Shipping Weight (kg)	Total Charging Watts	10.5		
Charging Ports / Amps (2) 2.1A Overcharge Protection No SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1200 AC Suppression Response Time <1 ns	Charging Method	USB		
Overcharge Protection No SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 1200 AC Suppression Response Time < 1 ns	Charging Port Type	USB A (FEMALE)		
AC Suppression Joule Rating 1200 AC Suppression Response Time < 1 ns Protection Modes Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression UL1449 Let Through Rating 500.500,500 EMI / RFI Filtering Yes Automatic Shut-Off No PATALINE SURGE SUPPRESSION Telephone/DSL Protection Details 1 line in/2 line out Cable (Coax) Protection No Network (Ethernet) Protection No Telephone/DSL Protection Yes PHYSICAL Material of Construction Plastic Power Cord Color Black Housing Color Black Mounting Holes or Slots Yes Receptacle Color Black Shipping Dimensions (hwd / in.) 11.02 x 7.09 x 1.50 Shipping Weight (kg) 0.85 Unit Dimensions (hwd / in.) 23.11 x 9.60 x 3.30 Int Dimensions (hwd / in.) 23.11 x 9.60 x 3.30 Int Dimensions (hwd / on.) 2.311 x 9.60 x 3.30	Charging Ports / Amps	(2) 2.1A		
AC Suppression Joule Rating 1200 AC Suppression Response Time < 1 ns	Overcharge Protection	No		
AC Suppression Response Time < 1 ns	SURGE / NOISE SUPPRESSION			
Protection Modes Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression UL 1449 Let Through Rating 500,500,500 EMI / RFI Filtering Yes Automatic Shut-Off No No PATALINE SURGE SUPPRESSION Telephone/DSL Protection Details 1 line in/2 line out Cable (Coax) Protection No Network (Ethernet) Protection No Telephone/DSL Protection Yes PHYSICAL Material of Construction Plastic Power Cord Color Black Housing Color Black Mounting Holes or Slots Yes Receptacle Color Black Receptacle Color Black Nounting Dimensions (hwd / in.) 11.02 x 7.09 x 1.50 Shipping Weight (kg) 0.85 Unit Dimensions (hwd / rm) 23.11 x 9.60 x 3.30 Line In India and common mode (N-G / H-G) line suppression No 10.00,000,000 No No No No No No No No No	AC Suppression Joule Rating	1200		
UL1449 Let Through Rating 500,500,500 EMI / RFI Filtering Yes Automatic Shut-Off No DATALINE SURGE SUPPRESSION Telephone/DSL Protection Details 1 line in/2 line out Cable (Coax) Protection No Network (Ethernet) Protection No Telephone/DSL Protection Yes PHYSICAL Material of Construction Plastic Power Cord Color Black Housing Color Black Mounting Holes or Slots Yes Receptacle Color Black Shipping Dimensions (hwd / in.) 11.02 x 7.09 x 1.50 Shipping Weight (kg) 0.85 Unit Dimensions (hwd / in.) 9.100 x 3.780 x 1.300 Unit Dimensions (hwd / cm) 23.11 x 9.60 x 3.30	AC Suppression Response Time	<1 ns		
EMI / RFI Filtering Yes Automatic Shut-Off No DATALINE SURGE SUPPRESSION Telephone/DSL Protection Details 1 line in/2 line out Cable (Coax) Protection Details 1 line in/2 line out Cable (Coax) Protection No Network (Ethernet) Protection No Telephone/DSL Protection Yes PHYSICAL Material of Construction Plastic Power Cord Color Black Housing Color Black Mounting Holes or Slots Yes Receptacle Color Black Shipping Dimensions (hwd / in.) 11.02 x 7.09 x 1.50 Shipping Weight (kg) 0.85 Unit Dimensions (hwd / rm) 2.3.11 x 9.60 x 3.30	Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression		
Automatic Shut-Off No DATALINE SURGE SUPPRESSION Telephone/DSL Protection Details 1 line in/2 line out Cable (Coax) Protection No Network (Ethernet) Protection No Telephone/DSL Protection Yes PHYSICAL Material of Construction Plastic Power Cord Color Black Housing Color Black Mounting Holes or Slots Yes Receptacle Color Black Shipping Dimensions (hwd / in.) 11.02 x 7.09 x 1.50 Shipping Weight (kg) 0.85 Unit Dimensions (hwd / cm) 23.11 x 9.60 x 3.30 Unit Dimensions (hwd / cm) 23.11 x 9.60 x 3.30	UL1449 Let Through Rating	500,500,500		
DATALINE SURGE SUPPRESSION Telephone/DSL Protection Details 1 line in/2 line out Cable (Coax) Protection No Network (Ethernet) Protection No Telephone/DSL Protection Yes PHYSICAL Material of Construction Plastic Power Cord Color Black Housing Color Black Mounting Holes or Slots Yes Receptacle Color Black Shipping Dimensions (hwd / in.) 1.02 x 7.09 x 1.50 Shipping Weight (kg) 0.85 Unit Dimensions (hwd / or.) 2.3.11 x 9.60 x 3.30 Unit Dimensions (hwd / cm) 2.3.11 x 9.60 x 3.30	EMI / RFI Filtering	Yes		
Telephone/DSL Protection Details 1 line in/2 line out Cable (Coax) Protection No Network (Ethernet) Protection No Telephone/DSL Protection Yes PHYSICAL Material of Construction Plastic Power Cord Color Black Mounting Holes or Slots Yes Receptacle Color Black Shipping Dimensions (hwd / in.) 11.02 x 7.09 x 1.50 Shipping Weight (kg) 0.85 Unit Dimensions (hwd / cm) 23.11 x 9.60 x 3.30	Automatic Shut-Off	No		
Cable (Coax) Protection No Network (Ethernet) Protection No Telephone/DSL Protection Yes PHYSICAL Material of Construction Plastic Power Cord Color Black Housing Color Black Mounting Holes or Slots Yes Receptacle Color Black Shipping Dimensions (hwd / in.) 11.02 x 7.09 x 1.50 Shipping Weight (kg) 0.85 Unit Dimensions (hwd / cm) 23.11 x 9.60 x 3.30	DATALINE SURGE SUPPRESSION			
Network (Ethernet) Protection No Telephone/DSL Protection Yes PHYSICAL Material of Construction Plastic Power Cord Color Black Housing Color Black Mounting Holes or Slots Yes Receptacle Color Black Shipping Dimensions (hwd / in.) 11.02 x 7.09 x 1.50 Shipping Weight (kg) 0.85 Unit Dimensions (hwd / cm) 23.11 x 9.60 x 3.30	Telephone/DSL Protection Details	1 line in/2 line out		
PHYSICAL Material of Construction Plastic Power Cord Color Black Housing Color Black Mounting Holes or Slots Yes Receptacle Color Black Shipping Dimensions (hwd / in.) 11.02 x 7.09 x 1.50 Shipping Weight (kg) 0.85 Unit Dimensions (hwd / cm) 23.11 x 9.60 x 3.30	Cable (Coax) Protection	No		
PHYSICAL Material of Construction Plastic Power Cord Color Black Housing Color Black Mounting Holes or Slots Yes Receptacle Color Black Shipping Dimensions (hwd / in.) 11.02 x 7.09 x 1.50 Shipping Weight (kg) 0.85 Unit Dimensions (hwd / cm) 23.11 x 9.60 x 3.30	Network (Ethernet) Protection	No		
Material of Construction Plastic Power Cord Color Black Housing Color Black Mounting Holes or Slots Yes Receptacle Color Black Shipping Dimensions (hwd / in.) 11.02 x 7.09 x 1.50 Shipping Weight (kg) 0.85 Unit Dimensions (hwd / cm) 23.11 x 9.60 x 3.30	Telephone/DSL Protection	Yes		
Material of Construction Plastic Power Cord Color Black Housing Color Black Mounting Holes or Slots Yes Receptacle Color Black Shipping Dimensions (hwd / in.) 11.02 x 7.09 x 1.50 Shipping Weight (kg) 0.85 Unit Dimensions (hwd / cm) 23.11 x 9.60 x 3.30	DUVOICAL			
Power Cord Color Black Housing Color Black Mounting Holes or Slots Receptacle Color Black Shipping Dimensions (hwd / in.) 11.02 x 7.09 x 1.50 Shipping Weight (kg) 0.85 Unit Dimensions (hwd / cm) 23.11 x 9.60 x 3.30		Plastic		
Housing Color Mounting Holes or Slots Yes Receptacle Color Shipping Dimensions (hwd / in.) 11.02 x 7.09 x 1.50 Shipping Weight (kg) 0.85 Unit Dimensions (hwd / in.) 9.100 x 3.780 x 1.300 Unit Dimensions (hwd / cm) 23.11 x 9.60 x 3.30				
Mounting Holes or Slots Receptacle Color Black Shipping Dimensions (hwd / in.) 11.02 x 7.09 x 1.50 Shipping Weight (kg) 0.85 Unit Dimensions (hwd / in.) 9.100 x 3.780 x 1.300 Unit Dimensions (hwd / cm) 23.11 x 9.60 x 3.30				
Receptacle Color Black Shipping Dimensions (hwd / in.) 11.02 x 7.09 x 1.50 Shipping Weight (kg) 0.85 Unit Dimensions (hwd / in.) 9.100 x 3.780 x 1.300 Unit Dimensions (hwd / cm) 23.11 x 9.60 x 3.30				
Shipping Dimensions (hwd / in.) 11.02 x 7.09 x 1.50 Shipping Weight (kg) 0.85 Unit Dimensions (hwd / in.) 9.100 x 3.780 x 1.300 Unit Dimensions (hwd / cm) 23.11 x 9.60 x 3.30				
Shipping Weight (kg) 0.85 Unit Dimensions (hwd / in.) 9.100 x 3.780 x 1.300 Unit Dimensions (hwd / cm) 23.11 x 9.60 x 3.30				
Unit Dimensions (hwd / in.) 9.100 x 3.780 x 1.300 Unit Dimensions (hwd / cm) 23.11 x 9.60 x 3.30				
Unit Dimensions (hwd / cm) 23.11 x 9.60 x 3.30				
	Unit Weight (lbs.)			



Unit Weight (kg)	0.66	
FEATURES & SPECIFICATIONS		
Rotatable Outlets	No	
Antimicrobial	No	
GaN Technology	No	
STANDARDS & COMPLIANCE		
Product Certifications	CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL 497A; UL 1363; UL Listed	
Product Compliance	FCC Part 68; RoHS	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$75,000 Ultimate Lifetime Insurance	



© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.