

# USB 3.2 Gen 1 SuperSpeed Device Cable (A to B M/M) Black, 15 ft. (4.57 m)

### MODEL NUMBER: U322-015-BK





Highlights

- 15-ft SuperSpeed USB 3.2 Gen 1 A-B Cable
- 10 times faster than USB 2.0 with transfer rates up to 5 Gbps

#### **System Requirements**

• Computers and peripherals with USB 3.2 Gen 1 capability

#### Package Includes

 15-ft. USB 3.2 Gen 1 SuperSpeed A-B Device Cable -Black

Connect USB 3.2 Gen 1 computers to USB 3.2 Gen 1 enabled peripherals such as hard drives and printers.

#### Features

- 15-ft USB 3.2 Gen 1 SuperSpeed Cable Black
- SuperSpeed USB is 10 times faster than Hi-Speed USB, with transfer rates up to 5 Gbps
- Sync-N-Go technology minimizes user wait-time
- Provides Optimized Power Efficiency...No device polling and lower active and idle power requirements
- Backwards compatible with USB 2.0. Devices operate with USB 2.0 platforms. Hosts support USB 2.0 legacy devices

## **Specifications**

| OVERVIEW                  |              |
|---------------------------|--------------|
| UPC Code                  | 037332183149 |
| Technology                | USB 3.x      |
| USB Cable Type            | Passive      |
| PHYSICAL                  |              |
| Material of Construction  | PVC          |
| Cable Jacket Color        | Black        |
| Cable Jacket Rating       | VW-1         |
| Cable Outer Diameter (OD) | 5.5MM        |
| Cable Length (ft.)        | 15           |



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

| Cable Length (m)                       | 4.57                                |
|----------------------------------------|-------------------------------------|
| Cable Length (in.)                     | 180                                 |
| Shipping Dimensions (hwd / in.)        | 7.00 x 9.00 x 0.50                  |
| Shipping Dimensions (hwd / cm)         | 17.78 x 22.86 x 1.27                |
| Shipping Weight (lbs.)                 | 0.50                                |
| Shipping Weight (kg)                   | 0.23                                |
| ENVIRONMENTAL                          |                                     |
| Operating Temperature Range            | 14 to 140 F (-10 to 60 C)           |
| Storage Temperature Range              | -4 to 185 F (-20 to 85 C)           |
| Relative Humidity                      | 10% to 85%, Non-Condensing          |
| CONNECTIONS                            |                                     |
| Side A - Connector 1                   | USB A (MALE)                        |
| Side B - Connector 1                   | USB B (MALE)                        |
| Connector Plating                      | Nickel                              |
| Contact Plating                        | Gold                                |
| FEATURES & SPECIFICATIONS              |                                     |
| USB Specification                      | USB 3.2 Gen 1 (up to 5 Gbps)        |
| STANDARDS & COMPLIANCE                 |                                     |
| Product Compliance                     | RoHS; CE (Europe); REACH; FCC (USA) |
| WARRANTY & SUPPORT                     |                                     |
| Product Warranty Period<br>(Worldwide) | Lifetime limited warranty           |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies