

USB Dock, Triple Display - 4K HDMI & mDP, VGA, USB 3.2 Gen 1, USB-A/C Hub, GbE, 60W PD Charging

MODEL NUMBER: U442-DOCK16-B











USB-C dock with PD Charging connects up to 3 displays to your tablet or Windows laptop and transmits video to all 3 simultaneously.

Features

USB-C Docking Station Turns Your Device's USB-C or Thunderbolt 3 Port into a WorkstationThis multiport USB-C dock with PD Charging expands the potential of your Windows laptop, Chromebook, tablet or other device with a USB-C or Thunderbolt 3 port. It's ideal for transmitting 4K video and digital audio to multiple large displays, adding a thumb drive and other USB peripherals, powering and charging a PD Charging-compliant mobile device, and connecting to a Gigabit Ethernet network—all at the same time.

Supports USB-C DisplayPort Alternate Mode for Transmitting Audio/Video SignalsBy connecting the built-in USB-C cable to a source device that supports USB DisplayPort Alt Mode, you can output 4K video and digital audio to a compatible monitor, television or projector without installing special software drivers. Note: only one 4K display can be extended in an application. See the owner's manual for various configurations and maximum resolutions.

Transmits Crystal-Clear 4K Video and Digital AudioThe HDMI and Mini DisplayPort (mDP) outputs support true 4K resolutions up to 4096 x 2160 at 30 Hz. The VGA port supports HD resolutions up to 1920 x 1200, including 1080p, at 60 Hz.

Extends High-Definition Video Across All 3 External Displays at the Same TimeBy connecting the self-storing USB-C cable to a source that supports DisplayPort MST (Multi-Stream Transport) mode, you may connect up to three monitors simultaneously. With a Windows source device, you can display the same image on all connected monitors, extend the host desktop across them with different windows open on each, or combine them into one large display as a video wall. Note: macOS laptops or computers will only extend to one monitor. The other monitors will be mirrored. See the owner's manual for various configurations and maximum resolutions.

USB Ports Connect Keyboards, Thumb Drives and Other PeripheralsA USB-A port and a USB-C port accept USB peripherals, such as flash drives, mice, keyboards and printers. Both support fast USB 3.2 Gen 1 data transfer rates up to 5 Gbps and are backward compatible with USB 2.0 and USB 1.1 devices. Note: Host must support USB OTG (On-the-Go).

Highlights

- Connects 3 displays at the same time for easy multitasking and increasing productivity
- Converts audio/video signals from sources supporting USB-C DisplayPort Alt Mode
- Supports 20V 3A (60W) power output for fast-charging largecapacity mobile devices
- Joins a wired 10/100/1000 Gigabit Ethernet network when no Wi-Fi is available
- USB-C and USB-A data ports allow connection of flash drives and other peripherals

Applications

- Extend or mirror your laptop or PC monitor on multiple displays to aid in multitasking and increase productivity
- Transfer data to and from a USB flash drive or external hard drive
- Access a wired Ethernet network in a location with no or spotty Wi-Fi
- Charge your notebook or laptop by connecting its wall charger to the USB-C PD Charging port
- Connect a microphone/headset to record a podcast or listen to music

System Requirements

- Source device with USB-C or Thunderbolt 3 port that supports USB DisplayPort Alternate Mode
- Display device with Mini DisplayPort, VGA and/or HDMI input

Package Includes

- U442-DOCK16-B USB-C Dock, Triple Display, Black
- Owner's manual



PD Charging Port Charges the Connected Notebook, Tablet or Other DeviceThe USB-C Power Delivery port supports power output up to 20V 3A (60W), which is sufficient for charging and powering the connected source device, such as an Android smartphone or Chromebook. Just connect the device's AC wall charger to the USB-C PD port. This port, as mentioned above, can also be used for transferring data up to 5 Gbps. Note: USB-C PD port does not support Quick Charge (QC).

Accesses a Wired Gigabit Ethernet NetworkThe RJ45 port offers access to a Gigabit Ethernet network when Wi-Fi is unavailable or when a wired connection offers faster speeds. Connect using a UTP cable (N201-Series Cat6 cables sold separately), and enjoy true 10/100/1000 Mbps Ethernet speeds for fast data transfers.

Self-Storing USB-C Connector Attaches in Either DirectionUnlike traditional USB cables that connect in only one direction, the reversible USB-C male connector plugs into a USB-C or Thunderbolt 3 port in either direction for an instant connection every time. The built-in cable fits within the base of the dock for convenient storage.

Ready to Use Right Out of the PackageThe plug-and-play USB-C dock is specifically designed for use with Windows laptops and other notebooks, smartphones, tablets and devices equipped with a USB-C or Thunderbolt 3 port. It requires no software or external power source. It's slightly larger than an average smartphone, but compact enough to fit easily into your desk space without taking up much valuable room.

Specifications

OVERVIEW	
UPC Code	037332253620
Product Type	Docking Station
Technology	HDMI; Stereo Audio
Host Connector	USB C (MALE)
VIDEO	
Number of Monitors Supported	3
Video Ports	MINI DISPLAYPORT (FEMALE); HDMI (FEMALE); HD15 (FEMALE)
Video Ports Details	DisplayPort 1.2; HDMI 1.4; HDCP 1.4
Resolutions Supported	Mini DisplayPort: 4K 30Hz (4096 x 2160)HDMI: 4K 30Hz (3840 x 2160)VGA: 1920 x 1200 60Hz
Max Supported Video Resolution	HDMI/mDP: 4096 x 2160 @30Hz; VGA: 1920 x 1080 @60Hz
Extended Mode	Yes
Extended Mode Details	1x HDMI (4K 30Hz) + 1x VGA (1080p 60Hz)1x Mini DP (4K 30Hz) + 1x VGA (1080p 60Hz)1x HDMI (4K 30Hz) + 1x Mini DP (4K30Hz)1x HDMI (1080p 60Hz) + 1x Mini DP (1080p 60Hz) + 1x VGA (1600x900 60Hz)
Mirror Mode	Yes
Mirror Mode Details	1x HDMI (4K 30Hz) + 1x VGA (1080p 60Hz)1x Mini DP (4K 30Hz) + 1x VGA (1080p 60Hz)1x HDMI (4K 30Hz) + 1x Mini DP (4K 30Hz)1x HDMI (1080p 60Hz) + 1x Mini DP (1080p 60Hz) + 1x VGA (1600x900 60Hz)
Max Supported Color Depth	36-bit Deep Color
HDR Support	No
Chroma Sub Sampling	4:2:0; 4:2:2; 4:4:4



DATA			
Data Ports	(2) USB A (FEMALE); (1) USB C (FEMALE)		
Data Ports Details	(2) USB-A - USB 3.2 Gen 1 (5 Gbps); (1) USB-C - USB 3.2 Gen 1 (5 Gbps)		
NETWORK	NETWORK		
Network Ports	RJ45 (FEMALE)		
INPUT			
Built-In Cable Length (ft.)	0.49		
Built-In Cable Length (m)	0.15		
Built-In Cable Length (in.)	5.9		
Built-In Cable Length (cm)	15		
Bus Powered	Yes		
BATTERY			
Battery Charging (5V/1.5A Port)	No		
POWER			
USB Power Delivery (PD) Charging Support	Yes		
USB Power Delivery (PD) Charging Specification	3.0		
USER INTERFACE, ALERTS & CONTROLS			
LED Indicators	White (Connection to Power)		
CHARGING			
Total Charging Watts	60		
Charging Ports	USB-C: 60W (20V 3A) Power Delivery (PD 3.0)		
Charging Ports / Amps	(1) 3A		
PHYSICAL			
Color	Gray		
Material of Construction	Aluminum		
Cable Jacket Rating	VW-1		
Shipping Dimensions (hwd / in.)	0.98 x 7.87 x 3.94		
Shipping Weight (lbs.)	0.51		
Unit Dimensions (hwd / in.)	1.310 x 3.860 x 0.450		



Unit Weight (Ibs.)	[
Unit Weight (kg) 0.07 ENVIRONMENTAL Operating Temperature Range 32° to 122°F (0° to 50°C) Storage Temperature Range 4° to 158°F (-20° to 70°C) Operating Humidity Range 10% to 90% RH, Non-Condensing Storage Humidity Range 0% to 95% RH, Non-Condensing Power Provided to Connected USB-C PD: 20V/3A (60W), USB2.0-A: 5V/0.5A (2.5W) COMMUNICATIONS Network Compatibility 1 Stops (Gigabit) CONNECTIONS Number of Ports 7 Dock Connectors VGA, HDMI, Mini DisplayPort, (2) USB-A 3.0, RJ45, USB-C PD Charging/Data Side A - Connector 1 USB C (MALE) Side B - Connector 1 HD16 (FEMALE), HDMI (FEMALE), MINI DISPLAYPORT (FEMALE) Side B - Connector 2 (2) USB A (FEMALE), USB C (FEMALE) Side B - Connector 3 RJ45 (FEMALE) VEST HUM PORTS USB Specification Ves UASB Specification USB 3.0 (up to 5 Gbps); USB 3.2 Gen 1 (up to 5 Gbps) UASB Specification Ves UASP Support Yes UASP Support Yes		Box	
Communication Commun	Unit Weight (lbs.)	0.15	
Operating Temperature Range 32* to 122*F (0* to 50°C) Storage Temperature Range -4* to 158*F (-20* to 70°C) Operating Humidity Range 10% to 90% RH, Non-Condensing Storage Humidity Range 0% to 95% RH, Non-Condensing Power Provided to Connected Device(s) USB-C PD: 20V/3A (60W), USB2.0-A: 5V/0.5A (2.5W) COMMUNICATIONS Number of Ports 7 7 Dock Connectors VGA, HDMI, Mini DisplayPort, (2) USB-A 3.0, RJ45, USB-C PD Charging/Data Side B - Connector 1 USB C (MALE) Side B - Connector 2 (2) USB A (FEMALE): HDMI (FEMALE): MINI DISPLAYPORT (FEMALE) Side B - Connector 3 RJ45 (FEMALE) FEATURES & SPECIFICATIONS USB Hub Ports 3 USB Specification USB Specification USB 3.0 (up to 5 Gbps); USB 3.2 Gen 1 (up to 5 Gbps) Ethernet Support Yes UASP Support Yes Full Duplex Support Yes Suspend Mode Support Yes Remote Wakeup Support No Displayort Specification 1.2 HDCP Specification	Unit Weight (kg)	0.07	
Storage Temperature Range	ENVIRONMENTAL		
Operating Humidity Range 10% to 95% RH, Non-Condensing Storage Humidity Range 0% to 95% RH, Non-Condensing Power Provided to Connected USB-C PD: 20V/3A (60W), USB2.0-A: 5V/0.5A (2.5W) COMMUNICATIONS Network Compatibility 1 Gbps (Gigabit) CONNECTIONS Number of Ports 7 Dock Connectors VGA, HDMI, Mini DisplayPort, (2) USB-A 3.0, RJ45, USB-C PD Charging/Data Side A - Connector 1 USB C (MALE) Side B - Connector 2 (2) USB A (FEMALE); HDMI (FEMALE); MINI DISPLAYPORT (FEMALE) Side B - Connector 3 RJ45 (FEMALE) Side B - Connector 3 RJ45 (FEMALE) USB Hub Ports USB Hub Ports USB 3.0 (up to 5 Gbps); USB 3.2 Gen 1 (up to 5 Gbps) Ethernet Support Yes UASP Support No Auto MDIX Support Yes Suspend Mode Support Yes Suspend Mode Support No Displayport Specification 1.2 HDCPS Specification 1.4 Diver Required No	Operating Temperature Range	32° to 122°F (0° to 50°C)	
Storage Humidity Range 0% to 95% RH, Non-Condensing Power Provided to Connected Device(s) COMMUNICATIONS Network Compatibility 1 Gbps (Gigabit) CONNECTIONS Number of Ports 7 Dock Connectors VGA, HDMI, Mini DisplayPort, (2) USB-A 3.0, RJ45, USB-C PD Charging/Data Side A - Connector 1 USB C (MALE) Side B - Connector 1 HD15 (FEMALE); HDMI (FEMALE); MINI DISPLAYPORT (FEMALE) Side B - Connector 3 RJ45 (FEMALE) Side B - Connector 3 RJ45 (FEMALE) FEATURES & SPECIFICATIONS USB Subspecification USB 3.0 (up to 5 Gbps); USB 3.2 Gen 1 (up to 5 Gbps) Ethernet Support Yes UASP Support Yes Suspend Mode Support Yes Remote Wakeup Support No Displayport Specification 1.4 HD5 (FEMALE) HD6 (HD7) Power Required No Displayport Specification 1.4 HD7 (FEMALE) HD7 (HD7) Power Required No Displayport Specification 1.4 HD7 (FEMALE) HD7 (HD7) Power Required No Displayport Specification 1.4 HD7 (HD7) Power Required No Displayport Power Required No Displayport Specification 1.4 HD7 (HD7) Power Required No Displayport 1.4 HD7 (HD7) Power Required No Displayport 1.4 HD7 (HD7) Power Required No Displaypor	Storage Temperature Range	-4° to 158°F (-20° to 70°C)	
Power Provided to Connected Device(s) COMMUNICATIONS Network Compatibility 1 Gbps (Gigabit) CONNECTIONS Number of Ports 7 Dock Connectors VGA, HDMI, Mini DisplayPort, (2) USB-A 3.0, RJ45, USB-C PD Charging/Data Side A - Connector 1 USB C (MALE) Side B - Connector 1 HD15 (FEMALE); HDMI (FEMALE); MINI DISPLAYPORT (FEMALE) Side B - Connector 2 (2) USB A (FEMALE): USB C (FEMALE) Side B - Connector 3 RJ45 (FEMALE) Side B - Connector 4 RJ45 (FEMALE) Side B - Connector 5 RJ45 (FEMALE) Side B - Connector 6 RJ45 (FEMALE) Side B - Connector 7 RJ45 (FEMALE) Side B - Connector 7 RJ45 (FEMALE) Side B - Connector 1 RJ45 (FEMALE) Side B - Connector	Operating Humidity Range	10% to 90% RH, Non-Condensing	
COMMUNICATIONS Network Compatibility 1 Gbps (Gigabit) CONNECTIONS Number of Ports 7 Dock Connectors VGA, HDMI, Mini DisplayPort, (2) USB-A 3.0, RJ45, USB-C PD Charging/Data Side A - Connector 1 USB C (MALE) Side B - Connector 2 (2) USB A (FEMALE); HDMI (FEMALE); MINI DISPLAYPORT (FEMALE) Side B - Connector 3 RJ45 (FEMALE) Side B - Connector 3 RJ45 (FEMALE) Side B - Connector 3 RJ45 (FEMALE) FEATURES & SPECIFICATIONS USB Hub Ports 7 USB Specification USB 3.0 (up to 5 Gbps); USB 3.2 Gen 1 (up to 5 Gbps) Ethernet Support Yes Full Duplex Support No Auto MDIX Support Yes Suspend Mode Support Yes Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.4 Driver Required No	Storage Humidity Range	0% to 95% RH, Non-Condensing	
Nework Compatibility 1 Gbps (Gigabit) CONNECTIONS Number of Ports 7 Dock Connectors VGA, HDMI, Mini DisplayPort, (2) USB-A 3.0, RJ45, USB-C PD Charging/Data Side A - Connector 1 USB C (MALE) Side B - Connector 1 HD15 (FEMALE); HDMI (FEMALE); MINI DISPLAYPORT (FEMALE) Side B - Connector 2 (2) USB A (FEMALE); USB C (FEMALE) Side B - Connector 3 RJ45 (FEMALE) FEATURES & SPECIFICATIONS USB Hub Ports Yes Number of USB Hub Ports 3 USB Specification USB 3.0 (up to 5 Gbps); USB 3.2 Gen 1 (up to 5 Gbps) Ethernet Support Yes UASP Support No Auto MDIX Support Yes Suspend Mode Support Yes Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.4 Driver Required No	Power Provided to Connected Device(s)	USB-C PD: 20V/3A (60W), USB2.0-A: 5V/0.5A (2.5W)	
Number of Ports 7 Dock Connectors VGA, HDMI, Mini DisplayPort, (2) USB-A 3.0, RJ45, USB-C PD Charging/Data Side A - Connector 1 USB C (MALE) Side B - Connector 1 HD15 (FEMALE); HDMI (FEMALE); MINI DISPLAYPORT (FEMALE) Side B - Connector 2 (2) USB A (FEMALE); USB C (FEMALE) Side B - Connector 3 RJ45 (FEMALE) FEATURES & SPECIFICATIONS USB Hub Ports Yes Number of USB Hub Ports 3 USB Specification USB 3.0 (up to 5 Gbps); USB 3.2 Gen 1 (up to 5 Gbps) Ethernet Support Yes UASP Support No Auto MDIX Support Yes Suspend Mode Support Yes Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.4 Driver Required No	COMMUNICATIONS		
Number of Ports 7 Dock Connectors VGA, HDMI, Mini DisplayPort, (2) USB-A 3.0, RJ45, USB-C PD Charging/Data Side A - Connector 1 USB C (MALE) Side B - Connector 1 HD15 (FEMALE): HDMI (FEMALE); MINI DISPLAYPORT (FEMALE) Side B - Connector 2 (2) USB A (FEMALE): USB C (FEMALE) FEATURES & SPECIFICATIONS USB Hub Ports Yes Number of USB Hub Ports 3 USB Specification USB 3.0 (up to 5 Gbps); USB 3.2 Gen 1 (up to 5 Gbps) Ethernet Support Yes UASP Support No Auto MDIX Support Yes Suspend Mode Support Yes Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.4 Driver Required No	Network Compatibility	1 Gbps (Gigabit)	
Number of Ports 7 Dock Connectors VGA, HDMI, Mini DisplayPort, (2) USB-A 3.0, RJ45, USB-C PD Charging/Data Side A - Connector 1 USB C (MALE) Side B - Connector 1 HD15 (FEMALE): HDMI (FEMALE); MINI DISPLAYPORT (FEMALE) Side B - Connector 2 (2) USB A (FEMALE): USB C (FEMALE) FEATURES & SPECIFICATIONS USB Hub Ports Yes Number of USB Hub Ports 3 USB Specification USB 3.0 (up to 5 Gbps); USB 3.2 Gen 1 (up to 5 Gbps) Ethernet Support Yes UASP Support No Auto MDIX Support Yes Suspend Mode Support Yes Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.4 Driver Required No			
Dock Connectors VGA, HDMI, Mini DisplayPort, (2) USB-A 3.0, RJ45, USB-C PD Charging/Data Side A - Connector 1 USB C (MALE) Side B - Connector 1 HD15 (FEMALE); HDMI (FEMALE); MINI DISPLAYPORT (FEMALE) Side B - Connector 2 (2) USB A (FEMALE); USB C (FEMALE) Side B - Connector 3 RJ45 (FEMALE) FEATURES & SPECIFICATIONS USB Hub Ports Yes Number of USB Hub Ports 3 USB Specification USB 3.0 (up to 5 Gbps); USB 3.2 Gen 1 (up to 5 Gbps) Ethernet Support Yes UASP Support No Auto MDIX Support Yes Suspend Mode Support Yes Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.4 Driver Required No			
Side A - Connector 1 USB C (MALE) Side B - Connector 1 HD15 (FEMALE); HDMI (FEMALE); MINI DISPLAYPORT (FEMALE) Side B - Connector 2 (2) USB A (FEMALE) Side B - Connector 3 RJ45 (FEMALE) FEATURES & SPECIFICATIONS USB Hub Ports Yes Number of USB Hub Ports 3 USB Specification USB 3.0 (up to 5 Gbps); USB 3.2 Gen 1 (up to 5 Gbps) Ethernet Support Yes UASP Support No Auto MDIX Support Yes Full Duplex Support Yes Suspend Mode Support Yes Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.4 Driver Required No	Number of Ports		
Side B - Connector 1 HD15 (FEMALE); HDMI (FEMALE); MINI DISPLAYPORT (FEMALE) Side B - Connector 2 (2) USB A (FEMALE); USB C (FEMALE) Side B - Connector 3 RJ45 (FEMALE) FEATURES & SPECIFICATIONS USB Hub Ports Yes Number of USB Hub Ports 3 USB Specification USB 3.0 (up to 5 Gbps); USB 3.2 Gen 1 (up to 5 Gbps) Ethernet Support Yes UASP Support No Auto MDIX Support Yes Suspend Mode Support Yes Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.4 Driver Required No	Dock Connectors	VGA, HDMI, Mini DisplayPort, (2) USB-A 3.0, RJ45, USB-C PD Charging/Data	
Side B - Connector 2 (2) USB A (FEMALE); USB C (FEMALE) FEATURES & SPECIFICATIONS USB Hub Ports Yes Number of USB Hub Ports 3 USB Specification USB 3.0 (up to 5 Gbps); USB 3.2 Gen 1 (up to 5 Gbps) Ethernet Support Yes UASP Support No Auto MDIX Support Yes Full Duplex Support Yes Suspend Mode Support Yes Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.4 Driver Required No	Side A - Connector 1	USB C (MALE)	
FEATURES & SPECIFICATIONS USB Hub Ports Yes Number of USB Hub Ports 3 USB Specification USB 3.0 (up to 5 Gbps); USB 3.2 Gen 1 (up to 5 Gbps) Ethernet Support Yes UASP Support No Auto MDIX Support Yes Suspend Mode Support Yes Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.4 Driver Required No	Side B - Connector 1	HD15 (FEMALE); HDMI (FEMALE); MINI DISPLAYPORT (FEMALE)	
FEATURES & SPECIFICATIONS USB Hub Ports Number of USB Hub Ports 3 USB Specification USB 3.0 (up to 5 Gbps); USB 3.2 Gen 1 (up to 5 Gbps) Ethernet Support Yes UASP Support No Auto MDIX Support Yes Full Duplex Support Yes Suspend Mode Support Yes Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.4 Driver Required No	Side B - Connector 2	(2) USB A (FEMALE); USB C (FEMALE)	
USB Hub Ports Yes Number of USB Hub Ports 3 USB Specification USB 3.0 (up to 5 Gbps); USB 3.2 Gen 1 (up to 5 Gbps) Ethernet Support Yes UASP Support No Auto MDIX Support Yes Full Duplex Support Yes Suspend Mode Support Yes Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.4 Driver Required No	Side B - Connector 3	RJ45 (FEMALE)	
Number of USB Hub Ports 3 USB Specification USB 3.0 (up to 5 Gbps); USB 3.2 Gen 1 (up to 5 Gbps) Ethernet Support Yes UASP Support No Auto MDIX Support Yes Full Duplex Support Yes Suspend Mode Support Yes Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.4 Driver Required No	FEATURES & SPECIFICATIONS		
USB Specification USB 3.0 (up to 5 Gbps); USB 3.2 Gen 1 (up to 5 Gbps) Ethernet Support Yes UASP Support No Auto MDIX Support Yes Full Duplex Support Yes Suspend Mode Support Yes Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.4 Driver Required No	USB Hub Ports	Yes	
Ethernet Support Yes UASP Support No Auto MDIX Support Yes Full Duplex Support Yes Suspend Mode Support Yes Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.4 Driver Required No	Number of USB Hub Ports	3	
Ethernet Support Yes UASP Support No Auto MDIX Support Yes Full Duplex Support Yes Suspend Mode Support Yes Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.4 Driver Required No	USB Specification	USB 3.0 (up to 5 Gbps); USB 3.2 Gen 1 (up to 5 Gbps)	
Auto MDIX Support Yes Full Duplex Support Yes Suspend Mode Support Yes Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.4 Driver Required No	Ethernet Support		
Full Duplex Support Yes Suspend Mode Support Yes Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.4 Driver Required No	UASP Support	No	
Suspend Mode Support Yes Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.4 Driver Required No	Auto MDIX Support	Yes	
Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.4 Driver Required No	Full Duplex Support	Yes	
Displayport Specification 1.2 HDCP Specification 1.4 Driver Required No	Suspend Mode Support	Yes	
HDCP Specification 1.4 Driver Required No	Remote Wakeup Support	No	
Driver Required No	Displayport Specification	1.2	
	HDCP Specification	1.4	
Recommended Category Cable Cat6 Cables	Driver Required	No	
	Recommended Category Cable	Cat6 Cables	



STANDARDS & COMPLIANCE		
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	3-year limited warranty	



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.