

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

# USB-C to DVI Adapter Cable, 3 ft. (0.91 m)

MODEL NUMBER: U444-003-D







Connects your existing DVI monitor or projector to the USB-C or Thunderbolt 3 port on your tablet, laptop, notebook, smartphone or PC.

### Features

## Connects a DVI Display to Your USB-C or Thunderbolt 3 Device

- Compatible with USB-C or Thunderbolt 3 source devices that support USB DisplayPort Alternate Mode
- Ideal for giving video presentations, editing multiple documents or streaming 1080p video for digital signage
- Supports USB 3.1 Gen 1 data transfer rates up to 5 Gbps

#### **Common Applications**

- Extends video from your primary display to another
- Duplicates the same video on 2 displays
- Converts a secondary display to your primary display

#### Crystal-Clear 1080p Video

- Supports HD video resolutions up to 1920 x 1080 (1080p) @ 60 Hz
- Supports 36-bit Deep Color (12 bits per channel)
- Supports DVI digital transfer rates of 6.75 Gbps (2.25 Gbps per channel)

#### **Reversible USB-C Connector**

• Fumble-free reversible USB-C plug connects in either direction for quick connection every time

#### **Premium Construction**

- Gold-plated connectors and contacts for maximum conductivity and minimum data loss
- · Foil and braid shielding protects against EMI/RFI line noise that can distort or destroy data

#### **Highlights**

- Supports USB DisplayPort
   Alternate Mode for transmitting
   video
- Supports HD video resolutions up to 1920 x 1080 (1080p) @ 60 Hz
- Supports USB 3.1 Gen 1 data transfer rates up to 5 Gbps
- Reversible USB-C plug connects in either direction
- Plug-and-play operation with no software or drivers required
- Note: This cable is unidirectional. Will only work from a USB-C port to DVI port

#### **System Requirements**

- Source device with USB-C or Thunderbolt 3 port that supports USB DisplayPort Alternate
   Mode
- Display device with DVI input

#### **Package Includes**

U444-003-D USB 3.1 Gen 1
 USB-C to DVI Adapter Cable
 (M/M), 3 ft.



- Integral strain relief helps cable and connectors move freely without stress or cracking
- Durable PVC jacket designed to last a long time

#### Ready for Instant Use

- Plug-and-play operation with no software, drivers or external power required
- 3 ft. length easy to manage in crowded environments
- Backward compatible with non-1080p displays

# **Specifications**

OVERVIEW	
UPC Code	037332202499
Technology	DVI; USB; USB 3.1 (Gen 1)
VIDEO	
Max Supported Video Resolution	DVI: 1920 x 1080 (1080p) @ 60Hz
INPUT	
Bus Powered	Yes
Product Length (in.)	36
Product Length (cm.)	91.44
Product Length (ft.)	3
Product Length (m.)	0.91
BATTERY	
Battery Charging (5V/1.5A Port)	No
PHYSICAL	
Color	Black
Cable Jacket Rating	VW-1
Cable Length (ft.)	3
Cable Length (m)	0.914
Material of Construction	PVC, ABS
Shipping Dimensions (hwd / cm)	22.86 x 17.78 x 1.27
Shipping Dimensions (hwd / in.)	9.00 x 7.00 x 0.50
Shipping Weight (kg)	0.08
Shipping Weight (lbs.)	0.17





Polybag	
0.08	
0.17	
ENVIRONMENTAL	
32 to 113 F (0 to 45 C)	
14 to 158 F (-10 to 70 C)	
1.7 BTU/Hr	
0.5	
10% to 85% RH, Non-Condensing	
5% to 90% RH, Non-Condensing	
CONNECTIONS	
USB C (MALE)	
DVI-D DUAL-LINK (MALE) (WIRED TO DVI-D SINGLE-LINK)	
Gold	
FEATURES & SPECIFICATIONS	
1.3	
USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)	
No	
STANDARDS & COMPLIANCE	
Tested to CE, FCC, RoHS, REACH	
WARRANTY	
3-year limited warranty	

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>