

Pro L20000UNL WUXGA 3LCD Laser Projector Without Lens

Contact Us 800.463.7766

Mon-Fri 7am-4pm PT



Premium large-venue WUXGA laser projector with 20,000 lumens.

The Pro L20000UNL combines a laser light source and 3-chip, 3LCD technology for powerful, lifelike images, delivering outstanding brightness in a remarkably compact form factor. A premium large-venue projector, it features Full HD WUXGA resolution and 20,000 lumens of color/white brightness¹ for ultra bright, vivid color. Its laser light engine and electrostatic air filter provide virtually maintenance-free operation for up to 20,000 hours². With two interface slots designed to accommodate a wide range of inputs, the Pro L20000UNL provides the ultimate in connectivity. And, it supports optional lenses (sold separately), including a zero-offset ultra short-throw lens. Projector also available in white.

Model: V11H833820



Ultra bright, vivid color

20,000 lumens color/white brightness¹; advanced 3-chip, 3CLD technology

Exceptional widescreen display

Full HD WUXGA (1920 x 1200) resolution; accepts 4K content and provides 2.3 million pixels on screen

Solid-state laser light source

with electrostatic air filter for up to 20,000 hours of virtually maintenance-free operation²

Wide range of optional lenses (sold separately)

including a zero-offset ultra short-throw lens

Powerful

outstanding brightness from a remarkably compact large-venue projector

Advanced connectivity

two interface slots accommodate a wide range of inputs

- **Designed for demanding environments** — features a sealed light source and optical engine for outstanding durability for live events and fixed installations
- **Dynamic projection capabilities** — with advanced tools like tiling assist, Edge Blending and auto-color adjustment for fast installation; free software for multi-projector setup
- **Bold, vibrant images** — supports High Dynamic Range (HDR) via HDR10 (PQ) and Hybrid Log Gamma (HLG); BT.709 color space
- **Mechanical shutter** — protects against damage from external laser lights
- **Frame interpolation** — ideal for fast-moving images
- **Wide lens shift** — optimized lens and optical engine design

Eco Features

- RoHS compliant
- Recyclable product³
- Epson America, Inc. is a SmartWay™ Transport Partner⁴

Better Products for a Better Future™

For more information on Epson's environmental programs, go to www.epson.com/environment



Specifications Projector:

High-aperture Epson® 3LCD, 3-chip technology

Projection Method:

Front/rear/ceiling mount

Driving Method:

Poly-silicon TFT Active Matrix

Native Resolution:

WUXGA (1920 x 1200)

Resolution on Screen:

WUXGA / 2.3 million pixels

Pixel Number in Device:

2,304,000 pixels (1920 x 1200) x 3 chips

Signal Input:

Maximum display resolution 1920 x 1200.

Display resolution 1920 x 1200 pixels

Color Brightness - Color Light Output:

Color Light Output: 20,000 lumens¹

White Brightness - White Light Output:

White Light Output: 20,000 lumens¹

Aspect Ratio:

16:10, 16:9, 4:3

Brightness Uniformity:

90%

Pixel Arrangement:

Cross stripe

Contrast Ratio:

2,500,000:1

Color Reproduction:

Up to 1.07 billion colors

Light Source Life:

20,000 hours (Normal); 30,000 hours (Extended)²

Illumination Technology:

Laser Diode

General:

Operating Temperature:

32 ° to 113 ° F (0 ° to 45 ° C)

Weight:

109.3 lb (without standard lens, not included)

Security:

Security cable hole, Kensington lock provision

Projection Lens:

Type:

Powered shift/focus/zoom (ELPLM15 Lens)

F-number:

1.8 – 2.35 (ELPLM15 Lens)

Focal Length:

36.0 – 57.4 mm (ELPLM15 Lens)

Zoom Ratio:

Optical zoom 1 – 1.6x (ELPLM15 Lens)

Throw Ratio Range:

1.57 – 2.56 (ELPLM15 Lens)

Lens Shift:

Vertical: ± 60 percent; Horizontal: ± 18 percent (ELPLM15 Lens)

Projector Details:

Input Signal:

Input Video Signal (HDMI, DVI-D and HDBaseT ports) 480i/480p/576i/576p/720p/1080i/1080p/3840 x 2160/4096 x 2160

Interfaces:

- 3G-SDI x 1 (SDI out x 1 - Active through)
- HDBaseT x 1
- 5-BNC
- VGA x 1

Interface (Slot 1)

- ELPIF01 (included from factory)
- DVI-D x 1
- HDMI® x 1 (HDCP2.2)
- DC Out (500 mA)

Interface (Slot 2)

- Blank from factory
- Interface Card (optional)
- ELPIF03
- Display Port x 2 (DP 20p)

Other

- USB connector Type B x 1: for Firmware update, Copy OSD Settings
- USB connector Type A x 1: for Firmware update, Copy OSD Settings, DC Out 900 mA
- Monitor out: Mini D-sub 15-pin x 1
- Serial: RS-232c x 1
- Remote: Stereo mini
- Wire LAN x 1 etherCON

Fan Noise:

45 dB (Normal Mode); max. 38 dB (Quiet Mode)

Projector Dimensions:

Including feet:

24.4" x 14.1" x 31.1" (620 x 358.5 x 790 mm)

Remote Control:

Features:

Power, Search Selection, Lens Shift, Zoom, Focus, Test Pattern Selection, Shutter, Freeze, User ID, Auto, Aspect, Color Mode, Menu, Slot 1, Slot 2 and more

Operating Distance:

49 ft

Operating Angle:

Right/Left: Front: ± 50 degrees; Rear: ± 40 degrees

Upper/Lower: Front: ± 50 degrees; Rear: $+30$ degrees

Power:

Power Supply Voltage:

100 – 240 V $\pm 10\%$, 50/60 Hz AC; Requires 200-240 V for full spec. operation

Power Consumption:

1860 W (Normal Mode)

1123 W (Extended Mode)

2.0 W Standby (Communication on)

0.5 W Standby (Communication off)
