EPSON EXCEED YOUR VISION

SPECIFICATION SHEET

BrightLink® 770Fi 1080p 3LCD Interactive Ultra Short Throw Lamp-Free Laser Display



Product shown with mount, sold separately.

The large, easy-to-read display for captivating interactive lessons.

Best-in-Class Color Brightness¹ with 3-chip 3LCD technology - 4,100 lumens of color and white brightness²

Incredible image quality - Full HD 1080p resolution for amazing clarity and readability

See more, do more — ultra wide 21:9 and 16:6 display with split screen³ support allows for simultaneous display of whiteboard and digital content

Interactive display up to 100" — provides up to 75 percent more interactive space vs. 75" interactive panels for a low cost per square inch

Multi-user capability for easy collaboration — dual-pen-enabled interactivity; optional slim design touch module allows up to eight users to collaborate at once

Convenient connectivity — works with popular applications and devices including Microsoft[®] Office 365 and Google[®] Workspace

PC-free digital whiteboard — draw, save, print and email without a computer; also share whiteboard content to other networked BrightLink projectors⁴

No lamps to replace ever — solid-state, 20,000-hour, virtually maintenance-free laser light source⁵

Connect and cast from up to 50 devices⁶ — free downloadable Epson iProjection[™] software makes it easy to cast wirelessly from Chromebooks, iOS[®] and Android[™] devices, Mac[®] computers and PCs⁶; with moderator feature⁷, teachers never lose control of the displayed content

Easy-to-use interactive Home screen — with image preview capability makes source selection easier than ever





Education

Education

:PSO EXCEED YOUR VISION

BrightLink® 770Fi 1080p 3LCD Interactive Ultra Short Throw Lamp-Free Laser Display

Specifications

Projection System Epson® 3-chip 3LCD technology Projection Method Front/rear/wall mount/table mount Driving Method Epson Poly-Silicon TFT Active Matrix Pixel Number 2,073,600 dots (1920 x 1080) x 3 Color Brightness¹ Color Light Output: 4,100 lumens White Brightness¹ White Light Output: 4,100 lumens Native Aspect Ratio 16:9, Supported Aspect Ratios: 4:3, 16:10.21:9 Native Resolution 1920 x 1080 (1080p HD) LCD 0.62' Light Source Laser Diode Laser Light Source Life² Up to 20,000 hours, Extended Mode: Up to 30,000 hours Image Size (projection distance) With ELPMB62 Mount: 65" – 100" (14.01" – 22.7") 16:9 60" – 110" (13.9" – 27.24") 16:6 56.8" – 110" (14.1" – 27.2") 21:9 Keystone Correction (Manual) Horizontal: ±3 degrees; Vertical: ±3 degrees USB Plug 'n Play Mac OS® 10.8/10.9/10.10/10.11/10.12/ 10.13/10.14/macOS 10.15.x, 11.0/12.0 USB Plug 'n Play for Windows® Windows 7/Windows 8/ Windows 10, Windows 11 Contrast Ratio Up to 2,500,000:1 Color Reproduction Up to 1.07 billion colors Wireless Specifications

Supported Security Modes OPEN, WPA2/WPA3-PSK, WPA2/WPA3-EAP Supported EAP Type: PEAP, PEAP-TLS, EAP-TLS, EAP-Fast Supported Speeds IEEE 802.11 b: 11 Mbps* (2.4 GHz) IEEE 802.11 g: 54 Mbps* (2.4 GHz) IEEE 802.11 n: 72.2 Mbps* (2.4 GHz) IEEE 802.11 a: 54 Mbps* (5 GHz) IEEE 802.11 n: 150 Mbps* (5 GHz) IEEE 802.11 ac: 325 Mbps* (5 GHz) Maximum speed and range are achievable when used with

the same Enhanced Mode technology. Actual data rates features and performance may vary depending on your computer system, the environment and other factors.

Projection Lens

Type Manual focus F-Number 1.6 Focal Length 3.7 mm Throw Ratio Range 0.25 - 0.35 Zoom Ratio Digital zoom 1.00 - 1.35x

Other

Speaker 16 W monaural Operating Temperature 41 °F to 104 °F (5 °C to 40 °C) Power Supply Voltage $100 \text{ V} - 240 \text{ V} \pm 10\%$, 50/60 Hz **Power Consumption** Quiet Mode: 214 W, Normal Mode: 277 W Standby (Communication On): 2.0 W Standby (Communication Off): 0.5 W **Fan Noise** Quiet Mode: 27 dB, Normal Mode: 37 dB

Interfaces

HDMI®: 3x Composite Video: 1x RCA (yellow) Audio In: 3x Mini stereo Audio Out: 1x Mini stereo Microphone In: 1x Mini stereo 1x Type USB-A (Powered 5 V, 2 A) 2x Type USB-B (USB display with audio and interactivity) Serial: 1x RS-232c Monitor Out/Computer: 1x D-Sub 15-pin Computer: 1x D-Sub 15-pin Integrated Wireless LAN: 802.11 b/g/n/ac Interactive Synchronization Mini Stereo In Interactive Synchronization Mini Stereo Out Touch Unit Connection Port

Other (Continued)

Security Kensington lock provision, security anchor bar, password-protection function

Interactivity

Interactive Technology Infrared, 850 nm Interactive Area (Image Size) 100" diagonal (16:9); 110" diagonal (16:Ò)

Interactive Modes Computer Interactivity, PC-Free and Whiteboard Annotation Mode; Pen: Dual User; Finger Touch: Up to 6 points of touch

PC-Free Annotation 2 pens and 6 fingers Interactive Tools Epson Easy Interactive Tools; 2 pens and 6 fingers

PC Interactive Sources USB, HDMI, Computer 1, Computer 2, LAN, Miracast

PC-Free Annotation Devices Document Cameras, DVD/ Blu-ray Disc[™] players, iPod[®]/iPad[®] devices, Chromebooks Calibration Method Automatic or Manual

Interactive Connectivity USB cable for non-networked LAN Interactive Software Requirements

Epson Easy Interactive Driver (required for Mac) Mac: Mac OS X® 10.12/10.13/10.14/macOS 10.15.x, 11.0/12.0/13.0

Epson Easy Interactive Tools for Windows and Mac System Compatibility Microsoft, Windows 8/8.1, Windows 10, Windows 11, Windows 7 SP1 (all editions except for Starter), Mac OS 10.11/10.12/10.13/10.14/ macOS 10.15.x, 11.0/12.0/13.0

Gestures Requires Windows 7 or later, or Mac OS 10.12 or later **GoBoard Software Requirements** Windows 10 version 1803 or later

CPU quad-core 2 GHz RAM DDR3 8 GB

Camera and microphone (for AV conferences, voice commands) Dimensions (W x D x H)

Excluding Feet 14.1" x 15.6" x 5.3'

Weight 13.2 lb

Remote Control

Features Computer, HDMI, USB, LAN, Source Search, Power, Aspect, Color Mode, Volume, E-Zoom, AV Mute, Freeze, Menu, Auto, Enter, Esc, User, ID, Default, Home, Split



Additional USB-A port on side of display.

Remote Control (Continued)

Operating Distance 19.7 ft (6 m)

Operating Angle

Rear: Right/Left: -55 to +55 degrees, Upper/Lower: +75 to +15 dearees Front: Right/Left: -30 to +30 degrees, Upper/Lower: 0 to +60

dearees **Eco Features**

Energy-efficient 3LCD light engine **BoHS** compliant Recyclable product[®]

Epson America, Inc. is a SmartWay® Transport Partner9

Support

Service Programs 3-year projector limited warranty, Epson Road Service Program, dedicated toll-free support

What's in the Box

BrightLink 770Fi Ultra Short Throw Interactive Display, Quick Start Guide, 6' power cable, 16' USB A/B cable, projector remote control, 2x interactive pens, 4x soft pen tips, 2x hard pen tips, pen tray, 2x AA batteries (for interactive pens), 2x AA batteries (for remote), projector feet, corner markers, magnets for corner markers, 1-year license key for BrightLink GoBoard Software

Ordering Information

BrightLink 770Fi	V11HA7802C
Air Filter	V13H134A6C
Ultra Short Throw Wall Mount (ELPMB62)	V12H406A05
Interactive Touch Module	V12H007A23
PowerLite® Pilot™ 3 (ELPCB03)	V12H92702C
Active Speakers (ELPSP02)	V12H46702C
Wireless 802.11 b/g/n LAN Unit (ELPAP11)	V12H005A02
100" Whiteboard (16:9)	V12H006A02
Interactive Pen A (orange)	V12H77601C
Interactive Pen B (blue)	V12H77501C
Replacement Pen Tips (hard/Teflon™)	V12H77501C
Replacement Pen Tips (soft/felt)	V12H77501C
DC-07 Document Camera	V12H77501C
DC-07 Document Camera	V12H759020
DC-13 Document Camera	V12H757020
DC-21 Document Camera	V12H758020

1 Color brightness measured per IDMS 15.4. Additional colors and picture modes tested. Top-selling Epson 3LCD projectors vs. comparable top-selling 1-chip DLP projectors based on NPD sales data for October 2019 – September 2020. COLOR BRIGHTNESS WILL VARY BASED ON USAGE CONDITIONS. I 2 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15 4; white light output measured in accordance with ISO 21118. | 3 Consult your user manual for split screen input combinations. | 4 Networked Screen Sharing is supported by the following models: BrightLink 725Wi, 735Fi, 760Wi, 770Fi, 1480Fi and 1485Fi. | 5 No required maintenance for the light source for up to 20,000 hours. Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m³ of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period. I 6 For wireless functionality, including via the Epson iProjection App, the projector must be configured on a network, either through the Ethernet port on the projector (check model specifications for availability) or via a wireless connection. Check your owner's manual to determine if a wireless LAN module must be purchased separately to enable a wireless connection. Not all Epson projectors are able to be networked. The Epson iProjection App does not support all files and formats. See www.epson.com for details. 7 Moderator control, connecting via QR code and projector remote are not available on Epson iProjection for Chromebooks. | 8 For convenient and reasonable recycling options, visit www.epson.com/recycle | 9 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency

Learn more about how our products can empower your institution. Visit us at www.epson.com/foreducation

Better Products for a Better Future" eco.epson.com



3131 Katella Ave., Los Alamitos, CA 90720



www.epson.ca

1915

Specifications and terms are subject to change without notice. EPSON and PowerLite are registered trademarks EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future and Epson iProjection are trademarks of Seiko Epson Corporation. BrightLink is a registered trademark and GoBoard and Pilot are trademarks of Epson America, Inc. iPad, iPod, Mac, macOS and OS X are trademarks of Apple Inc., registered in the U.S. and other countries. Google is a registered trademark and Android and Chromebook are trademarks of Google LLC. Microsoft Windows and Windows Vista are either registered trademarks or trademarks of Microsoft Corporation in the United States and other countries. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. Miracast® is a registered trademark of Wi-Fi Alliance®. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2022 Epson America, Inc. Com-SS-Oct-13 CPD-62990 12/22



www.epson.com

Contact: