#### **SPECIFICATION SHEET**

## **EPSON**<sup>®</sup>

### **EB-PQ2010B**

10,000-Lumen 4K 3LCD Laser Projector



### The world's smallest and lightest 10,000-lumen 4K projector<sup>1</sup>.





The world's smallest and lightest 10,000-lumen 4K projector<sup>1</sup> — produces incredibly bright images with a light, compact and energy efficient design

 $\mbox{Incredible color}$  — Epson 3-chip 3LCD technology produces 10,000 lumens of equal white and color brightness^2

**4K resolution on-screen** — leverages Epson's 4K Crystal Motion technology, thermo-controlled panel and double micro-lens array for crystal clear image quality that fully realizes 4K resolution (3840 x 2160)

**Low-maintenance design** — virtually maintenance-free 20,000-hour laser light source and air filter<sup>3</sup>; optional external air filter is available for high-dust environments

**Stunning image quality** — high native contrast ratio for deep blacks; 50 percent improvement over the already high contrast ratio found with the current Epson EB-PU Series; frame interpolation for fast moving objects; HDR support<sup>4</sup> and scene adaptive gamma correction

**Simplified installation** — 10 optional powered lenses (sold separately) including ultra short throw .35 throw lens with a unique zero offset design for installation flexibility; projector compatible with existing Epson lens family

**Enhanced connectivity** — HDMI<sup>®</sup> two in and one out; 12G-SDI in/out for daisy chaining and signal monitoring; features automatic input switching when input signal is disrupted

Low latency performance and high frame rate support — high-speed graphics chip and panel drive technology enable high frame rate 4K playback

**Optional attachable PixAlign™ external camera** — access powerful automated tools including edge blending assist<sup>5</sup>, stacking assist function<sup>5</sup>, auto color calibration<sup>6</sup> and screen matching<sup>6</sup> with or without a connected PC and router

**Efficient setup and management** — control multiple projectors in a single, large space with Epson Projector Professional Tool (EPPT app)<sup>7</sup>; easily manage your installed inventory using Epson Projector Management – Connected (EPM-C)<sup>8</sup> from any device with a Web browser

# **EPSON**<sup>®</sup>

#### **Specifications**

Projection System High-aperture Epson 3-chip 3LCD technology

Projection Method Front/rear/ceiling mount Driving Method Poly-Silicon TFT Active Matrix Pixel Number 2,073,600 pixels (1920 x 1080) x 3 chips Signal Input Maximum Display Resolution: 4096 x 2160 pixels (resizing display)

Native Resolution 1080p with 4K Crystal Motion (1920 x 1080 x 4)

Resolution on Screen 4K UHD (3840 x 2160) Aspect Ratio Supports 4:3, 16:10, 16:9\*, 21:9\* \* With vertical image shift control within letterbox area. Pixel Arrangement Cross stripe

Color Brightness<sup>2</sup> Color Light Output: 10,000 lumens White Brightness<sup>2</sup> White Light Output: 10,000 lumens Contrast Ratio Up to 5,000,000:1 (Dynamic Contrast: On) Brightness Uniformity (Typical) 85%

Color Reproduction Up to 1.07 billion colors Keystone Correction

Vertical: ±45 degrees; Horizontal: ±30 degrees Illumination Technology Laser Phosphor Light Source Life<sup>3</sup> 20,000 hours (Normal Mode) 30,000 hours (Extended Mode)

#### Projection Lens (Standard)

Visit www.epson.com for information on optional lenses. **Standard Lens** ELPLM15 (sold separately) **Type** Powered shift/focus/zoom **F-Number** 2.0 – 2.1 **Focal Length** 14.8 mm – 17.7 mm **Zoom Ratio** Optical Zoom: 1.0 – 1.6 **Throw Ratio** Range 1.52 – 2.47 **Lens Shift** Vertical:  $\pm 60\%$ ; Horizontal:  $\pm 18\%$ 

#### **Other Features**

Operating Temperature 32 °F to 122 °F (0 °C to 50 °C) Power Supply Voltage 100 V – 240 V ±10%, 50/60 Hz AC Power Consumption 640 W (Normal/Custom) 501 W (Quiet/Extended) 2.0 W Standby (Network Standby)

0.5 W Standby (Energy Saving) **Fan Noise** 39 dB (Normal Mode), 29 dB (Eco Mode) **Security** Security cable hole, lens lock, Kensington<sup>®</sup> lock provision, wireless LAN unit lock

#### Video I/O

Input Signal Input Video Signal (HDMI and HDBaseT<sup>®</sup> ports): 480i/480p/576i/576p/720p/1080i/1080p/3840 x 2160/ 4096 x 2160

Max PC Graphics: 2560 x 1600/3440 x 1440

Auto Power On Signal Detection on HDMI/Plug-In Detection (HDMI) Sleep Mode Yes (with timer)

HDMI CEC Control Yes

#### Interfaces

12G-SDI In/Out HDMI (HDCP 2.3) x 2/HDMI Out x 1 HDBaseT x 1 Variable Audio Out: Mini Stereo x 1 USB Type-A for Wireless LAN (optional) USB Connector Type-B x 1 Serial: RS-232c x 1 Remote Stereo Mini Network: RJ-45



#### Dimensions (W x D x H)

Excluding Feet 21.5" x 17.2" x 6.5" (545 mm x 436 mm x 164 mm) Weight 41.4 lb (18.8 kg)

#### **Remote Control**

Features Power, Source Search Selection, Lens Shift, Zoom, Focus, Test Pattern Selection, Shutter, Freeze, ID, Color Mode, Number, E-Zoom, Volume, Menu, Enter, ESC, Pointer Functions, Blend Guides, Multi-Projection, Color Tone Adjust and Memory Operating Angle

Angle Front: Right/Left: 60 to +60; Upper/Lower: +30 to 20 degrees Angle Rear: Right/Left: 30 to +30; Upper/Lower: +50

Angle Kear: Right/Left: 30 to +30; Upper/Lower: +50 to +10 degrees **Operating Distance** 98 ft

#### Eco Features

ECO Featu

RoHS compliant

End-of-life options available<sup>9</sup> Epson America, Inc. is a SmartWay<sup>®</sup> Transport Partner<sup>10</sup>

#### Limited Warranty and Service

Warranty Three-year limited or 20,000 hours, whichever comes first, in the U.S. and Canada

Service Toll-free telephone support, Monday through Friday Epson Connection<sup>SM</sup>

Pre-Sales Support (U.S. and Canada): 800-463-7766 Website: www.epson.com

#### Enson Preferred<sup>™</sup> Plus Extended Service Plan

Epoli i loi liuo Extenueu oci	
3-Year Upgrade to Next-Business-Day Whole Unit	
Exchange <sup>11</sup> for Years 1-3	EPPPRJPQ3
5-Years Next-Business-Day Whole Unit Exchange <sup>11</sup>	
for Years 1-5	EPPPRJPQE5
Other extended service plans may be available.	

#### What's Included

EB-PQ2010B projector, power cable, remote control with 2 batteries, cable cover, lens connector cap, quick reference guide and warranty sheet

#### **Ordering Information** EB-PQ2010B V11HB02820 Air Filter (ELPAF46) V13H134A46 External Air Filter (ELPAF63) V13H134AD0 Ultra Short Throw Lens (ELPLX02S) V12H004X0B Ultra Short Throw Lens - White (ELPLX02WS) V12H004Y0B V12H004UA3 Short Throw #1 Zoom Lens (ELPLU03S) Short Throw #2 Zoom Lens (ELPLU04) V12H004U04 Wide Throw #1 Zoom Lens (ELPLW05) V12H004W05 Wide Throw #3 Zoom Lens (ELPLW08) V12H004W08 Wide Throw #2 Zoom Lens (ELPLW06) V12H004W06 Middle Throw #2 Zoom Lens (ELPLM15) V12H004M0F Middle Throw #3 Zoom Lens (ELPLM10) V12H004M0A Middle Throw #4 Zoom Lens (ELPLM11) V12H004M0B Long Throw Zoom Lens (ELPLL08) V12H004L08 Rigging Frame (ELPMB59) V12H996A01 Wireless LAN Module (ELPAP11) V12H005A02 Projector Ceiling Mount (ELPMB67) V12HA54010 Suspension Adapter (ELPFP15) V12HA55010 PixAlign Camera (ELPEC01) V12HA46010

1 Comparison based on 4K projectors rated at 10,000 lumens. Lumens, resolution, size and weight based on the manufacturers' online specifications and industry-available data as of October 2023. | 2 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. | 3 No required maintenance for the light source and filter for up to 20,000 hours (Normal Mode), 30,000 hours (Extended Mode). Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m<sup>3</sup> of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period. | 4 HDR performance available with select third-party devices. For more information, see www.epson.com/hdrcompatibility | 5 Requires Epson external camera for each projector. | 7 Mac<sup>®</sup> and PC only. | 8 Requires one on-site PC with Epson Projector Connected Agent installed. | 9 For convenient and reasonable recycling options, visit www.epson.com/recycle | 10 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency. | 11 Product comes with a 3-year limited warranty with the option to purchase extended service plans up to a total of 5 years of continuous coverage. Extended service plan must be purchased within 90 days of hardware. See individual service plan for details. Expedited shipping not available in all areas. Orders must be placed and processed by 1 p.m. Pacific Time, Monday through Friday, excluding holidays.

See the latest innovations from Epson Business Solutions at www.epson.com/forbusiness



Epson America, Inc. 3131 Katella Ave., Los Alamitos, CA 90720

**Epson Canada Limited** 185 Renfrew Drive, Markham, Ontario L3R 6G3 www.epson.com www.epson.ca

Specifications and terms are subject to change without notice. EPSON is a registered trademark of Seiko Epson Corporation. PixAlign, Epson Connection and Epson Preferred are trademarks of Epson America, Inc. Mac is a trademark of Apple Inc., registered in the U.S. and other countries. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2024 Epson America, Inc. CPD-64127R1 2/24

Page 2 of 2

#### Contact:

### EB-PQ2010B