

ULTRAWF

Frigidaire PureSource Ultra® Water and Ice Refrigerator Filter

AVAILABLE COLORS



MORE EASY-TO-USE FEATURES

Push to Lock & Release Easy Install

Always review your Use & Care Guide before installation, to install slide new filter into housing and push until it locks into place.

Keeps Great Tasting Water Flowing up to 6 Months

Replace your water filter every 6 months or 200 gallons, whichever comes first.

Water Quality Association Certified

Frigidaire Genuine Filters are certified by the Water Quality Association to WQA/ASPE/ANSI S 803 for sustainability.

NSF 42, 53 & 401 Certified to Filter Out Contaminants

Tested and certified by NSF International against NSF/ANSI Standards 42, 53 and 401 in PureSource Ultra for reduction of the claims on the Performance Data Sheet.

SAME GREAT FILTER, New Look

We have refreshed our packaging! Look for our berry-colored design on the package to know for certain your filter is authentic and sold by Frigidaire. As we transition, packaging may vary from blue to berry colors.

Easy Setup for Optimal Results

Always consult your fridge's Use & Care Guide and run water through the dispenser for approximately 3 minutes, or 1.5 gallons, to prime the filter before use. Discard the water.

SIGNATURE FEATURES



Make Safe Water Second Nature

Certified to reduce contaminants and keep great tasting water flowing for you and your family.¹



Purity You Can Trust

Know for certain your filter is a protector. Counterfeits and knockoffs put fridges and health at risk. Frigidaire Genuine Filters – the smarter, safer choice.



Every Drop Gives Back

Partnered on sustainability efforts, Frigidaire Genuine Filters save the cost of bottled water and cut back on plastic.



Filters Out up to 99% of Contaminants

Reduces Chlorine Taste & Odor, Particulates Class I, Cysts, Lead, Mercury, Pesticides, Insecticides, BPA, Asbestos, Pharmaceuticals and more.²

ULTRAWF

Frigidaire PureSource Ultra® Water and Ice Refrigerator Filter

FRIGIDAIRE

General Specifications

Alternate Part Number	241791601; 242017801; 242017805; 242294401; RENEWULTRAWF; SULTRAWF
Country of Origin	Singapore
Filter Location	Back Top-right
Filter Type	Water Filter
Flow Rate	0.5 gpm
Genuine Replacement Part	Yes
Installation Action	Push to lock
Item Package Quantity	1
Maximum Operating Temperature	100 F
Maximum Working Pressure	100 psi
Minimum Operating Temperature	33 F
Minimum Working Pressure	30 psi
Product Weight	1.14 lbs
Rated Capacity	200 Gallons
Recommended Change Frequency	3 - 6 Months
Power Type	
Installation Type	
Collection	Frigidaire

Safety Certifications and Approvals

NSF Certified	Yes
ANSI Certified	Yes

Dimensions and Volume

Retail Packaging Height	11 1/5"
Retail Packaging Width	2 2/5"
Retail Packaging Depth	2 3/10"
Volume	0.43 Cu. Ft.

Use and Care

	Installation and Care Instructions NOTICE: Review Frigidaire Refrigerator Use and Care Guide before installation and use of system. See fits models listing on Frigidaire.com. Fits all PureSource Ultra® and PureSource® 3 models manufactured by Frigidaire after 2009. 1. Push to release current filter, remove and discard. 2. Slide the new filter into the housing and push until it locks in place. 3. Run water through the dispenser for approximately 3 minutes, or 1.5 gallons, to prime the filter before use. Discard the water. 4. Replace every 6 months or 200 gallons (757 liters), whichever comes first.
Care Instructions	
Dishwasher Safe	No
Patent	
Intellectual Property	No

Note: For planning purposes only. Always consult local and national electric, gas and plumbing codes. Refer to Product Installation Guide for detailed installation instructions on the web at frigidaire.com / frigidaire.ca.

Specifications subject to change. Accessories information available on the web at frigidaire.com / frigidaire.ca

FRIGIDAIRE

USA • 10200 David Taylor Drive • Charlotte, NC 28262 • 1-800-FRIGIDAIRE • frigidaire.com
CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • frigidaire.ca

ULTRAWF
©2017 Electrolux Home Products, Inc.

