

MIW-SURGE-1G

MAX IN-WALL™ SINGLE GANG SURGE PROTECTION

Two AC receptacles provide power protection to remotely located devices. Fits most standard single gang plastic or metal boxes.



FEATURES

- Decora Faceplate Interface. This piece surrounds the receptacles and fits within a standard cover plates Decora cutout.
- Uses standard wiring device screw-hole.
- Both Outlets with Protect-or-Disconnect Circuitry.
- Bi-color Indicator LED.
Green = Power On
Red = Line Fault

INCLUDES

- Three Wire Nuts
- Two Mounting Screws, (Pre-installed)

- Provides power protection.
- Mounts behind electronic equipment.
- CSA Certified for code compliant installations.
- 3 Year Product Warranty

TECHNICAL SPECIFICATIONS

AC CIRCUIT

AC Outlets.....	2
Line Voltage.....	120V, 50/60Hz
Total Current Capacity.....	15A
UL 1449 2nd Ed. Suppressed Voltage Rating (@500A)	330V
UL 1449 3rd Ed. Voltage Protection Rating (@3000A).....	400V
Protection Modes.....	L-N, L-G, N-G
Energy Dissipation.....	1350 Joules
Protect-or-Disconnect Circuitry.....	Yes

Specifications subject to change without notice due to product upgrades and improvements.

SHIPPING INFORMATION

Single Pack Dimensions..	2.5"W x 2"D x 4.25"H
Single Unit UPC.....	0 50616 00885 3

Inner Pack Qty.....	6
Inner Pack UPC.....	30 050616 00885 4

Master Pack Qty.....	36
Master Pack UPC.....	50 050616 00885 8

MODEL: MIW-SURGE-1G

DESIGNED & ENGINEERED IN USA • MANUFACTURED IN CHINA



PFP Power By Panamax-Furman

www.panamax.com

www.furmansound.com

L-MIW-SURGE-1G 9/10